



BSKE080S120

General Description

概述



Specifically designed for Automotive applications, this SiC Power MOSFET utilizes the latest processing techniques to achieve extremely low on-resistance per unit area.

本产品是一款专为汽车应用设计的碳化硅功率MOSFET产品，采用了最先进的工艺技术，产品的单位面积导通电阻非常低。

Features

特点

- High Speed Switching with Low Capacitances
开关速度快，寄生电容小
- High Blocking Voltage with Low $R_{DS(on)}$
阻断电压高，开通电阻低
- 100% avalanche tested
100%通过雪崩测试
- Halogen Free and RoHS Compliant
无卤元素，符合 RoHS



Typical Applications

典型应用

- EV Charging
EV 充电
- DC-AC Inverters
DC-AC 转换器
- High Voltage DC/DC Converters
高压 DC/DC 变压器
- Power Factor Correction Modules
功率因子校正模块

Ordering Information

订货信息

Type 型号	$BV_{DSS}[V]$ 漏极-源极电压	$R_{DS(on)}[m\Omega]$ 导通电阻	$T_{jmax}[^{\circ}C]$ 最高结温	Marking 标记	Packing 封装外形
BSKE080S120	1200	80	175	080S120	TO247-4L



BSKE080S120

Maximum Rated Values

最大额定参数

Parameter 参数	Symbol 符号	Value 数值	Unit 单位
Drain-Source Voltage, $T_j \geq 25^\circ\text{C}$ 漏-源电压, $T_j \geq 25^\circ\text{C}$	V_{DSS}	1200	V
Drain Current(continuous)at $T_c=25^\circ\text{C}$ 常温下漏极电流(持续)	I_{D}	36	A
Drain Current(continuous)at $T_c=100^\circ\text{C}$ $T_c=100^\circ\text{C}$ 下漏极电流(持续)		25	
Pulsed Drain current, t_p limited by $T_{j\max}$ 集电极脉冲电流, 脉宽时间受 $T_{j\max}$ 限制	I_{DM}	80	
Gate-Source Voltage(dynamic: AC>1Hz) 栅极-源极电压(瞬态: AC>1Hz)	V_{GSmax}	-10V/+25V	V
Gate-Source Voltage(Static) 栅极-源极电压(稳态)	V_{GS}	-10V/+20V	V
Gate-Source Voltage (Recommended operational values) 栅极-源极电压(推荐工作电压)	V_{GSop}	-4/+18	V
Power Dissipation $T_c = 25^\circ\text{C}$ 常温耗散功率	P_{D}	238	W
Storage Temperature Range 储存温度范围	T_{stg}	-55 to +175	$^\circ\text{C}$
Solder Temperature (1.6mm from case for 10s) 焊接温度	T_{L}	260	
Operating junction temperature Range 工作结温	T_{J}	-55 to +175	
Mounting Torque 安装力矩	M_{d}	1 8.8	Nm lbf-in

Caution: These values must not be exceeded under any conditions.

注意: 任何条件下都不能超出上述值。

Thermal Resistance

热阻

Parameter 参数	Symbol 符号	Value 值	Unit 单位
Thermal Resistance, Junction to Case, Max. 结-管壳热阻	$R_{\theta\text{JC}}$	0.63	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient, Max. 结-环境热阻	$R_{\theta\text{JA}}$	40	



BSKE080S120

Electrical Characteristic at $T_j = 25^\circ\text{C}$ (unless otherwise specified)

$T_j=25^\circ\text{C}$ 时电学特性（除非特别声明）

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	
Static Characteristic 静态特性						
Drain to Source Breakdown Voltage 漏极-源极电压击穿电压	BV _{DSS}	V _{GS} =0V, I _D =100μA T _j =25°C	1200	-	-	V
Zero Gate Voltage Drain Current 栅源短路的漏极电流	I _{DSS}	V _{DS} =1200V, V _{GS} =0V T _j =25°C	-	0.5	100	μA
Gate to Body Leakage Current 栅极-源极漏泄电流	I _{GSS}	V _{GS} =20V, V _{DS} =0V	-	2.1	100	nA
Gate to Body Leakage Current 栅极-源极漏泄电流	I _{SGS}	V _{GS} =-10V, V _{DS} =0V	-	1	100	nA
Static Drain-source On Resistance(Fig.4) 漏极-源极通态电阻	R _{DS(on)}	V _{GS} =18V, I _D =20A T _j =25°C	-	80	100	mΩ
		V _{GS} =18V, I _D =20A T _j =175°C	-	120	-	
Gate Threshold Voltage 栅极-源极阈值电压	V _{GS(th)}	V _{DS} =V _{GS} , I _{DS} =5mA T _j =25°C	2	-	4	V
		V _{DS} =V _{GS} , I _D =5mA T _j =175°C	-	2.1	-	
Gate Resistance 栅极电阻	R _G	f=1MHz, V _{AC} =25mV	-	5	-	Ω

Dynamic Characteristic

动态特性

Input Capacitance 输入电容	C_{iss}	$V_{DS}=1000V,$ $f=1MHz, V_{GS}=0V,$ $V_{AC}=25mV$	-	827	-	pF
Output Capacitance 输出电容	C_{oss}		-	22	-	
Reverse Transfer Capacitance 反向传输电容	C_{rss}		-	1	-	
Total Gate Charge 栅极总电荷	$Q_{g(tot)}$	$V_{DS}=800V,$ $I_D=40A, V_{GS}=-4/18V,$ $R_L=20\Omega, I_{GS}=48.5mA$	-	79	-	nC
Gate-source Charge 栅-源电荷	Q_{gs}		-	40	-	
Gate-Drain Charge 栅-漏电荷	Q_{gd}		-	15	-	



BSKE080S120

Switching Characteristic at $T_j=25^\circ\text{C}$ (Inductive Load)

$T_j=25^\circ\text{C}$ 时开关特性（电感负载）

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	
MOSFET Characteristic MOSFET 特性						
Turn-on delay time 开通延迟时间	t _{d(on)}	V _{DS} =800V, V _{GS} =-4/18V, I _D =20A, R _{G(ext)} =20Ω, T _j =25°C	-	23	-	ns
Rise time 上升时间	t _r		-	13	-	
Turn-off delay time 关断延迟时间	t _{d(off)}		-	66	-	
Fall time 下降时间	t _f		-	35	-	
Turn-on Switching Energy 开通损耗	E _{on}	V _{DS} =800V, V _{GS} =-4/18V, I _D =20A, R _{G(ext)} =20Ω, L=500μH, T _j =25°C	-	588	-	μJ
Turn-off Switching Energy 关断损耗	E _{off}		-	162	-	

SOURCE-DRAIN DIODE CHARACTERISTICS

源极-漏极二极管特性

Source to Drain Diode Forward Voltage 源极-漏极正向电压	V_{SD}	$I_{SD}=10\text{A},$ $T_j=25^\circ\text{C}$	-	3.5	-	V
		$I_{SD}=10\text{A},$ $T_j=175^\circ\text{C}$	-	3.0	-	
Continuous Diode Forward Current 正向电流	I_S	$T_C=25^\circ\text{C}$	-	36	-	A

Notes:

a: Repetitive Rating : Pulse width limited by maximum junction temperature

b: Pulse Test : Pulse width $\leq 380\mu\text{s}$

c: Essentially independent of operating temperature

注:

a: 重复范围: 脉冲宽度受限于最大结温

b: 脉冲测试: 脉冲宽度 $\leq 380\mu\text{s}$

c: 本质上与工作温度无关



BSKE080S120

Electrical characteristics diagram

特性曲线

Figure 1. Output Characteristics $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 175^\circ\text{C}$




Figure 4. On-Resistance vs. Junction Temperature




Figure 5. On-Resistance vs. Drain Current





Figure 6. Transfer Characteristic for Various Junction Temperatures





BSKE080S120

Figure 7. Body Diode Characteristics for Various Junction Temperatures




Figure 8. Capacitances vs. Drain-Source Voltage




Figure 9. Threshold Voltage vs. Temperature




Figure 10. Continuous Drain Current Derating vs. Case Temperature




Figure 11. Gate Charge Characteristics





Figure 12. Maximum Power Dissipation Derating vs. Case Temperature





BSKE080S120

Figure 13 Forward Voltage vs. Junction Temperature




Figure 14. Clamped Inductive Switching Energy vs. Temperature




Figure 15. Switching Times vs. Junction Temperature




Figure 16. 3rd Quadrant Characteristic at -55°C





Figure 17. 3rd Quadrant Characteristic at 25°C





BSKE080S120

TO247-4L Packing Outline Dimensions:

TO247-4L 封装外形尺寸

Dim.	Mechanical Dimensions /mm	
	MIN	MAX
A	4.83	5.21
A1	1.9	2.16
B	1.07	1.33
B2	2.39	2.94
B4	1.07	1.6
C	0.55	0.68
D	23.25	23.65
D1	16.35	16.75
E	15.74	16.14
E4	13.06	13.46
F1	3.68	5.1
F3	2.35	2.65
e	2.34	2.74
e1	4.88	5.28
L	17.31	17.82
L1	3.97	4.37
ΦP2	3.50	3.70
S	6.05	6.27
Q	5.49	6.00

Note: The mold may vary little from different packaging plants, please refer to the actual product.
备注: 因封装厂的模具存在细微差异, 请以实物的尺寸为准

Packing 包装

Package 包装	Pcs/tube 片/管	Tube/ inner box 管/内盒	Inner box/ carton 内盒/外箱	Pcs/carton 片/外箱
Tube 管	30	12	6	2160



BSKE080S120

DISCLAIMER 免责声明

- **Warranty Period:** Unless otherwise agreed in the COOPERATION AGREEMENT or other WRITTEN DOCUMENTS, the Warranty Period for products specified in this specification shall be one year from the date of purchase if the products are properly preserved.

Special instructions: Storage Temperature: 20±5°C; Relative Humidity: 30%-60%; The product should be stored in a place away from direct light and vibration.

质保期: 除双方在合作协议或其他书面文件中另行约定外, 产品妥当保存的情况下自购买之日起, 本规格书所述产品质保期为一年。

特殊说明: 储存温度: 20±5°C; 相对湿度: 30%-60%; 产品应放置于避光地方, 避免震动。

- Our Company is committed to enhancing product quality and stability. This specification serves solely to delineate technical product details.

本公司致力于提高产品质量与稳定性。本文件之目的, 仅在于陈述产品相关技术信息。

- **Notwithstanding the Company's reasonable efforts and due diligence, the sensitive nature of the products and variations in testing environments and systems may result in a certain failure rate, including potential malfunctions or failures under specific conditions. Consequently, the Company does not warrant the accuracy of the information contained in this specification, nor the fitness for a particular purpose or merchantability of the products. The information in this specification shall not be construed as a guarantee or commitment regarding product functionality, condition, or quality.**

尽管本公司已尽合理努力及注意, 但由于产品本身敏感特性以及测试环境、系统的差异, 存在一定的故障发生率以及可能在某些情况下出现故障或失效。因此, 本公司不承诺本文件中所列信息准确性及产品适配、适销性。本文件所载信息不应被视为本公司对产品功能、条件或质量的保证与承诺。

- **The content contained in this specification shall not be construed as any express, implied, or otherwise grant and/or license to patents, trademarks, copyrights, or other intellectual property rights owned by the Company or third parties. The Company's commitments regarding product intellectual property are strictly limited to the terms expressly stated in SEPARATE WRITTEN AGREEMENTS with Customers. Reverse-engineering, disassembly, or any form of analysis of the product is strictly prohibited without the Company's prior written consent.**

本文件所载内容, 不应视为对本公司或他人所有的专利、商标(标识)及版权等知识产权做出的任何明示、默示或其他方式的转让及/或许可; 本公司对本文件所列产品知识产权的承诺, 仅限于与客户另行达成书面合作约定中示明的内容。未经本公司书面许可, 禁止客户对产品进行任何形式的拆解和逆向工程分析。

- **The Company shall not be held liable for any product damage or consequential incidents resulting from usage beyond the recommended storage conditions, operating parameters, or absolute maximum ratings (or other explicitly stated limits) specified in this specification. Customers must strictly adhere to the operational procedures and conditions outlined in the latest version of the specification when utilizing or testing the product. Customers are responsible for complying with safety standards,**



BSKE080S120

including but not limited to redundant design, fire prevention measures, and fault prevention, to design and maintain a safe and stable system environment. Customers must verify all functionalities described in this specification before or during actual application to ensure product suitability, safety (preventing potential accidents, fires, or public harm etc.), and reliability. It is recommended that Customers consult our company prior to testing to confirm whether the product information adequately covers the application requirements.

任何超出本文件中建议存储条件、使用条件及绝对最大额定参数条件（或部分明确值）使用，造成的产品损坏或连带事故发生，本公司不承担相关责任。当客户在使用产品时，应根据最新版本文件上规定的操作步骤或说明条件进行使用或测试。客户有责任遵从安全规则（包括冗余设计、防火措施、故障预防等）设计安全及稳定的系统环境，在实际应用前、或实际应用中验证本文件所述的任何功能，以确保适用性、安全性（预防可能发生的任何事故、火灾或社会伤害等）及可靠性。建议客户在测试前可咨询本公司，以验证产品信息是否可以涵盖应用需求。

- This product shall not be used in any equipment or applications requiring higher reliability or quality standards where failure could result in personal injury, death, or catastrophic events, including but not limited to nuclear control systems, aircraft/aviation components, maritime/rail transport equipment, traffic signaling devices, combustion control systems, medical equipment, or other safety-critical applications. Customers must procure genuine products exclusively through the Company or authorized channels, and utilize them strictly within legally permitted boundaries and under conditions expressly defined in this specification. The Company disclaims all liability for losses, damages, or injuries arising from non-compliance with these requirements.

本产品不能且禁止应用在一些需要更高稳定性及质量的特殊设备上，以免导致人员伤亡等意外发生，包括原子能控制设备，飞机及航空器件，船舶、轨道等运输设备，交通信号设备，燃烧控制设备，医药设备以及所有安全性设备等。客户应通过本公司或经本公司授权的渠道购买正品，并应在法律约束范围内及本文件明确条件下合法、合理使用，否则造成损失与伤害的，本公司概不负责。

- The information presented in this specification constitutes the latest product details compiled and recorded by our Company with reasonable efforts at the time of publication. To ensure greater accuracy, our Company reserves the right to make periodic corrections, modifications, and version updates to this specification without prior notice. Customers should always refer to the latest version when using or consulting this document.

本文件示明信息，均为发布时本公司尽合理努力整理并记录的产品最新信息。为提供更加准确的信息，本公司保留对本文件不定期勘误修改及版本更新的权利。客户在使用或参阅时，请使用最新版本。

- This specification is written in both Chinese and English, and in case of any conflict between the Chinese and English versions, the Chinese version shall prevail.

本文件以中英文双语书就，如有不同之处，以中文内容为准。