

BVE3KSMJB28CA

Description 描述

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, telecommunications and intelligent control systems.

TVS 二极管可广泛应用于消费电子产品、汽车工业、电信和智能控制系统等领域。

Features

特性

- Low profile package
小体积包装
- Ideal for automated placement
包装适合自动贴片
- Excellent clamping capability
优秀的电压钳位能力
- Low incremental surge resistance
低增量浪涌能力
- 3000W peak pulse power capability with a 10/1000 μ s waveform
10/1000us 时峰值脉冲功率 3000W
- Hi reliability application and automotive grade AEC-Q101 qualified
高可靠性应用和汽车级 AEC-Q101 合格



DO-214AB(SMC)



Applications

应用

- Automotive industries
汽车工业
- Surge resistance protection
浪涌保护

Part Number 型号	$V_{RWM}[V]$ 反向隔离电压	$P_{PPM}[W](10/1000us)$ 峰值脉冲功率	$T_{Jmax}[^{\circ}C]$ 最高结温	Marking 标记	Package 封装
BVE3KSMJB28CA	28	3000	150	30B28CAX	DO-214AB(SMC)

BVE3KSMJB28CA**Maximum Rated Values****最大额定参数**

Parameter 参数	Symbol 符号	Value 值	Unit 单位
Peak pulse power dissipation at 10/1000μs 10/1000μs 时脉冲峰值功率	P _{PP}	3000	W
Operating junction temperature 工作结温	T _J	-55 to +150	°C
Storage temperature 储存温度	T _{STG}	-55 to +150	°C

Electrical Characteristic at (T_A = 25°C , unless otherwise specified)**电学特性 (T_A=25°C, 除非特别声明)**

Parameter 参数	Symbol 符号	Conditions 条件	Value 值			Unit 单位
			Min. 最小值	Typ. 典型值	Max. 最大值	
Reverse Stand-Off Voltage 反向隔离电压	V _{RWM}	-	-	-	28	V
Reverse Breakdown Voltage 反向击穿电压	V _{BR}	I _T =1mA	31.1	-	34.4	V
Reverse Leakage Current 反向漏电流	I _R	V _{RWM} =28V	-	-	1	μA
Peak Pulse Current 峰值脉冲电流	I _{PP}	t _p =10/1000μs	-	-	66.1	A
Clamping Voltage 钳位电压	V _C	I _{PP} =66.1A, t _p =10/1000μs	-	-	45.4	V

BVE3KSMJB28CA

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

特性曲线 ($T_A = 25^\circ\text{C}$, 除非特别声明)




Fig.1 I-V Curve Characteristics




Fig.2 Peak Pulse Power Rating




Fig.3 Clamping Power Pulse Waveform





Fig.4 Pulse Derating Curve

DO-214AB (SMC) Outline Dimensions


DO-214AB (SMC)外形尺寸



DO-214AB(单位: mm)		
Dim	Min	Max
A	2.32	2.72
A1	2.05	2.46
A2	0.10	0.25
A3	0.05	0.30
b	2.90	3.20
c	0.15	0.41
D	5.59	6.22
E	6.60	7.11
E1	7.75	8.13
E2	4.13	4.43
L	0.76	1.52


Suggested Pad Layout (Unit: mm)

建议焊盘布局 (单位: mm)





Tape and Reel Specification (Unit: mm)

编带和卷盘规格 (单位: mm)



备注:
每卷载带长度408M

项目	规格	公差
W	16.00	± 0.10
E	1.75	± 0.10
F	7.50	± 0.10
A0	6.15	± 0.10
B0	8.25	± 0.10
K0	2.75	± 0.10
T	0.25	± 0.05
D0	1.55	± 0.05
D1	1.55	± 0.05
P0	4.00	± 0.10
P1	8.00	± 0.10
P2	2.00	± 0.10



Packing 包装	pcs/reel 个/卷盘	reel/inner box 卷盘/内盒	inner box/carton 内盒/外箱	pcs/carton 个/外箱
Reel 卷盘	3000	2	10	60000

BVE3KSMJB28CA**DISCLAIMER 免责声明**

- **Warranty Period:** Unless otherwise agreed in the COOPERATION AGREEMENT or other WRITTEN DOCUMENTS, the Warranty Period for products specified in this specification shall be 12 months from the date of production.

质保期：除双方在合作协议或其他书面文件中另行约定外，本规格书所述产品质保期为自产品产出起 12 个月。

- **Our Company is committed to enhancing product quality and stability.** This specification serves solely to delineate technical product details.

本公司致力于提高产品质量与稳定性。本文件之目的，仅在于陈述产品相关技术信息。

- **Notwithstanding the Company's reasonable efforts and due diligence, the sensitive nature of the products and variations in testing environments and systems may result in a certain failure rate, including potential malfunctions or failures under specific conditions. Consequently, the Company does not warrant the accuracy of the information contained in this specification, nor the fitness for a particular purpose or merchantability of the products. The information in this specification shall not be construed as a guarantee or commitment regarding product functionality, condition, or quality.**

尽管本公司已尽合理努力及注意，但由于产品本身敏感特性以及测试环境、系统的差异，存在一定的故障发生率以及可能在某些情况下出现故障或失效。因此，本公司不承诺本文件中所列信息准确性及产品适配、适销性。本文件所载信息不应被视为本公司对产品功能、条件或质量的保证与承诺。

- **The content contained in this specification shall not be construed as any express, implied, or otherwise grant and/or license to patents, trademarks, copyrights, or other intellectual property rights owned by the Company or third parties. The Company's commitments regarding product intellectual property are strictly limited to the terms expressly stated in SEPARATE WRITTEN AGREEMENTS with Customers. Reverse-engineering, disassembly, or any form of analysis of the product is strictly prohibited without the Company's prior written consent.**

本文件所载内容，不应视为对本公司或他人所有的专利、商标（标识）及版权等知识产权做出的任何明示、默示或其他方式的转让及/或许可；本公司对本文件所列产品知识产权的承诺，仅限于与客户另行达成书面合作约定中示明的内容。未经本公司书面许可，禁止客户对产品进行任何形式的拆解和逆向工程分析。

- **The Company shall not be held liable for any product damage or consequential incidents resulting from usage beyond the recommended storage conditions, operating parameters, or absolute maximum ratings (or other explicitly stated limits) specified in this specification. Customers must strictly adhere to the operational procedures and conditions outlined in the latest version of the specification when utilizing or testing the product. Customers are responsible for complying with safety standards, including but not limited to redundant design, fire prevention measures, and fault prevention, to design and maintain a safe and stable system environment. Customers must verify all functionalities described in this**

BVE3KSMJB28CA

specification before or during actual application to ensure product suitability, safety (preventing potential accidents, fires, or public harm etc.), and reliability. It is recommended that Customers consult our company prior to testing to confirm whether the product information adequately covers the application requirements.

任何超出本文件中建议存储条件、使用条件及绝对最大额定参数条件（或部分明确值）使用，造成的产品损坏或连带事故发生，本公司不承担相关责任。当客户在使用产品时，应根据最新版本文件上规定的操作步骤或示明条件进行使用或测试。客户有责任遵从安全规则（包括冗余设计、防火措施、故障预防等）设计安全及稳定的系统环境，在实际应用前、或实际应用中验证本文件所述的任何功能，以确保适用性、安全性（预防可能发生的任何事故、火灾或社会伤害等）及可靠性。建议客户在测试前可咨询本公司，以验证产品信息是否可以涵盖应用需求。

- This product shall not be used in any equipment or applications requiring higher reliability or quality standards where failure could result in personal injury, death, or catastrophic events, including but not limited to nuclear control systems, aircraft/aviation components, combustion control systems, medical equipment, or other safety-critical applications. Customers must procure genuine products exclusively through the Company or authorized channels, and utilize them strictly within legally permitted boundaries and under conditions expressly defined in this specification. The Company disclaims all liability for losses, damages, or injuries arising from non-compliance with these requirements.

本产品不能且禁止应用在一些需要更高稳定性及质量的特殊设备上，以免导致人员伤亡等意外发生，包括原子能控制设备，飞机及航空器件，燃烧控制设备，医药设备以及所有安全性设备等。客户应通过本公司或经本公司授权的渠道购买正品，并应在法律约束范围内及本文件明确条件下合法、合理使用，否则造成损失与伤害的，本公司概不负责。

- The information presented in this specification constitutes the latest product details compiled and recorded by our Company with reasonable efforts at the time of publication. To ensure greater accuracy, our Company reserves the right to make periodic corrections, modifications, and version updates to this specification without prior notice. Customers should always refer to the latest version when using or consulting this document.

本文件示明信息，均为发布时本公司尽合理努力整理并记录的产品最新信息。为提供更加准确的信息，本公司保留对本文件不定期勘误修改及版本更新的权利。客户在使用或参阅时，请使用最新版本。

- This specification is written in both Chinese and English, and in case of any conflict between the Chinese and English versions, the Chinese version shall prevail.

本文件以中英文双语书就，如有不同之处，以中文内容为准。