

关键参数
Key Parameters

V_{RRM}		1200	V
V_F	Typ.	1.60	V
I_F	Max.	100	A
I_{FRM}	Max.	200	A

典型应用
Typical Applications

●工业整流	Industrial Rectification
●吸收电路	Snubber Circuit

特点
Features

●高浪涌能力	High Surge Capability
●绝缘基板	Isolated Baseplate
●双二极管电路	Dual Diode Double Circuit


电路结构
Circuit Configuration


图 1.电路结构


Fig. 1 Circuit configuration

模块外形
Module Appearance


图 2. 模块外形

Fig. 2 Module appearance

模块标签说明
Module Label Code Instruction

	数据位置 Data position	数据内容 Content of data
	1--8	模块批次号 Module batch number
	9--12	模块序列号 Module serial number

最大额定值
Absolute Maximum Ratings

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions	数值 Value	单位 Unit
V_{RRM}	重复峰值电压 Repetitive voltage	$T_C = 25\text{ }^{\circ}\text{C}$	1200	V
I_F	正向直流电流 Forward current	DC	100	A
I_{FRM}	正向重复峰值电流 Peak forward current	$t_P = 1\text{ms}$	200	A
I_{FSM}	浪涌电流 Surge current	$V_R = 0\text{V}$, $t_P = 10\text{ms}$, $T_{vj} = 150\text{ }^{\circ}\text{C}$	800	A
I^2t	I^2t 值 I^2t	$V_R = 0\text{V}$, $t_P = 10\text{ms}$, $T_{vj} = 150\text{ }^{\circ}\text{C}$	3.2	kA^2s
V_{isol}	绝缘电压(模块) Isolation voltage – per module	短接所有端子, 端子与基板间施加电压 (Connected terminals to base plate), AC RMS, 1 min, 50Hz, $T_C = 25\text{ }^{\circ}\text{C}$	2500	V

热和机械数据
Thermal & Mechanical Data

参数 Symbol	说明 Explanation	值 Value	单位 Unit
爬电距离 Creepage distance	端子-散热器 Terminal to heatsink	30	mm
	端子-端子 Terminal to terminal	25	mm
绝缘间隙 Clearance	端子-散热器 Terminal to heatsink	24	mm
	端子-端子 Terminal to terminal	13	mm
相对漏电起痕指数 CTI (Comparative Tracking Index)		> 600	

热和机械数据
Thermal & Mechanical Data

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
$R_{th(J-C)}$	结壳热阻 Thermal resistance – Diode				280	K / kW
$R_{th(C-H)}$	接触热阻 Thermal resistance – case to heatsink	安装力矩 5Nm, 导热脂 1W/m·K Mounting torque 5Nm, with mounting grease 1W/m·K		100		K / kW
$T_{vj\ op}$	工作结温 Operating junction temperature		-40		150	°C
T_{stg}	存储温度 Storage temperature range		-40		125	°C
M	安装力矩 Screw torque	安装紧固用 - M5 Mounting - M5	2.4		2.8	Nm
		电路互连用 - M5 Electrical connections - M5	2.4		2.8	Nm
L_M	模块电感 Module inductance			30		nH
R_{INT}	模块端子-芯片电阻 Internal transistor resistance, terminals - chip	$T_C = 25\ ^\circ\text{C}$		0.5		mΩ

电特性值
Electrical Characteristics

 除非特别声明, 否则 $T_C = 25\ ^\circ\text{C}$
 $T_C = 25\ ^\circ\text{C}$ unless otherwise stated

符号 Symbol	参数名称 Parameter	条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
I_{RRM}	重复反向电流 Repetitive reverse current	$V_{RM} = V_{RRM}$			1	mA
		$V_{RM} = V_{RRM}, T_C = 125\ ^\circ\text{C}$			3	mA
		$V_{RM} = V_{RRM}, T_C = 150\ ^\circ\text{C}$			5	mA
V_F	正向电压 Forward voltage	$I_F = 100\text{A}$		1.60	2.00	V
		$I_F = 100\text{A}, T_{vj} = 125\ ^\circ\text{C}$		1.65		V
		$I_F = 100\text{A}, T_{vj} = 150\ ^\circ\text{C}$		1.65		V




图 3.输出特性典型曲线, $I_F = f(V_F)$

Fig.3 Typical output characteristics, $I_F = f(V_F)$




图 4. 瞬态热阻抗曲线, $Z_{th(J-C)} = f(t_p)$

Fig.4 Transient thermal impedance, $Z_{th(J-C)} = f(t_p)$



1、未注尺寸公差 ± 0.2 。

重量 Weight: 145g 模块外观类型 Module outline code: T1

图 5. 模块外观尺寸

Fig. 5 Module outlines

株洲中车时代半导体有限公司

Zhuzhou CRRC Times Semiconductor Co., Limited

地 址	Address	湖南省株洲市石峰区田心工业园 Tianxin Industrial Park, Shifeng District, ZhuZhou City, Hunan Province, China
邮 编	Zipcode	412001
电 话	Telephone	+86 (0)731-28498268, 28498238, 28493472
传 真	Fax	+86 (0)731-28498851, 28498494
电子邮箱	Email	sbu@crzcic.cc
网 址	Web Site	http://www.sbu.crzcic.cc

使用条件和条款

(1) 数据手册中的产品信息是专门为技术人员提供的。由于产品应用的多样性，本文件所包含的信息只能作为一般性指南，无法保证其在某些特殊应用中的适用性，建议用户在使用前评估产品的适用性。如果需要额外的产品信息和帮助，请联系我公司的销售或技术支持。

(2) 本产品数据手册中提供的一部分产品数据是产品的典型值，实际出厂测试的产品数据可能与典型值略有偏离，但我公司保证这些偏离不会影响产品的正常使用。如果产品信息发生变更，我公司会及时修订产品数据手册，请随时关注我公司网站发布的产品手册信息。

(3) 如果对本产品有特殊要求，或用于特殊行业（如航空航天、医疗、生命维持等），强烈建议用户与我公司联合进行应用风险和产品质量评估，建立统一的质量协议。

(4) 产品使用过程中，如有超出产品数据手册中所定义的产品极限温度、电压、电流或安全工作区范围的情况，我公司无法保证产品的应用可靠性。

(5) 产品在使用时，严禁触碰。产品断电后，在确保无电荷残留、产品已冷却后，才可以在有静电防护措施的情况下触碰产品。

(6) 产品数据手册首页的右上角，会显示产品的状态。如果它尚未完全批准，会标示**初版 (preliminary)**，该标示意味着该产品已完成设计，量产的产品参数正在确定中，数据手册中的产品信息目前是可以参考的，但将来某些细节可能会发生变化。如果产品数据手册首页的右上角没有标注，则表示该产品已可以批量生产。

Terms and conditions of usage

(1) The product information in this datasheet are intended for use by technical personnel. Due to the diversity of product applications, the information contained in this document can only be used as a general guide, the application applicability cannot be guaranteed in some special applications. It is recommended that users do the assessment of the application applicability before applied. If users need additional product information and help, please contact our sales or technical support.

(2) Some product data in the datasheet of this product are the typical values, the actual factory testing data may deviate slightly from typical values, but our company guarantees that these deviations will not affect the normal use of the product. If the product information changes, our company will promptly amend the datasheet, please keeps your attention to product information changing in our company website.

(3) If there are special requirements for the product, or apply it in special industries (such as aerospace, medical, life support, etc.), we strongly recommend that to perform joint application risk and quality assessments, get the quality agreements.

(4) During the application, if the working conditions are beyond the limitation of temperature, voltage, current or safe operating area of the product defined in the product datasheet, our company cannot guarantee the reliability of the product.

(5) When the products are in use, it is strictly prohibited to touch. After power off, to ensure that there is no residual charge and the products have been cooled before they can be touched. And all operations must be under ESD protection measures.

(6) We annotate datasheet in the top right hand corner of the front page, to indicate product status. The annotation “Preliminary” indicates the product design is complete and final characterization for volume production is in progress, the product information in the datasheet is currently can be referenced, but some details may change in the future. There is no annotation indicates the product is capable to produce in batch quantity.