

关键参数		Key Parameters	
V_{DSS}		750	V
$R_{DS(on)}$	Typ.	1.80	mΩ
I_D	Max.	700	A
I_{DM}	Max.	1400	A

典型应用	Typical Applications
● 电动汽车	Automotive Applications
● 混合动力/纯电动车	Hybrid/Electrical Vehicles
● 电机驱动	Motor Drives

特点	Features
● 铜针翅基板	Cu Pin-fin Baseplate
● 低开关损耗	Low Switching Losses
● 低反向恢复损耗	Low Reverse Recovery Loss
● 低感设计	Low Inductive Design
● Si ₃ N ₄ 衬板	Si ₃ N ₄ AMB Substrate




图 1.电路结构
Fig. 1 Circuit configuration




图 2. 模块外形
Fig. 2 Module appearance

模块标签说明	Module Label Code Instruction	
	数据位置 Data position	数据内容 Content of data
	1--8	模块批次号 Module batch number
	9--12	模块序列号 Module serial number

最大额定值
Absolute Maximum Ratings

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions	数值 Value	单位 Unit
V_{DSS}	漏源极电压 Drain-source voltage	$V_{GS} = 0V$	750	V
V_{GSSMAX}	栅源电压 Gate-source voltage		-8/+23	V
V_{GSSOP}	栅源电压 Gate-source voltage		-4/+18	V
I_D	额定漏极电流 Rating drain current	$T_F = 60^\circ C, T_{vj\ max} = 175^\circ C$	700	A
I_{DM}	漏极峰值电流 Peak drain current	$t_P = 1ms$	1400	A
P_{max}	晶体管部分最大损耗 Max. transistor power dissipation	$T_F = 65^\circ C, T_{vj\ max} = 175^\circ C$	1093	W
V_{isol}	绝缘电压(模块) Isolation voltage – per module	短接所有端子，端子与基板间施加电压 (Connected terminals to baseplate), RMS, f=0 Hz, t=1 sec, $T_C = 25^\circ C$	4200	V

热和机械数据
Thermal & Mechanical Data

参数 Symbol	说明 Explanation	值 Value	单位 Unit
爬电距离 Creepage distance	端子-散热器 Terminal to heatsink	9	mm
	端子-端子 Terminal to terminal	9	mm
绝缘间隙 Clearance	端子-散热器 Terminal to heatsink	4.5	mm
	端子-端子 Terminal to terminal	4.5	mm
相对漏电起痕指数 CTI (Comparative tracking index)		>200	

热和机械数据
Thermal & Mechanical Data

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
$R_{th(J-F)}$ MOSFET	MOSFET 热阻 Thermal resistance -MOSFET	冷却液: 50%乙二醇溶液; $\Delta V/\Delta t=10 \text{ dm}^3/\text{min}$; $T_F = 65^\circ\text{C}$ Cooling Fluid: 50% water / 50% ethylene glycol; $\Delta V/\Delta t=10 \text{ dm}^3/\text{min}$; $T_F = 65^\circ\text{C}$		100.6	106	K / mW
ΔP	冷却液流阻 Pressure drop in cooling circuit	冷却液: 50%乙二醇溶液; $\Delta V/\Delta t=10 \text{ dm}^3/\text{min}$; $T_F = 65^\circ\text{C}$ Cooling Fluid: 50% water / 50% ethylenglycol; $\Delta V/\Delta t=10$ dm^3/min ; $T_F = 65^\circ\text{C}$		68		mbar
P	冷却液最大压力 Maximum pressure in cooling circuit				2.5	bar
$T_{vj \text{ op}}$	工作结温 Operating junction temperature		-40		175	$^\circ\text{C}$
T_{stg}	存储温度 Storage temperature range		-40		125	$^\circ\text{C}$
M	安装力矩 Screw torque	安装紧固用 - M4 Mounting - M4	1.8	2.0	2.2	Nm
		PCB 安装用 PCB Mounting	0.55	0.6	0.65	Nm

热敏电阻数据
NTC-Thermistor Data

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
R_{25}	额定电阻值 Rated resistance	$T_C = 25^\circ\text{C}$		5		k Ω
$\Delta R/R$	R_{100} 偏差 Deviation of R_{100}	$T_C = 100^\circ\text{C}$, $R_{100}=493\Omega$	-5		5	%
P_{25}	耗散功率 Power dissipation	$T_C = 25^\circ\text{C}$			20	mW
$B_{25/50}$	B -值 B -value	$R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298.15 \text{ K}))]$		3375		K
$B_{25/80}$	B -值 B -value	$R_2 = R_{25} \exp [B_{25/80}(1/T_2 - 1/(298.15 \text{ K}))]$		3411		K
$B_{25/100}$	B -值 B -value	$R_2 = R_{25} \exp [B_{25/100}(1/T_2 - 1/(298.15 \text{ K}))]$		3433		K

电特性值
Electrical Characteristics

 除非特别声明，否则 $T_C = 25\text{ }^{\circ}\text{C}$
 $T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

符号 Symbol	参数名称 Parameter	条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
I_{DSS}	零栅压漏极电流 Zero gate voltage drain current	$V_{GS} = 0V, V_{DS} = V_{DSS}$			100	μA
		$V_{GS} = 0V, V_{DS} = V_{DSS}, T_{vj} = 150\text{ }^{\circ}\text{C}$			500	μA
		$V_{GS} = 0V, V_{DS} = V_{DSS}, T_{vj} = 175\text{ }^{\circ}\text{C}$			1000	μA
I_{GSS}	栅极漏电流 Gate leakage current	$V_{GS} = -4/+18V, V_{DS} = 0V$			500	nA
$V_{GS(th)}$	栅极-源极阈值电压 Gate threshold voltage	$I_D = 60\text{mA}, V_{GS} = V_{DS}$	2.25	2.95	3.55	V
$R_{DS(on)}^{(*1)}$	漏极-源极通态电阻 Drain-source on-state resistance	$V_{GS} = 18V, I_D = 700A$		1.80		m Ω
		$V_{GS} = 18V, I_D = 700A, T_{vj} = 150\text{ }^{\circ}\text{C}$		2.00		m Ω
		$V_{GS} = 18V, I_D = 700A, T_{vj} = 175\text{ }^{\circ}\text{C}$		2.25		m Ω
g_{fs}	跨导 Forward transconductance	$V_{DS} = 20V, I_D = 700A$		487		S
$V_{SD}^{(*1)}$	二极管正向电压 Diode forward voltage	$I_{SD} = 700A, V_{GS}^{(*2)} = -4V$		5.20		V
		$I_{SD} = 700A, V_{GS} = -4V, T_{vj} = 150\text{ }^{\circ}\text{C}$		4.85		V
		$I_{SD} = 700A, V_{GS} = -4V, T_{vj} = 175\text{ }^{\circ}\text{C}$		4.80		V
I_{SC}	短路电流 Short circuit current	$T_{vj} = 175\text{ }^{\circ}\text{C}, V_{DD} = 470V,$ $V_{GS} \leq 18V, t_p \leq 2.4\mu\text{s},$ $V_{DS(max)} = V_{DSS} - L^{(*3)} \times di/dt,$ IEC 60747-8		7000		A

注意:
Note:

- (*1) 表示该参数的测试点为辅助母排端子 (*1) indicates it is measured at the auxiliary busbar terminal),
- (*2) 图 13 中也提供了 V_{GS} 为 0、18V 条件下的 V_{SD} . (*2) V_{SD} with $V_{GS}=0$ 、18V is also provided in figure 13.)
- (*3) 表示 L 是电路杂散电感加上 L_{SDS} (*3) indicates L is the circuit stray inductance plus L_{SDS}).

电特性值

Electrical Characteristics

除非特别声明，否则 $T_C = 25\text{ }^{\circ}\text{C}$ $T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise stated

符号 Symbol	参数名称 Parameter	条件 Test Conditions	最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
C_{iss}	输入电容 Input capacitance	$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$, $f = 100\text{kHz}$		35		nF
Q_g	栅极电荷 Gate charge	-4/+18V		1.40		μC
C_{rss}	反向传输电容 Reverse transfer capacitance	$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$, $f = 100\text{kHz}$		0.1		nF
L_{sDS}	模块电感 Module inductance			8		nH
$R_{DD'+SS'}$	模块引线电阻，端子-芯片 Module lead resistance, terminal-chip			0.7		m Ω
R_{Gint}	内部栅极电阻 Internal gate resistor			0.8		Ω

电特性值
Electrical Characteristics

符号 Symbol	参数名称 Parameter	测试条件 Test Conditions		最小值 Min.	典型值 Typ.	最大值 Max.	单位 Unit
$t_{d(off)}$	关断延迟时间 Turn-off delay time	I_D =700A, V_{DS} = 470V, V_{GS} = -4/+18V, $R_{G(OFF)}$ = 6.3Ω, L_S = 30nH, dv/dt =5880V/μs (T_{vj} = 175 °C).	T_{vj} = 25 °C		413		ns
			T_{vj} = 150 °C		485		
			T_{vj} = 175 °C		505		
t_f	下降时间 Fall time		T_{vj} = 25 °C		83		ns
			T_{vj} = 150 °C		89		
			T_{vj} = 175 °C		88		
E_{OFF}	关断损耗 Turn-off energy loss		T_{vj} = 25 °C		28		mJ
			T_{vj} = 150 °C		29		
			T_{vj} = 175 °C		29		
$t_{d(on)}$	开通延迟时间 Turn-on delay time	T_{vj} = 25 °C		145		ns	
		T_{vj} = 150 °C		144			
		T_{vj} = 175 °C		136			
t_r	上升时间 Rise time	T_{vj} = 25 °C		167		ns	
		T_{vj} = 150 °C		123			
		T_{vj} = 175 °C		123			
E_{ON}	开通损耗 Turn-on energy loss	T_{vj} = 25 °C		50		mJ	
		T_{vj} = 150 °C		31			
		T_{vj} = 175 °C		31			
Q_{rr}	二极管反向恢复电荷 Diode reverse recovery charge	T_{vj} = 25 °C		2		μC	
		T_{vj} = 150 °C		4			
		T_{vj} = 175 °C		4			
I_{rr}	二极管反向恢复电流 Diode reverse recovery current	T_{vj} = 25 °C		96		A	
		T_{vj} = 150 °C		148			
		T_{vj} = 175 °C		159			
E_{rec}	二极管反向恢复损耗 Diode reverse recovery energy	T_{vj} = 25 °C		0.03		mJ	
		T_{vj} = 150 °C		0.01			
		T_{vj} = 175 °C		0.05			




图 3. MOSFET 输出特性典型曲线, $I_D = f(V_{DS})$

Fig.3 Typical MOSFET output characteristics, $I_D = f(V_{DS})$




图 4. MOSFET 输出特性典型曲线, $I_D = f(V_{DS})$

Fig.4 Typical MOSFET output characteristics, $I_D = f(V_{DS})$




图 5. MOSFET 输出特性典型曲线, $I_D = f(V_{DS})$

Fig.5 Typical MOSFET output characteristics, $I_D = f(V_{DS})$




图 6. MOSFET 传输特性典型曲线, $I_D = f(V_{GS})$

Fig.6 Typical MOSFET transfer characteristics, $I_D = f(V_{GS})$




图 7. 导电电阻典型曲线, $R_{DS(on)} = f(I_D)$

Fig.7 Typical On-Resistance characteristics, $R_{DS(on)} = f(I_D)$




图 8. MOSFET 开关损耗典型曲线, $E_{on} = f(I_C)$, $E_{off} = f(I_C)$

Fig.8 Typical MOSFET switching energy, $E_{on} = f(I_C)$, $E_{off} = f(I_C)$




图 9. MOSFET 开关损耗典型曲线, $E_{on} = f(R_G)$, $E_{off} = f(R_G)$

Fig.9 Typical MOSFET switching energy, $E_{on} = f(R_G)$, $E_{off} = f(R_G)$




图 10. MOSFET 反偏安全工作区, $I_D = f(V_{DS})$

Fig.10 Reverse bias safe operating area of MOSFET, $I_D = f(V_{DS})$



图 11. 电容特性典型曲线, $C = f(V_{DS})$


Fig.11 Typical capacity characteristic, $C = f(V_{DS})$

图 12. 栅极电荷特性典型曲线, $V_{GS} = f(Q_G)$


Fig.12 Typical gate charge characteristic, $V_{GS} = f(Q_G)$

图 13. 体二极管及第三象限输出特性典型曲线, $I_D = f(V_{DS})$

Fig.13 Typical body diode output and 3rd quadrant characteristic,

$$I_D = f(V_{DS})$$



图 14. 体二极管反向恢复损耗典型曲线, $E_{rec} = f(I_F)$

Fig.14 Typical body diode switching loss E_{rec} , $E_{rec} = f(I_F)$




图 15. 体二极管反向恢复损耗典型曲线, $E_{rec}=f(R_G)$

Fig.15 Typical body diode switching loss E_{rec} , $E_{rec}=f(R_G)$




图 16. 热敏电阻典型特性曲线, $R= f(T_c)$

Fig.16 Typical NTC thermistor characteristic, $R= f(T_c)$





图 17. 瞬态热阻抗曲线, $Z_{th(J-F)} = f(t_p)$

Fig.17 Transient thermal impedance, $Z_{th(J-F)} = f(t_p)$



重量 Weight: TBDg

模块外观类型 Module outline code: S3

图 18. 模块外观尺寸

Fig. 18 Module outlines

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

注意: 该器件对静电敏感, 用户须采取 ESD 防护措施。

株洲中车时代半导体有限公司

ZHUZHOU CRRC TIMES SEMICONDUCTOR CO., LTD.

地 址	Address	湖南省株洲市石峰区田心工业园	Tianxin Industrial Park, Shifeng District, ZhuZhou City, Hunan Province, China
邮 编	Zipcode	412001	
电 话	Telephone	+86 (0)731-28498268, 28498238, 28493472	
传 真	Fax	+86 (0)731-28498851, 28498494	
电子邮箱	Email	ctsc@csrzc.com	
网 址	Web Site	http://ctsc.crrczie.com	

使用条件和条款

(1) 数据手册中的产品信息是专门为技术人员提供的。由于产品应用的多样性，本文件所包含的信息只能作为一般性指南，无法保证其在某些特殊应用中的适用性，建议用户在使用前评估产品的适用性。如果需要额外的产品信息和帮助，请联系我公司的销售或技术支持。

(2) 本产品数据手册中提供的一部分产品数据是产品的典型值，实际出厂测试的产品数据可能与典型值略有偏离，但我公司保证这些偏离不会影响产品的正常使用。如果产品信息发生变更，我公司会及时修订产品数据手册，请随时关注我公司网站发布的产品手册信息。

(3) 如果对本产品有特殊要求，或用于特殊行业（如航空航天、医疗、生命维持等），强烈建议用户与我公司联合进行应用风险和产品质量评估，建立统一的质量协议。

(4) 产品使用过程中，如有超出产品数据手册中所定义的产品极限温度、电压、电流或安全工作区范围的情况，我公司无法保证产品的应用可靠性。

(5) 产品在使用时，严禁触碰。产品断电后，在确保无电荷残留、产品已冷却后，才可以在有静电防护措施的情况下触碰产品。

(6) 产品数据手册首页的右上角，会显示产品的状态。如果它尚未完全批准，会标示**初版（preliminary）**，该标示意味着该产品已完成设计，量产的产品参数正在确定中，数据手册中的产品信息目前是可以参考的，但将来某些细节可能会发生变化。如果产品数据手册首页的右上角没有标注，则表示该产品已可以批量生产。

Terms and conditions of usage

(1) The product information in this datasheet are intended for use by technical personnel. Due to the diversity of product applications, the information contained in this document can only be used as a general guide, the application applicability cannot be guaranteed in some special applications. It is recommended that users do the assessment of the application applicability before applied. If users need additional product information and help, please contact our sales or technical support.

(2) Some product data in the datasheet of this product are the typical values, the actual factory testing data may deviate slightly from

typical values, but our company guarantees that these deviations will not affect the normal use of the product. If the product information changes, our company will promptly amend the datasheet, please keeps your attention to product information changing in our company website.

(3) If there are special requirements for the product, or apply it in special industries (such as aerospace, medical, life support, etc.), we strongly recommend that to perform joint application risk and quality assessments, get the quality agreements.

(4) During the application, if the working conditions are beyond the limitation of temperature, voltage, current or safe operating area of the product defined in the product datasheet, our company cannot guarantee the reliability of the product.

(5) When the products are in use, it is strictly prohibited to touch. After power off, to ensure that there is no residual charge and the products have been cooled before they can be touched. And all operations must be under ESD protection measures.

(6) We annotate datasheet in the top right hand corner of the front page, to indicate product status. The annotation “Preliminary” indicates the product design is complete and final characterization for volume production is in progress, the product information in the datasheet is currently can be referenced, but some details may change in the future. There is no annotation indicates the product is capable to produce in batch quantity.