



PROTON-ELECTROTEX RUSSIA

High power cycling capability
Low on-state and switching losses
Designed for traction and industrial applications

Phase Control Thyristor Chip Type TR40-1250-10

Maximum allowable mean on-state current ¹⁾					I _{TAV}		1250 A				
Repetitive peak off-state voltage					V _{DRM}		100...1000 V				
Repetitive peak reverse voltage					V _{RRM}						
Turn-off time					t _q		160, 200, 250, 320, 400, 500 μs				
V _{DRM} , V _{RRM} , V	100	200	300	400	500	600	700	800	900	1000	
Voltage code	1	2	3	4	5	6	7	8	9	10	
T _j , °C	-60...+150										

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
ON-STATE					
I_{TAV}	Maximum allowable mean on-state current ¹⁾	A	1250 1446	$T_c=97\text{ }^{\circ}\text{C}$, Double side cooled $T_c=85\text{ }^{\circ}\text{C}$, Double side cooled 180° half-sine wave; 50 Hz	
I_{TRMS}	RMS on-state current ¹⁾	A	1962	$T_c=97\text{ }^{\circ}\text{C}$, Double side cooled 180° half-sine wave; 50 Hz	
I_{TSM}	Surge on-state current ¹⁾	kA	22.0 25.0	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			23.0 26.0	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
I^2t	Safety factor ¹⁾	$\text{A}^2\text{s}\cdot 10^3$	2400 3100	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			2100 2800	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
BLOCKING					
V_{DRM}, V_{RRM}	Repetitive peak off-state and Repetitive peak reverse voltages	V	100...1000	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; 50 Hz; Gate open	
V_{DSM}, V_{RSM}	Non-repetitive peak off-state and Non-repetitive peak reverse voltages	V	200...1100	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; single pulse; Gate open	
V_D, V_R	Direct off-state and Direct reverse voltages	V	$0.6\cdot V_{DRM}$ $0.6\cdot V_{RRM}$	$T_j=T_{j\text{ max}}$; Gate open	

TRIGGERING				
I_{FGM}	Peak forward gate current	A	8	$T_j = T_{j\max}$
V_{RGM}	Peak reverse gate voltage	V	5	
P_G	Gate power dissipation	W	4	$T_j = T_{j\max}$ for DC gate current
SWITCHING				
$(di_T/dt)_{crit}$	Critical rate of rise of on-state current non-repetitive ($f=1$ Hz)	A/ μ s	800	$T_j = T_{j\max}$; $V_D = 0.67 \cdot V_{DRM}$; $I_{TM} = 3500$ A; Gate pulse: $I_G = 2$ A; $t_{GP} = 50$ μ s; $di_G/dt \geq 2$ A/ μ s
THERMAL				
T_{stg}	Storage temperature	$^{\circ}$ C	-60...+50	
T_j	Operating junction temperature	$^{\circ}$ C	-60...+150	
MECHANICAL				
F	Mounting force ¹⁾	kN	14.0...16.0	
F_{cg}	Force on control gate	N	7.8	



CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V _{TM}	Peak on-state voltage ¹⁾ , max	V	1.55	T _j =25 °C; I _{TM} =3925 A	
V _{T(TO)}	On-state threshold voltage, max	V	0.870	T _j =T _{j max} ;	
r _T	On-state slope resistance ¹⁾ , max	mΩ	0.177	0.5 π I _{TAV} < I _T < 1.5 π I _{TAV}	
I _L	Latching current, max	mA	1000	T _j =25 °C; V _D =12 V; Gate pulse: I _G =2 A; t _{GP} =50 μs; di _G /dt≥1 A/μs	
I _H	Holding current, max	mA	300	T _j =25 °C; V _D =12 V; Gate open	
BLOCKING					
I _{DRM} , I _{RRM}	Repetitive peak off-state and Repetitive peak reverse currents, max	mA	100	T _j =T _{j max} ; V _D =V _{DRM} ; V _R =V _{RRM}	
(dv _D /dt) _{crit}	Critical rate of rise of off-state voltage ²⁾ , min	V/μs	200, 320, 500, 1000, 1600, 2000, 2500	T _j =T _{j max} ; V _D =0.67·V _{DRM} ; Gate open	
TRIGGERING					
V _{GT}	Gate trigger direct voltage, max	V	3.00 2.50 1.50	T _j = T _{j min} T _j =25 °C T _j = T _{j max}	V _D =12 V; I _D =3 A; Direct gate current
I _{GT}	Gate trigger direct current, max	mA	400 250 150	T _j = T _{j min} T _j = 25 °C T _j = T _{j max}	
V _{GD}	Gate non-trigger direct voltage, min	V	0.55	T _j =T _{j max} ; V _D =0.67·V _{DRM} ;	
I _{GD}	Gate non-trigger direct current, min	mA	70.00	Direct gate current	
SWITCHING					
t _{gd}	Delay time, max	μs	0.85	T _j =25 °C; V _D =600 V; I _{TM} =I _{TAV} ; di/dt=200 A/μs;	
t _{gt}	Turn-on time, max	μs	4.00	Gate pulse: I _G =2 A; V _G =20 V; t _{GP} =50 μs; di _G /dt=2 A/μs	
t _q	Turn-off time ³⁾ , max	μs	160, 200, 250, 320, 400, 500	dv _D /dt=50 V/μs; T _j =T _{j max} ; I _{TM} =I _{TAV} ; di _R /dt=-10 A/μs; V _R =100V; V _D =0.67·V _{DRM}	


THERMAL					
R _{thjc}	Thermal resistance, junction to case ¹⁾ , max	°C/W	0.030	Direct current	Double side cooled
R _{thjc-A}			0.066		Anode side cooled
R _{thjc-K}			0.054		Cathode side cooled
MECHANICAL					
m	Weight, max	g	25.90		

PART NUMBERING GUIDE						NOTES																	
TR	40	1250	10	A2	E2	1) Depending on the specifications of the housing used. The specified values are relevant when using the Proton-Electrotex T.C1 housing. 2) Critical rate of rise of off-state voltage																	
1	2	3	4	5	6																		
1. Phase Control Thyristor Chip						<table><tr><td>Symbol of Group</td><td>P2</td><td>K2</td><td>E2</td><td>A2</td><td>T1</td><td>P1</td><td>M1</td></tr><tr><td>(dv_D/dt)_{crit}, V/μs</td><td>200</td><td>320</td><td>500</td><td>1000</td><td>1600</td><td>2000</td><td>2500</td></tr></table>		Symbol of Group	P2	K2	E2	A2	T1	P1	M1	(dv _D /dt) _{crit} , V/μs	200	320	500	1000	1600	2000	2500
Symbol of Group	P2	K2	E2	A2	T1			P1	M1														
(dv _D /dt) _{crit} , V/μs	200	320	500	1000	1600			2000	2500														
2. Maximum diameter, mm																							
3. Mean on-state current, A																							
4. Voltage code																							
5. Critical rate of rise of off-state voltage, V/μs																							
6. Turn-off time (dv _D /dt=50 V/μs)						3) Turn-off time (dv _D /dt=50 V/μs)																	
						<table><tr><td>Symbol of Group</td><td>T2</td><td>P2</td><td>M2</td><td>K2</td><td>H2</td><td>E2</td></tr><tr><td>t_{qf}, μs</td><td>160</td><td>200</td><td>250</td><td>320</td><td>400</td><td>500</td></tr></table>		Symbol of Group	T2	P2	M2	K2	H2	E2	t _{qf} , μs	160	200	250	320	400	500		
Symbol of Group	T2	P2	M2	K2	H2	E2																	
t _{qf} , μs	160	200	250	320	400	500																	

OVERALL DIMENSIONS



**Dimensions for reference.*



All dimensions in millimeters

The information contained herein is confidential and protected by Copyright.
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.