



PROTON-ELECTROTEX RUSSIA

High power cycling capability
Low on-state and switching losses
Designed for traction and industrial applications

Phase Control Thyristor Chip Type TR40-400-44

Maximum allowable mean on-state current ¹⁾		I _{TAV}	400 A		
Repetitive peak off-state voltage		V _{DRM}	3800...4400 V		
Repetitive peak reverse voltage		V _{RRM}			
Turn-off time		t _q	500, 630, 800 μs		
V _{DRM} , V _{RRM} , V	3800	4000	4200	4400	
Voltage code	38	40	42	44	
T _j , °C	-60...+125				

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
ON-STATE					
I_{TAV}	Maximum allowable mean on-state current ¹⁾	A	400 482	$T_c=95\text{ }^{\circ}\text{C}$, Double side cooled $T_c=85\text{ }^{\circ}\text{C}$, Double side cooled 180° half-sine wave; 50 Hz	
I_{TRMS}	RMS on-state current ¹⁾	A	628	$T_c=95\text{ }^{\circ}\text{C}$, Double side cooled 180° half-sine wave; 50 Hz	
I_{TSM}	Surge on-state current ¹⁾	kA	6.5 7.5	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			7.0 8.0	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
I^2t	Safety factor ¹⁾	$A^2s\cdot 10^3$	210 280	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			200 260	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^{\circ}\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_D=V_R=0\text{ V}$; Gate pulse: $I_G=2\text{ A}$; $t_{GP}=50\text{ }\mu\text{s}$; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
BLOCKING					
V_{DRM}, V_{RRM}	Repetitive peak off-state and Repetitive peak reverse voltages	V	3800...4400	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; 50 Hz; Gate open	
V_{DSM}, V_{RSM}	Non-repetitive peak off-state and Non-repetitive peak reverse voltages	V	3900...4500	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; single pulse; Gate open	
V_D, V_R	Direct off-state and Direct reverse voltages	V	$0.6\cdot V_{DRM}$ $0.6\cdot V_{RRM}$	$T_j=T_{j\text{ max}}$; Gate open	

TRIGGERING				
I_{FGM}	Peak forward gate current	A	8	$T_j = T_{j\max}$
V_{RGM}	Peak reverse gate voltage	V	5	
P_G	Gate power dissipation	W	4	$T_j = T_{j\max}$ for DC gate current
SWITCHING				
$(di_T/dt)_{crit}$	Critical rate of rise of on-state current non-repetitive ($f=1\text{ Hz}$)	A/ μs	500	$T_j = T_{j\max}$; $V_D = 0.67 \cdot V_{DRM}$; $I_{TM} = 1250\text{ A}$; Gate pulse: $I_G = 2\text{ A}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt \geq 2\text{ A}/\mu\text{s}$
THERMAL				
T_{stg}	Storage temperature	$^{\circ}\text{C}$	$-60 \dots +50$	
T_j	Operating junction temperature	$^{\circ}\text{C}$	$-60 \dots +125$	
MECHANICAL				
F	Mounting force ¹⁾	kN	14.0...16.0	
F_{cg}	Force on control gate	N	7.8	


CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V _{TM}	Peak on-state voltage ¹⁾ , max	V	2.25	T _j =25 °C; I _{TM} =1256 A	
V _{T(TO)}	On-state threshold voltage, max	V	1.117	T _j =T _{j max} ;	
r _T	On-state slope resistance ¹⁾ , max	mΩ	1.245	0.5 π I _{TAV} < I _T < 1.5 π I _{TAV}	
I _L	Latching current, max	mA	1000	T _j =25 °C; V _D =12 V; Gate pulse: I _G =2 A; t _{GP} =50 μs; di _G /dt≥1 A/μs	
I _H	Holding current, max	mA	300	T _j =25 °C; V _D =12 V; Gate open	
BLOCKING					
I _{DRM} , I _{RRM}	Repetitive peak off-state and Repetitive peak reverse currents, max	mA	100	T _j =T _{j max} ; V _D =V _{DRM} ; V _R =V _{RRM}	
(dv _D /dt) _{crit}	Critical rate of rise of off-state voltage ²⁾ , min	V/μs	200, 320, 500, 1000, 1600, 2000, 2500	T _j =T _{j max} ; V _D =0.67·V _{DRM} ; Gate open	
TRIGGERING					
V _{GT}	Gate trigger direct voltage, max	V	3.00 2.50 1.50	T _j = T _{j min} T _j =25 °C T _j = T _{j max}	V _D =12 V; I _D =3 A; Direct gate current
I _{GT}	Gate trigger direct current, max	mA	400 250 150	T _j = T _{j min} T _j = 25 °C T _j = T _{j max}	
V _{GD}	Gate non-trigger direct voltage, min	V	0.45	T _j =T _{j max} ; V _D =0.67·V _{DRM} ;	
I _{GD}	Gate non-trigger direct current, min	mA	55.00	Direct gate current	
SWITCHING					
t _{gd}	Delay time, max	μs	3.20	T _j =25 °C; V _D =1500 V; I _{TM} =I _{TAV} ; di/dt=200 A/μs;	
t _{gt}	Turn-on time, max	μs	15.00	Gate pulse: I _G =2 A; V _G =20 V; t _{GP} =50 μs; di _G /dt=2 A/μs	
t _q	Turn-off time ³⁾ , max	μs	500, 630, 800	dv _D /dt=50 V/μs; T _j =T _{j max} ; I _{TM} = I _{TAV} ; di _R /dt=-5 A/μs; V _R =100V; V _D =0.67·V _{DRM}	

THERMAL					
R _{thjc}	Thermal resistance, junction to case ¹⁾ , max	°C/W	0.0320	Direct current	Double side cooled
R _{thjc-A}			0.0704		Anode side cooled
R _{thjc-K}			0.0576		Cathode side cooled
MECHANICAL					
m	Weight, max	g	28.00		

PART NUMBERING GUIDE						NOTES							
TR	40	400	44	A2	B2	1) Depending on the specifications of the housing used. The specified values are relevant when using the Proton-Electrotex T.C2 housing. 2) Critical rate of rise of off-state voltage							
1	2	3	4	5	6								
1. Phase Control Thyristor Chip						3) Turn-off time ($dv_D/dt=50\text{ V}/\mu\text{s}$)							
2. Maximum diameter, mm													
3. Mean on-state current, A													
4. Voltage code													
5. Critical rate of rise of off-state voltage, $\text{V}/\mu\text{s}$													
6. Turn-off time ($dv_D/dt=50\text{ V}/\mu\text{s}$)						Symbol of Group							
						P2	K2	E2	A2	T1	P1	M1	
						$(dv_D/dt)_{crit}, \text{V}/\mu\text{s}$	200	320	500	1000	1600	2000	2500
						Symbol of Group							
						E2	C2		B2				
						$t_{qf}, \mu\text{s}$	500	630		800			

OVERALL DIMENSIONS



**Dimensions for reference.*

All dimensions in millimeters