

DOSEMI

IGBT

DG75H12T2E

1200V/75A IGBT with Diode

General Description

DOSEMI IGBT Power Discrete provides ultra low conduction loss as well as low switching loss. They are designed for the applications such as general inverters and UPS.


Features

- Low $V_{CE(sat)}$ Trench IGBT technology
- Low switching loss
- Maximum junction temperature 175°C
- $V_{CE(sat)}$ with positive temperature coefficient
- Fast & soft reverse recovery anti-parallel FWD

Typical Applications

- Solar Power
- Electronic welder
- Uninterruptible power supply

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**IGBT**

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage Transient Gate-Emitter Voltage	± 20 -25/+30	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$ @ $T_C=100^{\circ}\text{C}$	150 75	A
I_{CM}	Pulsed Collector Current t_p limited by T_{vjmax}	225	A
P_D	Maximum Power Dissipation @ $T_{vj}=175^{\circ}\text{C}$	937	W

Diode

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	75	A
I_{FM}	Diode Maximum Forward Current t_p limited by T_{vjmax}	225	A

Discrete

Symbol	Description	Values	Unit
T_{vjop}	Operating Junction Temperature	-40 to +175	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55 to +150	$^{\circ}\text{C}$
T_S	Soldering Temperature, 1.6mm from case for 10s	260	$^{\circ}\text{C}$
M	Mounting Torque, Screw M3	0.6	N.m

IGBT Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=75\text{A}, V_{GE}=15\text{V}, T_{vj}=25^{\circ}\text{C}$		2.10	2.55	V
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_{vj}=150^{\circ}\text{C}$		2.90		
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_{vj}=175^{\circ}\text{C}$		3.15		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=3.0\text{mA}, V_{CE}=V_{GE}, T_{vj}=25^{\circ}\text{C}$	5.0	5.8	6.0	V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_{vj}=25^{\circ}\text{C}$			350	μA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_{vj}=25^{\circ}\text{C}$			100	nA
R_{Gint}	Internal Gate Resistance			5.0		Ω
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=100\text{kHz}, V_{GE}=0\text{V}$		14.5		nF
C_{res}	Reverse Transfer Capacitance			0.4		nF
C_{oes}	Output Capacitance			0.2		nF
Q_G	Gate Charge	$V_{GE}=-8\dots+15\text{V}$		0.65		μC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=10\Omega, LS=40\text{nH}, V_{GE}=-8/+15\text{V}, T_{vj}=25^{\circ}\text{C}$		229		ns
t_r	Rise Time			129		ns
$t_{d(off)}$	Turn-Off Delay Time			336		ns
t_f	Fall Time			120		ns
E_{on}	Turn-On Switching Loss			10.0		mJ
E_{off}	Turn-Off Switching Loss			2.4		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=10\Omega, LS=40\text{nH}, V_{GE}=-8/+15\text{V}, T_{vj}=150^{\circ}\text{C}$		235		ns
t_r	Rise Time			132		ns
$t_{d(off)}$	Turn-Off Delay Time			382		ns
t_f	Fall Time			121		ns
E_{on}	Turn-On Switching Loss			12.5		mJ
E_{off}	Turn-Off Switching Loss			2.9		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=10\Omega, LS=40\text{nH}, V_{GE}=-8/+15\text{V}, T_{vj}=175^{\circ}\text{C}$		235		ns
t_r	Rise Time			132		ns
$t_{d(off)}$	Turn-Off Delay Time			385		ns
t_f	Fall Time			122		ns
E_{on}	Turn-On Switching Loss			13.5		mJ
E_{off}	Turn-Off Switching Loss			3.0		mJ

Diode Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_F=75\text{A}, V_{GE}=0\text{V}, T_{vj}=25^{\circ}\text{C}$		1.75	2.2	V
		$I_F=75\text{A}, V_{GE}=0\text{V}, T_{vj}=150^{\circ}\text{C}$		1.70		
		$I_F=75\text{A}, V_{GE}=0\text{V}, T_{vj}=175^{\circ}\text{C}$		1.70		
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=460\text{A}/\mu\text{s}, V_{GE}=-8\text{V}$ $LS=40\text{nH}, T_{vj}=25^{\circ}\text{C}$		4.5		μC
t_{rr}	Recovered Time			276		ns
I_{RM}	Peak Reverse Recovery Current			23		A
E_{rec}	Reverse Recovery Energy			1.40		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=470\text{A}/\mu\text{s}, V_{GE}=-8\text{V}$ $LS=40\text{nH}, T_{vj}=150^{\circ}\text{C}$		9.3		μC
t_{rr}	Recovered Time			362		ns
I_{RM}	Peak Reverse Recovery Current			38		A
E_{rec}	Reverse Recovery Energy			2.90		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=480\text{A}/\mu\text{s}, V_{GE}=-8\text{V}$ $LS=40\text{nH}, T_{vj}=175^{\circ}\text{C}$		10.0		μC
t_{rr}	Recovered Time			377		ns
I_{RM}	Peak Reverse Recovery Current			40		A
E_{rec}	Reverse Recovery Energy			3.25		mJ

Discrete Characteristics $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
R_{thJC}	Junction-to-Case (per IGBT)			0.160	K/W
	Junction-to-Case (per Diode)			0.308	
R_{thJA}	Junction-to-Ambient		40		K/W




Fig 1. IGBT-inverter Output Characteristics




Fig 2. IGBT Output Characteristics




Fig 3. IGBT Output Characteristics












Fig 4. IGBT Transfer Characteristics

Fig 5. IGBT Switching Times as I_C Fig 6. IGBT Switching Times as R_G Fig 7. IGBT Switching Times vs. T_{vj} Fig 8. Switching Energy Loss vs. I_C

Fig 11. Switching Energy Loss vs. V_{CE} Fig 12. IGBT Gate Charge vs. V_{CE}




Fig 13. IGBT Capacity Characteristic




Fig 14 . RBSOA




Fig 15. IGBT Transient Thermal Impedance








Fig 16. Diode Forward Characteristics

Fig 17. Reverse Recovery Time vs. di_F/d_t Fig 18. Reverse Recovery Charge vs. di_F/d_t Fig 19. Reverse Recovery Current vs. di_F/d_t Fig 20. Reverse Energy Losses vs. di_F/d_t






Fig 21. Diode Transient Thermal Impedance

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.