

STARPOWER

SEMICONDUCTOR™

IGBT

GD200HFU120C2S

Molding Type Module

1200V/200A 2 in one-package


General Description

STARPOWER IGBT Power Module provides ultrafast Switching speed as well as short circuit ruggedness. It's designed for the applications such as electronic welders and Inductive heating.



Features

- High short circuit capability, self limiting to $6 \cdot I_{Cnom}$
- Rugged with ultrafast performance
- Low t_{rr} and I_{rr}
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- 10us short circuit capability
- Isolated copper baseplate using DBC Direct Copper Bonding technology



Typical Applications

- Switching mode power supplies up to 40kHz
- Resonant inverters up to 100kHz
- Inductive heating
- UPS
- Electronic welders at $f_{sw} > 20kHz$

Equivalent Circuit Schematic

Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Description	GD200HFU120C2S	Units
V_{CES}	Collector-Emitter Voltage	1200	V

Symbol	Description	GD200HFU120C2S	Units
V_{GES}	Gate-Emitter Voltage	$\pm 20V$	V
I_C	Collector Current @25°C @80°C	280	A
		200	
$I_{CM(1)}$	Pulsed Collector Current @80°C	400	A
I_F	Diode Continuous Forward Current	200	A
I_{FM}	Diode Maximum Forward Current	400	A
P_D	Maximum power Dissipation @ Tc=25°C	1400	W
T_{SC}	Short Circuit Withstand Time @Tc=125°C	10	us
T_J	Operating Junction Temperature	-40 to +150	°C
T_{STG}	Storage Temperature Range	-40 to +125	°C
I^2t -value, Diode	$V_R=0V, t=10ms, T_J=125^\circ C$	18000	A ² s
V_{ISO}	Isolation Voltage RMS, f=50Hz, t=1min	2500	V
Mounting Torque	Power Terminal Screw:M6	2.5 to 5	N.m
	Mounting Screw:M6	3 to 5	N.m

Notes:

(1) Repetitive rating: Pulse width limited by max. junction temperature

Electrical Characteristics of IGBT Tc=25°C unless otherwise noted**Off Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$B_{V_{CES}}$	Collector-Emitter Breakdown Voltage	$T_J=25^\circ C$	1200			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0V$		0.20	0.50	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0V$ @ $T_J=25^\circ C$			200	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=4mA, V_{CE}=V_{GE}$	4.4	5.0	6.0	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=200A, V_{GE}=15V,$ @25°C		3.50	3.7	V
		$I_C=200A, V_{GE}=15V,$ @125°C		3.65		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=200A, R_G=4.7\Omega, V_{GE} = \pm 15V, \text{Inductive Load, } T_C = 25^\circ C$		64		ns
t_r	Rise Time			28		ns
$t_{d(off)}$	Turn-Off Delay Time			320		ns
t_f	Fall Time			40		ns

E_{on}	Turn-On Switching Loss	$V_{CC}=600V, I_C=200A, R_G=4.7\Omega, V_{GE} = \pm 15V,$ Inductive Load, $T_C = 125^\circ C$		4		mJ
E_{off}	Turn-Off Switching Loss			6.0		mJ
$t_{d(on)}$	Turn-On Delay Time			70		ns
t_r	Rise Time			30		ns
$t_{d(off)}$	Turn-Off Delay Time			352		ns
t_f	Fall Time			45		ns
E_{on}	Turn-On Switching Loss	$V_{CC}=600V, V_{GE} = 20V@T_C = 125^\circ C$	10			us
E_{off}	Turn-Off Switching Loss			12		mJ
T_{SC}	Short Circuit Withstand Time					
C_{ies}	Input Capacitance	$V_{CE} = 25V, f=1MHz, V_{GE} = 0V$		9		nF
C_{oes}	Output Capacitance			0.8		nF
C_{res}	Reverse Transfer Capacitance			0.45		nF
L_{CE}	Stray inductance			15	20	nH
$R_{CC'+EE'}$	Module lead resistance, terminal to chip	$T_C = 125^\circ C$		0.5		m Ω

Electrical Characteristics of DIODE $T_C=25^\circ C$ unless otherwise noted

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case (IGBT Part, per 1/2 Module)		0.10	$^\circ C/W$
$R_{\theta JC}$	Junction-to-Case (DIODE Part, per 1/2 Module)		0.20	$^\circ C/W$
$R_{\theta CS}$	Case-to-Sink (Conductive grease applied)	0.04		$^\circ C/W$
Weight	Weight of Module	300		g




Fig 1. Typical Output Characteristics




Fig 2. Typical transfer Characteristics




Fig 3. Switching Loss vs. Collector Current




Fig 4. Switching Loss vs. Gate Resistance




Fig 5. Gate Charge Characteristics.






Fig 6. Typical Capacitance vs. Collector-Emitter Current

Fig 7. Typical Switching Times vs. I_C Fig 8. Typical Switching Times vs. R_G




Fig 9. Typical Forward Characteristics (diode)




Fig 10. Diode reverse recovery charge




Fig 11. transient thermal impedance IGBT





Fig 12. Transient thermal impedance diode

Package Dimension

Dimensions in Millimeters



Terms and Conditions of usage

The data contained in this product datasheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.com), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or life endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.