

STARPOWER

SEMICONDUCTOR™

IGBT

GD50MLT60L2S

Preliminary

Molding Type Module**600V/50A 3-level in one-package**

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as solar power.



Features

- Low $V_{CE(sat)}$ trench IGBT technology
- Low switching losses
- 5 μ s short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

Typical Applications

- 3-level application
- Solar power
- UPS

IGBT-inverter $T_C=25^{\circ}\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD50MLT60L2S	Units
V_{CES}	Collector-Emitter Voltage @ $T_j=25^{\circ}\text{C}$	600	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	85	A
	@ $T_C=80^{\circ}\text{C}$	50	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	100	A
P_{tot}	Total Power Dissipation @ $T_j=175^{\circ}\text{C}$	214	W

Off Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^{\circ}\text{C}$	600			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V},$ $T_j=25^{\circ}\text{C}$			1.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V},$ $T_j=25^{\circ}\text{C}$			400	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.4\text{mA}, V_{CE}=V_{GE},$ $T_j=25^{\circ}\text{C}$	4.0	5.5	6.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=50\text{A}, V_{GE}=15\text{V},$ $T_j=25^{\circ}\text{C}$		1.65	2.15	V
		$I_C=50\text{A}, V_{GE}=15\text{V},$ $T_j=175^{\circ}\text{C}$		2.05		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Q_G	Total Gate Charge	$V_{CC}=400\text{V}, I_C=50\text{A},$ $V_{GE}=15\text{V}$		95		nC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=400\text{V}, I_C=50\text{A},$ $R_G=10\Omega, V_{GE}=15\text{V},$ $T_j=25^{\circ}\text{C}$		55		ns
t_r	Rise Time			45		ns
$t_{d(off)}$	Turn-Off Delay Time			146		ns
t_f	Fall Time			36		ns
E_{on}	Turn-On Switching Loss			0.64		mJ
E_{off}	Turn-Off Switching Loss			1.29		mJ

$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=400V, I_C=50A,$ $R_G=10\Omega, V_{GE}=15V,$ $T_J=175^\circ C$		58		ns
t_r	Rise Time			49		ns
$t_{d(off)}$	Turn-Off Delay Time			166		ns
t_f	Fall Time			46		ns
E_{on}	Turn-On Switching Loss			1.64		mJ
E_{off}	Turn-Off Switching Loss			1.60		mJ
C_{ies}	Input Capacitance	$V_{CE}=30V, f=1Mhz,$ $V_{GE}=0V$		3.03		nF
C_{oes}	Output Capacitance			0.25		nF
C_{res}	Reverse Transfer Capacitance			0.09		nF
I_{SC}	SC Data	$T_P \leq 5\mu s, V_{GE}=15V,$ $T_J=125^\circ C, V_{CC}=360V,$ $V_{CEM} \leq 600V$		TBD		A

DIODE-inverter $T_C=25^\circ C$ unless otherwise noted

Maximum Rated Values

Symbol	Description	GD50MLT60L2S	Units
V_{RRM}	Collector-Emitter Voltage @ $T_J=25^\circ C$	600	V
I_F	DC Forward Current @ $T_C=80^\circ C$	50	A
I_{FRM}	Repetitive Peak Forward Current $t_p=1ms$	100	A

Characteristics Values

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
V _F	Diode Forward Voltage	I _F =50A,V _{GE} =0V	T _j =25°C		1.35	1.75	V
			T _j =125°C		1.35		
Q _{rr}	Recovered Charge	I _F =50A, V _R =300V, di/dt=-2600A/μs, V _{GE} =-15V	T _j =25°C		1.9		ns
			T _j =125°C		3.1		
I _{RM}	Peak Reverse Recovery Current		T _j =25°C		55		A
			T _j =125°C		63		
E _{rec}	Reverse Recovery Energy		T _j =25°C		0.39		mJ
			T _j =125°C		0.68		

DIODE D5 D6 $T_C=25^{\circ}\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD50MLT60L2S	Units
V_{RRM}	Collector-Emitter Voltage @ $T_J=25^{\circ}\text{C}$	600	V
I_F	DC Forward Current @ $T_C=80^{\circ}\text{C}$	50	A
I_{FRM}	Repetitive Peak Forward Current $t_p=1\text{ms}$	100	A

Characteristics Values

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
V _F	Diode Forward Voltage	I _F =50A,V _{GE} =0V	T _j =25°C		1.35	1.75	V
			T _j =125°C		1.35		
Q _{rr}	Recovered Charge	I _F =50A, V _R =300V, di/dt=-2600A/μs, V _{GE} =-15V	T _j =25°C		1.9		ns
			T _j =125°C		3.1		
I _{RM}	Peak Reverse Recovery Current		T _j =25°C		55		A
			T _j =125°C		63		
E _{rec}	Reverse Recovery Energy		T _j =25°C		0.39		mJ
			T _j =125°C		0.68		


Electrical Characteristics of NTC $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
R_{25}	Rated Resistance			5.0		$\text{k}\Omega$
$\Delta R/R$	Deviation of R_{100}	$T_C=100^{\circ}\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

IGBT Module


Symbol	Parameter	Min.	Typ.	Max.	Units
V _{ISO}	Isolation Voltage RMS, f=50Hz, t=1min		2500		V
L _{CE}	Stray Inductance		15		nH
R _{CC'+EE'}	Module Lead Resistance, Terminal to Chip @ T _C =25 °C		2.00		m Ω
R _{θJC}	Junction-to-Case (per IGBT-inverter)			0.70	K/W
	Junction-to-Case (per DIODE-inverter)			0.81	
	Junction-to-Case (per DIODE D5 D6)			0.81	
T _{jmax}	Maximum Junction Temperature			175	°C
T _{STG}	Storage Temperature Range	-40		125	°C
F	Mounting Force Per Clamp	20		50	N
G	Weight of Module		24		g

Equivalent Circuit Schematic



Package Dimension

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or life endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.