

STARPOWER

SEMICONDUCTOR

IGBT

GD600HFL120P1S

Molding Type Module**1200V/600A 2 in one-package**

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as wind and solar power.



Features

- Low $V_{CE(sat)}$ SPT+ IGBT technology
- 10 μ s short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- High power and thermal cycling capability

Typical Applications

- Auxiliary Inverters
- High Power Converters
- UPS
- Wind and Solar Power
- Traction Drives

Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Description	GD600HFL120P1S	Units
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$ @ $T_C=100^{\circ}\text{C}$	1000 600	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	1200	A
I_F	Diode Continuous Forward Current @ $T_C=100^{\circ}\text{C}$	600	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	1200	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	4.02	kW
T_{jmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}$, $t=1\text{min}$	4000	V
Mounting Torque	Power Terminal Screw:M4	1.8 to 2.1	N.m
	Power Terminal Screw:M8	8.0 to 10	N.m
	Mounting Screw:M5	3.0 to 6.0	N.m

Electrical Characteristics of IGBT $T_C=25^{\circ}\text{C}$ unless otherwise noted**Off Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^{\circ}\text{C}$	1200			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}$, $V_{GE}=0\text{V}$, $T_j=25^{\circ}\text{C}$			5.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}$, $V_{CE}=0\text{V}$, $T_j=25^{\circ}\text{C}$			400	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=24.0\text{mA}$, $V_{CE}=V_{GE}$, $T_j=25^{\circ}\text{C}$	5.0	6.2	7.0	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=600\text{A}$, $V_{GE}=15\text{V}$, $T_j=25^{\circ}\text{C}$		1.90	2.35	V
		$I_C=600\text{A}$, $V_{GE}=15\text{V}$, $T_j=125^{\circ}\text{C}$		2.10		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=600A,$ $R_{Gon}=1.8\Omega,$ $R_{Goff}=2.2\Omega,$ $V_{GE}=\pm 15V,$ $T_j=25^\circ C$		150		ns
t_r	Rise Time			80		ns
$t_{d(off)}$	Turn-Off Delay Time			450		ns
t_f	Fall Time			100		ns
E_{on}	Turn-On Switching Loss			65.1		mJ
E_{off}	Turn-Off Switching Loss			45.5		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=600A,$ $R_{Gon}=1.8\Omega,$ $R_{Goff}=2.2\Omega,$ $V_{GE}=\pm 15V,$ $T_j=125^\circ C$		180		ns
t_r	Rise Time			90		ns
$t_{d(off)}$	Turn-Off Delay Time			500		ns
t_f	Fall Time			130		ns
E_{on}	Turn-On Switching Loss			82.5		mJ
E_{off}	Turn-Off Switching Loss			58.1		mJ
C_{ies}	Input Capacitance	$V_{CE}=25V, f=1MHz,$ $V_{GE}=0V$		44.6		nF
C_{oes}	Output Capacitance			3.12		nF
C_{res}	Reverse Transfer Capacitance			2.04		nF
I_{SC}	SC Data	$t_p \leq 10\mu s, V_{GE}=15V,$ $T_j=125^\circ C, V_{CC}=900V,$ $V_{CEM} \leq 1200V$		2820		A
R_{Gint}	Internal Gate Resistance			1.2		Ω
Q_G	Gate Charge	$V_{CC}=600V, I_C=600A,$ $V_{GE}=-15 \sim +15V$		6.3		μC
L_{CE}	Stray Inductance			18		nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal To Chip			0.30		m Ω

Electrical Characteristics of Diode $T_C=25^\circ C$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=600A$	$T_j=25^\circ C$	1.60	2.25	V
			$T_j=125^\circ C$	1.65		
Q_r	Recovered Charge	$I_F=600A,$ $V_R=600V,$ $R_G=1.8\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$	65.5		μC
			$T_j=125^\circ C$	120		
I_{RM}	Peak Reverse Recovery Current		$T_j=25^\circ C$	420		A
			$T_j=125^\circ C$	480		
E_{rec}	Reverse Recovery Energy		$T_j=25^\circ C$	26.0		mJ
			$T_j=125^\circ C$	50.2		


Electrical Characteristics of NTC $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
R_{25}	Rated Resistance			5.0		k Ω
$\Delta R/R$	Deviation of R_{100}	$T_C=100^{\circ}\text{C}, R_{100}=493\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

Thermal Characteristics


Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case (per IGBT)		37.3	K/kW
$R_{\theta JC}$	Junction-to-Case (per Diode)		57.3	K/kW
$R_{\theta CS}$	Case-to-Sink (Conductive grease applied)	4.5		K/kW
Weight	Weight of Module	825		g

Equivalent Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.