

STARPOWER

SEMICONDUCTOR

SiC MOSFET

MD17HTC75P6HE

750V/1.70mΩ 6 in one-package

General Description

STARPOWER MOSFET Power Module provides very low $R_{DS(on)}$ as well as optimized intrinsic diode. It's designed for the applications such as hybrid and electric vehicle.


Features

- SiC power MOSFET
- High blocking voltage with low $R_{DS(on)}$
- Easy to parallel and simple to drive
- Low inductance case avoid oscillations
- Isolated copper pinfin baseplate using Si_3N_4 AMB technology

Typical Applications

- Automotive application
- Hybrid and electric vehicle
- Inverter for motor drive

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_F=25^{\circ}\text{C}$ unless otherwise noted**MOSFET**

Symbol	Description	Value	Unit
V_{DSS}	Drain-Source Voltage	750	V
V_{GSSmax}	Gate-Source Voltage	-8/+19	V
V_{GSSop}	Gate-Source Voltage	-4...0/+15	V
I_D	Drain Current @ $T_F=75^{\circ}\text{C}$	485	A
I_{DM}	Pulsed Drain Current, t_p limited by T_{jmax}	970	A
P_D	Maximum Power Dissipation @ $T_F=75^{\circ}\text{C}$ $T_j=175^{\circ}\text{C}$	719	W

Body Diode

Symbol	Description	Value	Unit
I_S	Source Current @ $T_F=75^{\circ}\text{C}$	173	A

Module

Symbol	Description	Value	Unit
T_{jmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +175	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}$, $t=1\text{min}$	2500	V

MOSFET Characteristics $T_F=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$R_{DS(on)}$	Static Drain-Source On-Resistance	$I_D=490\text{A}, V_{GS}=15\text{V}, T_j=25^\circ\text{C}$		1.70	2.25	$\text{m}\Omega$
		$I_D=490\text{A}, V_{GS}=15\text{V}, T_j=175^\circ\text{C}$		2.50		
$V_{GS(th)}$	Gate-Source Threshold Voltage	$I_D=135\text{mA}, V_{DS}=V_{GS}, T_j=25^\circ\text{C}$	1.8	2.4	3.6	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=V_{DSS}, V_{GS}=0\text{V}, T_j=25^\circ\text{C}$			500	μA
I_{GSS}	Gate-Source Leakage Current	$V_{GS}=19\text{V}, V_{DS}=0\text{V}, T_j=25^\circ\text{C}$			600	nA
R_{Gint}	Internal Gate Resistance			0.86		Ω
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=470\text{V}, f=100\text{kHz}$		43.1		nF
C_{oss}	Output Capacitance			2.78		nF
C_{rss}	Reverse Transfer Capacitance			0.23		nF
Q_g	Total Gate Charge	$I_D=490\text{A}, V_{DS}=470\text{V}, V_{GS}=-4/+15\text{V}$		0.88		μC
$t_{d(on)}$	Turn-On Delay Time	$V_{DS}=470\text{V}, I_D=490\text{A}, R_{Gon}=1.5\Omega, R_{Goff}=3.3\Omega, L_S=25\text{nH}, V_{GS}=-4/+15\text{V}, T_j=25^\circ\text{C}$		75		ns
t_r	Rise Time			51		ns
$t_{d(off)}$	Turn-Off Delay Time			370		ns
t_f	Fall Time			59		ns
E_{on}	Turn-On Switching Loss			4.85		mJ
E_{off}	Turn-Off Switching Loss			16.8		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{DS}=470\text{V}, I_D=490\text{A}, R_{Gon}=1.5\Omega, R_{Goff}=3.3\Omega, L_S=25\text{nH}, V_{GS}=-4/+15\text{V}, T_j=150^\circ\text{C}$		76		ns
t_r	Rise Time			52		ns
$t_{d(off)}$	Turn-Off Delay Time			447		ns
t_f	Fall Time			58		ns
E_{on}	Turn-On Switching Loss			5.00		mJ
E_{off}	Turn-Off Switching Loss			17.9		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{DS}=470\text{V}, I_D=490\text{A}, R_{Gon}=1.5\Omega, R_{Goff}=3.3\Omega, L_S=25\text{nH}, V_{GS}=-4/+15\text{V}, T_j=175^\circ\text{C}$		78		ns
t_r	Rise Time			54		ns
$t_{d(off)}$	Turn-Off Delay Time			470		ns
t_f	Fall Time			57		ns
E_{on}	Turn-On Switching Loss			5.41		mJ
E_{off}	Turn-Off Switching Loss			18.9		mJ

Body Diode Characteristics $T_F=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_{SD}	Diode Forward Voltage	$I_S=245\text{A}, V_{GS}=-4\text{V}, T_J=25^{\circ}\text{C}$		4.20		V
		$I_S=245\text{A}, V_{GS}=-4\text{V}, T_J=175^{\circ}\text{C}$		3.80		
Q_r	Diode Reverse Recovery Charge	$V_R=470\text{V}, I_S=490\text{A}, -di/dt=10900\text{A}/\mu\text{s}, L_S=25\text{nH}, V_{GS}=-4\text{V}, T_J=25^{\circ}\text{C}$		3.42		μC
I_{rrm}	Peak Reverse Recovery Current			133		A
E_{rec}	Reverse Recovery Energy			1.83		mJ
Q_r	Diode Reverse Recovery Charge	$V_R=470\text{V}, I_S=490\text{A}, -di/dt=11990\text{A}/\mu\text{s}, L_S=25\text{nH}, V_{GS}=-4\text{V}, T_J=150^{\circ}\text{C}$		4.57		μC
I_{rrm}	Peak Reverse Recovery Current			220		A
E_{rec}	Reverse Recovery Energy			2.31		mJ
Q_r	Diode Reverse Recovery Charge	$V_R=470\text{V}, I_S=490\text{A}, -di/dt=12120\text{A}/\mu\text{s}, L_S=25\text{nH}, V_{GS}=-4\text{V}, T_J=175^{\circ}\text{C}$		6.20		μC
I_{rrm}	Peak Reverse Recovery Current			252		A
E_{rec}	Reverse Recovery Energy			3.37		mJ

NTC Characteristics $T_F=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R_{25}	Rated Resistance			5.0		k Ω
$\Delta R/R$	Deviation of R_{100}	$T_j=100^{\circ}\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K
$B_{25/80}$	B-value	$R_2=R_{25}\exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$		3411		K
$B_{25/100}$	B-value	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298.15\text{K}))]$		3433		K

Module Characteristics $T_F=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
L_{CE}	Stray Inductance		8		nH
Δp	$\Delta V/\Delta t=10.0\text{dm}^3/\text{min}, T_F=75^{\circ}\text{C}$		64		mbar
p	Maximum Pressure In Cooling Circuit			2.5	bar
R_{thJF}	Junction-to-Cooling Fluid (per MOSFET) $\Delta V/\Delta t=10.0\text{dm}^3/\text{min}, T_F=75^{\circ}\text{C}$		0.126	0.139	K/W
M	Terminal Connection Torque, Screw M5 Mounting Torque, Screw M4	3.6 1.8		4.4 2.2	N.m
G	Weight of Module		750		g




Fig 1. MOSFET Output Characteristics




Fig 2. MOSFET Output Characteristics





Fig 3. MOSFET Transfer Characteristics

Fig 4. MOSFET Switching Loss vs. I_{DS}





Fig 5. MOSFET Switching Loss vs. R_G 

Fig 6. Body Diode Characteristics

Fig 7. Body Diode Switching Loss vs. I_S Fig 8. Body Diode Switching Loss vs. R_G



Fig 9. Capacitance vs. V_{DS} 

Fig 10. MOSFET Transient Thermal Impedance






Fig 11. NTC Temperature Characteristic

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.