

**Features**

- Low forward voltage drop
- Soft recovery
- Hermetic metal cases with ceramic insulators


Typical Applications

- Inverters and choppers
- Motor control
- Snubber and free-wheeling diodes

Part No. Y38ZKB-ZT33cT

I_{F(AV)}	950A	
V_{RRM}	200V	400V
	600V	800V
	1000V	

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled, T _C =85°C	150			950	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms	150	200		1000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			50	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			13	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}				845	A ² s*10 ³
V _{FO}	Threshold voltage		150			1.15	V
r _F	Forward slope resistance					0.34	mΩ
V _{FM}	Peak forward voltage	I _{TM} =2400A, F=15kN	25			2.80	V
I _{rm}	Reverse recovery current		150		51		A
t _{rr}	Reverse recovery time	I _{TM} =1000A, tp=4000μs, di/dt=-60A/μs, V _R =100V			3		μs
Q _{rr}	Recovery charge				77	90	μC
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 15kN				0.035	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink					0.008	
F _m	Mounting force			10		20	kN
T _{vj}	Junction temperature			-40		150	°C
T _{stg}	Stored temperature			-40		160	°C
W _i	Weight				250		g
Outline	ZT33cT						

Outline:

TECHSEM reserves the right to change specifications without notice.