



PNP Digital Transistor (Built-in Resistors)



Features

- Halogen free and RoHS compliant.
- Epoxy meets UL-94 V-0 flammability rating.
- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors.

Mechanical data

- **Package:** DFN1006-3L
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Value
Device marking code			52
Supply voltage	V_{CC}	V	-50
Input voltage	V_{IN}	V	-12 to +5
Output current	I_O	mA	-100
Power dissipation	P_D	mW	150
Operation junction temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150



DTA123YL3

RoHS
COMPLIANT

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Input voltage	V _{I(OFF)}	V	V _{CC} =-5V, I _O =-100uA	-0.3		
	V _{I(ON)}	V	V _O =-0.3V, I _O =-20mA			-3.
Output voltage	V _{O(ON)}	V	I _O /I _I =-10mA/-0.5mA			-0.3
Input current	I _I	mA	V _I =-5V			-3.8
Output current	I _{O(OFF)}	uA	V _{CC} =-50V, V _I =0			-0.5
DC current gain	G _I		V _O =-5V, I _O =-10mA	33		
Input resistance	R ₁	kΩ		1.54	2.2	2.86
Resistance ratio	R ₂ /R ₁			3.5	4.5	5.5
Transition frequency	f _T	MHz	I _E =-5mA, V _{CE} =-10V, f=100MHz		250	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	833







Note:1. Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

■ Ordering Information


Preferred P/N	Packing code	Unit weight(mg)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
DTA123YL3	F1	Approximate 0.9	10000	100000	400000	Tape & Reel



■Typical of Characteristics




■ Outline Dimensions



DIMENSIONS			
SYMBOL	Millimeter		
	MIN.	NOM.	MAX.
A	0.42	---	0.55
A1	0.025REF		
b	0.45	0.50	0.55
b1	0.10	0.15	0.20
D	0.95	1.00	1.05
E	0.55	0.60	0.65
E1	0.35BSC		
e	0.65BSC		
L	0.20	0.25	0.30

■ Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.