


1-Line, Uni-directional, Transient Voltage Suppressor



DFN1006-2L

Features

- Ultra small package
- Stand-off voltage: 48V Max
- Transient protection for each line according to IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-5(surge): 4A (8/20 μs)
- Ultra-low capacitance: $C_J = 20\text{ pF}$ typ
- Low leakage current
- Low clamping voltage
- RoHS Compliant

Applications


- Cellular Handsets and Accessories
- Personal Digital Assistants
- Notebooks and Handhelds
- Portable Instrumentation
- Peripherals
- Pagers Peripherals
- Desktop and Servers

Mechanical Characteristics

- Package: DFN1006-2L
- Case Material: "Green" Molding Compound.
- Marking Information: See Below



■Definitions of electrical characteristics





ESD48VL

■Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	380	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	4	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	KV
Junction temperature	T_J	125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				48
Reverse breakdown voltage	V_{BR}	V	$I_{BR} = 1mA$	50		61
Reverse leakage current	I_R	nA	$V_{RWM} = 48V$			500
Clamping voltage ³⁾	V_{CL}	V	$I_{PP} = 1A, t_p = 8/20\mu s$			75
		V	$I_{PP} = 4A, t_p = 8/20\mu s$			95
Junction capacitance	C_J	pF	$V_R = 0V, f = 1MHz$		20	25

- (1). TLP parameter: $Z_0 = 50\Omega$, $t_p = 100ns$, $t_r = 2ns$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
 (2). Contact discharge mode, according to IEC61000-4-2.
 (3). Non-repetitive current pulse, according to IEC61000-4-5.


■Ordering Information (Example)

PREFERED P/N	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD48VL	Approximate 4	3000	30000	120000	Tape& reel




■ Typical Performance Characteristics (Ta=25°C unless otherwise Specified)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reverse voltage



Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature







TLP Measurement



■ Outline Dimensions



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	0.50	0.60	0.70
E	0.90	1.00	1.10
A	0.35	0.45	0.55
A1	0.15 BSC		
A2			0.10
F	0.005		
G	0.005		
L	0.15	0.25	0.35
b	0.41	0.50	0.59
e	0.65 BSC		

Note:

1. Controlling dimension: In millimeters.
2. General tolerance: ± 0.10 mm.
3. The pad layout is for reference purposes only.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.