

Schottky Rectifier Modules



V_{RRM} 60V
I_{FAV} 2X100 A


Applications

- Plating Power Supply
- High Frequency Power Supply
- High Current Switching Power Supply
- Reverse Battery Protection
- Welding Matching

Features

- Center Tap Module
- High Frequency Operation
- Low Forward Voltage
- Dual Diode Construction; May be Paralleled for High Current Output
- Lead (Pb)-free
- Designed and qualified for industrial level

Circuit



Maximum Ratings

Symbol	Conditions	Values	Units
V _R		60	V
I _{F(AV)}	T _C =125°C, Per Diode	100	A
	T _C =125°C, Per Module	200	A
I _{FSM}	1/2 Cycle, 50Hz, Sine	1500	A
I ² t	T _J =45°C, t=10ms, 50Hz, half Sine	11250	A ² s
T _J		-40 to +150	°C
T _{STG}		-40 to +150	°C
Visol	3600V AC 3s	1	mA
Torque	Recommended (M4)	0.6~1.2	N·m
Torque	Recommended (M4)	0.6~1	N·m
Weight		27	g

Thermal Characteristics


Symbol	Conditions	Values	Units
R _{th(j-c)}	Per diode	0.26	°C/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
I _{RM}	V _R =60V	--	--	1	mA
	V _R =60V, T _J =125°C	--	--	20	mA
V _F	I _F =100A, T _J =25°C	--	0.72	0.75	V
	I _F =100A, T _J =125°C	--	--	0.62	

Package Outline Information

CASE: FJ



DIM	Min (mm)	Max (mm)	Note
A	37.5	38.5	
B	27.5	28.5	
C	12.8	13.5	
D	29.5	30.5	
E	12.1	13.1	
F	14.5	15.5	
G	4.0	4.4	Ø
H	3.7	4.3	
I	3.3	3.9	
J	9.5	10.5	
K	3.7	4.3	
L	5.0	5.5	
M	4.0	4.4	
N	11.7	12.3	
O	1.8	2.2	

Packing Standard

Item	Length: A (mm)	Width: B (mm)	Height: C (mm)	Quantity (PCS)
Inner EPE	252	246	25	25
Inner Box	290	252	40	25
Outer Carton	300	270	280	150



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.