



SiC Schottky Power Modules

V_{RRM} 1200V
I_{FAV} 2 × 40 A


Applications

- Welding Equipment
- Uninterruptible Power Supply (UPS)
- High Frequency Power Supply
- Induction Heating
- High Speed Rectifiers

Features

- **SiC Schottky Diode:**
 - Zero reverse recovery
 - Zero forward recovery
 - Temperature independent switching behavior
 - Positive temperature coefficient VF
- Very low stray inductance
- High level of integration
- Low Forward Voltage
- Isolated package (SOT-227)
- Low noise switching
- RoHS Compliant

Circuit



Maximum Ratings

Symbol	Conditions	Values	Units
V _R		1200	V
I _{F(AV)}	T _C =25°C, Per diode	80	A
	T _C =25°C, Per Module	160	A
	T _C =135°C, Per diode	40	A
	T _C =135°C, Per Module	80	A
I _{FSM}	1/2 Cycle , 50Hz, Sine	450	A
T _J		-55 to +175	°C
T _{STG}		-55 to +175	°C
Torque	To Sink Recommended (M4)	0.6~1.2	N·m
Torque	To Terminal Recommended (M4)	0.6~1.1	N·m
Weight		27	g

Thermal Characteristics




Symbol	Conditions	Values	Units
R _{th(j-c)}	Per diode	0.3	°C/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
I _{RM}	V _R =1200V	--	1	100	uA
	V _R =1200V, T _J =175°C	--	1	5	mA
V _F	I _F =40A, , T _J =25°C	--	1.5	1.8	V
	I _F =40A, , T _J =175°C	--	2	2.4	




Performance Curves



Package Outline Information

CASE: FJ



DIM	Min (mm)	Max (mm)	Note
A	37.5	38.5	
B	27.5	28.5	
C	12.8	13.5	
D	29.5	30.5	
E	12.1	13.1	
F	14.5	15.5	
G	4.0	4.4	Ø
H	3.7	4.3	
I	3.3	3.9	
J	9.5	10.5	
K	3.7	4.3	
L	5.0	5.5	
M	4.0	4.4	
N	11.7	12.3	
O	1.8	2.2	

Packing Standard

Item	Length: A (mm)	Width: B (mm)	Height: C (mm)	Quantity (PCS)
Inner EPE	252	246	25	25
Inner Box	290	252	40	25
Outer Carton	300	270	280	150



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.