


Schottky Barrier Rectifiers



Features

- High frequency operation
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package:** TO-247AB
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBR40100PT	MBR40150PT	MBR40200PT
Device marking code			MBR40100PT	MBR40150PT	MBR40200PT
Repetitive peak reverse voltage	VRRM	V	100	150	200
Average Rectified Forward Current (Rated VR-20Khz Square Wave) - 50% duty cycle, T _c (FIG 1)	IFAV	A	40		
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T _j =25°C	IFSM	A	300		
Current Squared Time @1ms≤t≤8.3ms T _j =25°C	I ² t	A ² s	373		
Storage temperature	TSTG	°C	-55 ~+175		
Junction temperature	TJ	°C	-55 ~+175		

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MBR40100PT	MBR40150PT	MBR40200PT
Maximum instantaneous forward voltage drop per diode	V _F	V	I _F =20A, T _J =25°C	0.85	0.85	0.9
Maximum DC reverse current at rated DC blocking voltage per diode @ VRM=VRRM	I _{RRM}	mA	VRM=VRRM T _J =25°C	0.1		
			VRM=VRRM T _J =125°C	20		

Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS



MBR40100PT THRU MBR40200PT

■ Thermal Characteristics (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBR40100PT	MBR40150PT	MBR40200PT
Typical Thermal Resistance(Per leg)	R _{θJ-C}	°C/W	1.0		

■ Ordering Information (Example)

PREFERRED P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MBR40100PT THUR MBR40200PT	Approximate 6.0	30	330	1980	Tube

■ Characteristics(Typical)

FIG1:I_o-T_c Curve




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage






FIG4: Instantaneous Reverse Characteristics





MBR40100PT THRU MBR40200PT

■ Outline Dimensions



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ϕP	3.40	3.80
$\phi P1$		7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20



MBR40100PT THRU MBR40200PT

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.