



Rectifier Diode Module

VRRM 2200 to 2800V
IFAV 200A


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- International standard package
- High Surge Capability
- Simple Mounting

Circuit



Blocking Characteristics

TYPE			VRRM	VRSM	Units
MD200C22BD2	MD200A22BD2	MD200K22BD2	2200V	2400V	V
MD200C24BD2	MD200A24BD2	MD200K24BD2	2400V	2600V	V
MD200C26BD2	MD200A26BD2	MD200K26BD2	2600V	2800V	V
MD200C28BD2	MD200A28BD2	MD200K28BD2	2800V	3000V	V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	Single phase ,half wave 180° conduction Tc=100℃	200	A
IFSM	t=10ms Tvj=TVjM	7500	A
i²t	t=10ms Tvj=TVjM	281000	A²s
Visol	a.c.50HZ;r.m.s.;1min,Iiso :2mA(MAX)	3000	V
Tvj		-40 to 150	℃
Tstg		-40 to 125	℃
Mt	To terminals(M6)	6±15%	Nm
Ms	To heatsink(M6)	6±15%	Nm
Weight	Module (Approximately)	320	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	per diode	0.14	℃/W
Rth(c-s)	per diode	0.02	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
VFM	T=25℃ IF =600A			1.45	V
IRRM	Tvj=TVjM V=VRRM			20	mA
VFO	Tvj=TVjM			0.88	V
rF	Tvj=TVjM			1.5	mΩ

Performance Curves




Fig1. Power dissipation




Fig2. Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics



MD200C(A/K)-BD2

Package Outline Information

CASE: BD2





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.