



Rectifier Diode Module

VRRM 1200 to 2000V

IFAV 300A


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- International standard package
- High Surge Capability
- Simple Mounting

Circuit



Blocking Characteristics

TYPE			VRRM	VRS	Units
MD300C12D3	MD300A12D3	MD300K12D3	1200V	1300V	V
MD300C14D3	MD300A14D3	MD300K14D3	1400V	1500V	V
MD300C16D3	MD300A16D3	MD300K16D3	1600V	1760V	V
MD300C18D3	MD300A18D3	MD300K18D3	1800V	2000V	V
MD300C20D3	MD300A20D3	MD300K20D3	2000V	2200V	V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	Single phase ,half wave 180° conduction Tc=100℃	300	A
IFSM	t=10ms Tvj=TvjM	9100	A
i²t	t=10ms Tvj=TvjM	414000	A²s
Visol	a.c.50HZ;r.m.s.;1min,Iiso :2mA(max)	2500	V
Tvj		-40 to 150	℃
Tstg		-40 to 125	℃
Mt	To terminals(M8)	12±15%	Nm
Ms	To heatsink(M6)	6±15%	Nm
Weight	Module (Approximately)	690	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	per diode	0.12	℃/W
Rth(c-s)	per diode	0.04	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
VFM	T=25℃ IF =900A			1.35	V
IRRM	Tvj=TvjM V=VRRM			20	mA
VFO	Tvj=TvjM			0.75	V
rF	Tvj=TvjM			0.55	mΩ

Performance Curves




Fig1. Power dissipation




Fig2. Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics

CASE: D3



Unmarked dimensional tolerance: $\pm 0.5\text{mm}$



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.