



Rectifier Diode Module

VRRM 3000 to 3600V
IFAV 350A


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- International standard package
- High Surge Capability
- Simple Mounting

Circuit



Blocking Characteristics

TYPE			VRRM	VRSM	Units
MD350C30D6	MD350A30D6	MD350K30D6	3000	3100	V
MD350C32D6	MD350A32D6	MD350K32D6	3200	3300	V
MD350C34D6	MD350A34D6	MD350K34D6	3400	3500	V
MD350C36D6	MD350A36D6	MD350K36D6	3600	3700	V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	Single phase ,half wave 180° conduction Tc=100℃	350	A
IFSM	t=10ms Tvj=TVjM	13000	A
i ² t	t=10ms Tvj=TVjM	845000	A ² s
V _{isol}	a.c.50HZ;r.m.s.;1min,I _{iso} :2mA(max)	5600	V
Tvj		-40 to 150	℃
Tstg		-40 to 125	℃
Mt	To terminals(M10)	12±15%	Nm
Ms	To heatsink(M6)	6±15%	Nm
Weight	Module (Approximately)	1550	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	per diode	0.088	℃/W
Rth(c-s)	per diode	0.04	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
V _{FM}	T=25℃ IF =900A			1.76	V
I _{RRM}	Tvj=TVjM V=VRRM			30	mA
V _{FO}	Tvj=TVjM			0.97	V
r _F	Tvj=TVjM			0.72	mΩ

Performance Curves




Fig1. Power dissipation




Fig2. Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics

Package Outline Information

CASE: D6



Dimensions in mm

Unmarked dimensional tolerance: ±0.5mm



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.