




Rectifier Diode Module

VRRM 1200 to 2000V

IFAV 400A


Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- International standard package
- High Surge Capability
- Simple Mounting

Circuit



Blocking Characteristics

TYPE			VRRM	VRSM	Units
MD400C12D5	MD400A12D5	MD400K12D5	1200	1300	V
MD400C14D5	MD400A14D5	MD400K14D5	1400	1500	V
MD400C16D5	MD400A16D5	MD400K16D5	1600	1760	V
MD400C18D5	MD400A18D5	MD400K18D5	1800	2000	V
MD400C20D5	MD400A20D5	MD400K20D5	2000	2200	V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	Single phase ,half wave 180° conduction Tc=100℃	400	A
IFSM	t=10ms Tvj=TVjM	13000	A
i²t	t=10ms Tvj=TVjM	845000	A²s
Visol	a.c.50HZ;r.m.s.;1min,Iiso :2mA(max)	2500	V
Tvj		-40 to 150	℃
Tstg		-40 to 125	℃
Mt	To terminals(M10)	12±15%	Nm
Ms	To heatsink(M6)	6±15%	Nm
Weight	Module (Approximately)	1580	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	per diode	0.082	℃/W
Rth(c-s)	per diode	0.04	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
VFM	T=25℃ IF =1200A			1.25	V
IRRM	Tvj=TVjM V=VRRM			30	mA
VFO	Tvj=TVjM			0.75	V
rF	Tvj=TVjM			0.5	mΩ



Performance Curves




Fig1. Power dissipation




Fig2. Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics

CASE: D5



Unmarked dimensional tolerance: $\pm 0.5\text{mm}$



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.