


PNP General Purpose Amplifier



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- High Conductance
- Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-23
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** M2B

■Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V		-60
Collector-Emitter Voltage	V_{CEO}	V		-40
Emitter-Base Voltage	V_{EBO}	V		-5
Collector Current	I_C	A		-0.6
Collector Power Dissipation	P_C	W		0.25
Junction Temperature	T_J	°C		-55 to +150
Storage Temperature	T_{stg}	°C		-55 to +150



■Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	V _{CBO}	V	IC=-10μA,IE=0	-60	
Collector-emitter breakdown voltage	V _{CEO}	V	IC=-10mA,IB=0	-40	
Emitter-base breakdown voltage	V _{EBO}	V	IE=-10μA,IC=0	-5	
Collector-base cut-off current	I _{CBO}	nA	VCB=-50V,IE=0		-20
Base cut-off current	I _{EBO}	nA	VCE=-3V, IC=0		-10
Collector-emitter cut-off current	I _{CEX}	nA	VCE=-30V, VBE=-0.5V		-50
DC current gain	h _{FE}		VCE=-10V,IC=-0.1mA	52	
	h _{FE}		VCE=-10V,IC=-150mA	100	300
	h _{FE}		VCE=-10V,IC=-500mA	32	
Collector-emitter saturation voltage	V _{CE(sat)}	V	IC=-150mA,IB=-15mA		-0.4
Collector-emitter saturation voltage	V _{CE(sat)}	V	IC=-500mA,IB=-50mA		-0.67
Base-emitter saturation voltage	V _{BE(sat)*}	V	IC=-150mA,IB=-15mA		-1
Base-emitter saturation voltage	V _{BE(sat)*}	V	IC=-500mA,IB=-50mA		-1.2
Transition frequency	Ft	MHz	VCE=-20V,IC=-50mA,f=100MHz	200	
Delay time	td	ns	VCC=-30V,IC=-150mA, IB1=-15mA		10
Rise time	tr	ns			25
Storage time	ts	ns	VCC=-6V,IC=-150mA, IB1= IB2=-15mA		225
Fall time	tf	ns			60

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	RθJ-A ⁽¹⁾	°C/W	417
Thermal resistance, junction-to-case	RθJ-C ⁽¹⁾	°C/W	334

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBT2907	F2	Approximate 0.008	3000	30000	120000	7" reel
MMBT2907	F4	Approximate 0.008	10000	/	210000	13" reel

■Characteristics(Typical)

Fig 1: Static Characteristics




Fig 2: DC Current Gain




Fig 3: Collector-Emitter Saturation Voltage




Fig 4: Base-Emitter Saturation Voltage




Fig 5: Base-Emitter On Voltage




Fig 6: Cob/Cib-V_{CB}/V_{EB}








Fig 7: P_D -Ta Curve




■SOT-23 Package Outline Dimensions



Note:

1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位, 除非另有说明]
2. General tolerances: $\pm 0.10\text{mm}$ unless otherwise specified.
[通用公差为 $\pm 0.10\text{mm}$, 除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
4. All dimensions shown are exclusive of burrs and gate residues. Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5. Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
6. Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸, 不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺, 但是包含了包封错位的最大尺寸]
7. Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面, 共面性最大为0.1mm]

■SOT-23 Soldering Footprint





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.