


NPN Darlington Transistor



Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				3SS
Collector-base voltage	V _{CBO}	V	I _C =100μA, I _E =0	80
Collector-emitter voltage	V _{CEO}	V	I _C =100μA, I _B =0	80
Emitter-base voltage	V _{EBO}	V	I _E =10μA, I _C =0	12
Collector current	I _C	A		0.6
Power dissipation	P _D	mW		300
Junction temperature	T _J	°C		-55 to +150
Storage temperature	T _{STG}	°C		-55 to +150



MMBTA28

RoHS
COMPLIANT

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V _{(BR)CBO}	V	I _C =100μA, I _E =0	80		
Collector-emitter breakdown voltage	V _{(BR)CEO}	V	I _C =10mA, I _B =0	60		
Emitter-base breakdown voltage	V _{(BR)EBO}	V	I _E =10μA, I _C =0	10		
Collector-base cut-off current	I _{CBO}	uA	V _{CB} =60V			0.1
Emitter-base cut-off current	I _{EBO}	uA	V _{EB} =10V			0.1
DC current gain	h _{FE1}		V _{CE} =5V, I _C =10mA	10000		
	h _{FE2}		V _{CE} =-5V, I _C =100mA	10000		
Collector-emitter saturation voltage	V _{CE(sat)1}	V	I _C =10mA, I _B =0.01mA			1.2
	V _{CE(sat)2}	V	I _C =100mA, I _B =0.1mA			1.5
Base-emitter saturation voltage	V _{BE(sat)}	V	I _C =100mA, I _B =0.1mA			3
Base-emitter turn-on voltage	V _{BE(on)}	V	V _{CE} =5V, I _C =100mA			2
Transition frequency	f _T	MHz	V _{CE} =-20V, I _C =-50mA, f=100MHz		170	
Collector-base output capacitance	C _{OB}	pF	V _{CB} =10V, I _E =0A, f=1MHz		3.5	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	417
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	334

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint

■ Characteristics

Fig 1: Static Characteristics




Fig 2: DC Current Gain




Fig 3: Collector-Emitter Saturation Voltage




Fig 4: Base-Emitter Saturation Voltage




Fig 5: Base-Emitter On Voltage





Fig 6: P_D-Ta Curve






MMBTA28

RoHS
COMPLIANT


■ Ordering Information

Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
MMBTA28	F2	Approximate 0.008	3000	30000	120000	7" reel
MMBTA28	F4	Approximate 0.008	10000	/	210000	13" reel

■ Outline Dimensions



■ Suggested Pad Layout



Note:

1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位，除非另有说明]
2. General tolerances: $\pm 0.10\text{mm}$ unless otherwise specified.
[通用公差为 $\pm 0.10\text{mm}$ ，除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
4. All dimensions shown are exclusive of burrs and gate residues. Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5. Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 mm的中筋凸出部分]
6. Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸，不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺，但是包含了包封错位的最大尺寸]
7. Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面，共面性最大为0.1mm]



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.