


PNP General Purpose Amplifier



Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package:** SOT-89
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				1G
Collector-base voltage	V _{CB0}	V	I _C =100uA, I _E =0	-40
Collector-emitter voltage	V _{CE0}	V	I _C =1mA, I _B =0	-40
Emitter-base voltage	V _{EB0}	V	I _E =100uA, I _C =0	-6
Collector current	I _C	A		-4
Peak Collector Current	I _{CM}	A	single pulse ,t _p =1ms	-10
Power dissipation	P _D	mW		550
Junction temperature	T _J	°C		-55 to +150
Storage temperature	T _{STG}	°C		-55 to +150

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V _{(BR)CBO}	V	I _C =-100μA, I _E =0	-40		
Collector-emitter breakdown voltage	V _{(BR)CEO}	V	I _C =-1mA, I _B =0	-40		
Emitter-base breakdown voltage	V _{(BR)EBO}	V	I _E =-100μA, I _C =0	-6		
Collector-base cut-off current	I _{CBO}	nA	V _{CB} =-30V, I _E =0A			-100
Emitter-base cut-off current	I _{EBO}	nA	V _{EB} =-5V, I _B =0A			-100
Collector Cutoff Current	I _{CEO}	μA	V _{CE} =-30V, I _C =0A			-5
DC current gain	h _{FE}		V _{CE} =-2V I _C =-0.5A	250		
			V _{CE} =-2V I _C =-1A	200		
			V _{CE} =-2V I _C =-2A	150		
			V _{CE} =-2V I _C =-5A	50		
Collector-emitter saturation voltage	V _{CE(sat)}	mV	I _C =-0.5A I _B =-5mA			-120
			I _C =-1A I _B =-10mA			-170
			I _C =-2A I _B =-200mA			-160
			I _C =-4A I _B =-200mA			-340
			I _C =-5A I _B =-500mA			-375
Collector-emitter saturation resistance	R _{CE(sat)}	mΩ	I _C =-5A I _B =-500mA			-75
Base-emitter saturation voltage	V _{BE(sat)}	V	I _C =-4A I _B =-200mA			-1.1
			I _C =-5A I _B =-500mA			-1.2
Base-emitter turn-on voltage	V _{BE(ON)}	V	V _{CE} =-2V I _C =-2A			-1.0







■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R _{θJ-A} ⁽¹⁾	°C/W	227
Thermal resistance, junction-to-case	R _{θJ-C} ⁽¹⁾	°C/W	38

Note: (1) The device is installed and tested on 25.4 * 25.4 * 1.5mm P.C.B.



■ Characteristics(Typical)






■ Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
PBSS5540X	F2	Approximate 0.055	1000	8000	32000	7" reel

■ Outline Dimensions



DIM	DIMENSIONS			
	INCHES		MM	
	MIN.	MAX.	MIN.	MAX.
A	0.173	0.181	4.400	4.600
B	0.061 TYP.		1.550 TYP.	
C	0.155	0.167	3.940	4.250
D	0.031	0.047	0.800	1.200
E	0.094	0.102	2.400	2.600
F	0.118 TYP.		3.00 TYP.	
G	0.014	0.019	0.360	0.480
H	0.017	0.022	0.440	0.560
J	0.014	0.017	0.350	0.440
K	0.055	0.063	1.400	1.600
L	0.059 TYP.		1.500 TYP.	
M	0.108 TYP.		2.750 TYP.	

■ Suggested Pad Layout



UNIT:MM



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.