


N-Channel Enhancement Mode Field Effect Transistor



SOT-23

Product Summary

- V_{DS} 100V
- I_D 3A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) <140 mohm
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) <300 mohm

General Description

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- DC-DC Converters
- Power management functions

■ Absolute Maximum Ratings ($T_A=25^{\circ}C$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	100	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_A=25^{\circ}C$	I_D	3	A
	$T_A=70^{\circ}C$		2.4	
Pulsed Drain Current ^A		I_{DM}	12	A
Avalanche energy ^B		E_{AS}	1.3	mJ
Total Power Dissipation ^C	$T_A=25^{\circ}C$	P_D	1.2	W
	$T_A=70^{\circ}C$		0.8	
Junction and Storage Temperature Range		T_J, T_{STG}	-55~+150	$^{\circ}C$

■ Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient ^D	$t \leq 10S$	$R_{\theta JA}$	82	104	$^{\circ}C/W$
Thermal Resistance Junction-to-Ambient ^{D E}	Steady-State		111	140	
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JL}$	43	52	

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJL03G10A	F2	1003.	3000	30000	120000	7"Reel



YJL03G10A

■ Electrical Characteristics (T_j=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =250μA	100			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100,V _{GS} =0V			1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA	1.0	1.8	2.5	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D =3A		110	140	mΩ
		V _{GS} = 4.5V, I _D =2A		160	300	mΩ
Diode Forward Voltage	V _{SD}	I _S =3A,V _{GS} =0V			1.3	V
Maximum Body-Diode Continuous Current	I _S				3	A
Gate resistance	R _G	f= 1 MHz		8		Ω
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =50V,V _{GS} =0V,f=100KHZ		206		pF
Output Capacitance	C _{oss}			28.9		
Reverse Transfer Capacitance	C _{rss}			1.4		
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =10V,V _{DS} =50V,I _D =3A		4.3		nC
Gate-Source Charge	Q _{gs}			1.5		
Gate-Drain Charge	Q _{gd}			1.1		
Reverse Recovery Chrage	Q _{rr}	I _F =3A, di/dt=100A/us		39.4		ns
Reverse Recovery Time	t _{rr}			32.1		
Turn-on Delay Time	t _{D(on)}	V _{GS} =10V, V _{DD} =50V,I _D =3A R _{GEN} =2Ω		14.7		
Turn-on Rise Time	t _r			3.5		
Turn-off Delay Time	t _{D(off)}			20.9		
Turn-off fall Time	t _f			2.7		

A. Repetitive rating; pulse width limited by max. junction temperature.

B. V_{DD}=50V, R_G=25Ω, L=0.5mH.

C. Pd is based on max. junction temperature, using ≤10us junction-to-ambient thermal resistance.

D. The value of R_{θJA} is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design.

E. The R_{θJA} is the sum of the thermal impedance from junction to lead R_{θJL} and lead to ambient



■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. : On-Resistance vs. Drain Current and Gate Voltage




Figure6.Normalized On-Resistance



YJL03G10A




Figure7. Drain current




Figure8.Safe Operation Area




Figure9.Normalized Maximum Transient thermal impedance




Figure10. Normalized Threshold voltage




Figure 11. On-Resistance vs. Gate to Source Voltage




Figure 12. Forward characteristics of reverse diode




Figure 13. Normalized breakdown voltage





Figure 14. Power dissipation




YJL03G10A


■ SOT-23 Package information




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT: mm

SUGGESTED SOLDER PAD LAYOUT

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.200	0.300	0.500
θ	0°	8°	0°	8°


NOTE:

1. PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.

2. TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.

3. THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

■ Marking Information



Note:

1. All marking is at middle of the product body
2. All marking is in laser printing
3. 1003. is marking code
4. Body color: Black



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.