

ASR180N650D52C

650V, 20A, 180mΩ, N-Channel, Silicon Carbide MOSFET

Product Data Sheet

ASTC-3T04-107A A/1



爱仕特科技
AST TECHNOLOGY

General Description


The AST-D52 series SiC MOSFET in TO-252-3 package ensures stable high-temperature operation for power-dense and energy-critical systems, enabling compact designs with reduced EMI.

Features

- 3rd Generation SiC MOSFET Technology
- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low $R_{DS(on)}$
- RoHS Compliant, Halogen Free

Applications

- LED Driver
- PD Charger
- PC Adapter
- Air-Conditioning
- E-Bike Charger



Ordering Informations

Order Number	ASR180N650D52C
Marking	ASR180N650D52
Package Type	TO-252-3
Packing Method	Tape and Reel

Key Parameters

Symbol	Parameter	Values			Unit	Test Conditions
Absolute maximum rating						
V _{DS}	Drain-Source Voltage	650			V	T _C =25°C
I _D	Drain Current (continuous)	20			A	T _C =25°C
P _D	Power Dissipation	76			W	T _C =25°C
T _J ; Max	Junction Temperature	175			°C	
Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
Static characteristics						
R _{DS(on)}	Static Drain-Source on Resistance	-	300	375	mΩ	V _{GS} =12V; I _D =7A; T _J =25°C
		-	180	215		V _{GS} =15V; I _D =7A; T _J =25°C
		-	130	-		V _{GS} =18V; I _D =7A; T _J =25°C
Dynamic characteristics						
Q _G	Total Gate Charge	-	15.2	-	nC	V _{DS} =400V; V _{GS} =0/+15V; I _D =7A; T _J =25°C
Q _{GD}	Gate-Drain Charge	-	2.6	-		
Source-drain diode						
Q _{rr}	Reverse Recovery Charge	-	68	-	nC	V _{GS} =0V; I _{SD} =7A; V _R =400V; di/dt=2000A/μs; T _i =175°C

Absolute Maximum Ratings (at $T_c=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Values	Unit
V_{DS}	Drain-Source Voltage	650	V
I_D	Drain Current (continuous; $T_c=25^\circ\text{C}$)	20	A
	Drain Current (continuous; $T_c=100^\circ\text{C}$)	14	
I_{DM}	Drain Current (pulsed)	38	A
V_{GS}	Gate-Source Voltage	-10/+22	V
P_D	Power Dissipation ($T_c=25^\circ\text{C}$)	76	W
T_J, T_{stg}	Junction and Storage Temperature Range	-55 to +175	$^\circ\text{C}$

MOSFET Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
Static characteristics (at T _J =25°C unless otherwise specified)						
BV _{DS}	Drain-Source Breakdown Voltage	750	-	-	V	I _D =100μA; V _{GS} =0V
I _{DSS}	Zero Gate Voltage Drain Current	-	0.1	20	μA	V _{DS} =750V; V _{GS} =0V
I _{GSS}	Gate-Body Leakage Current	-	-	±250	nA	V _{GS} =-10 to 20V; V _{DS} =0V
V _{GS(th)}	Gate Threshold Voltage	3.0	3.8	4.6	V	V _{DS} =V _{GS} ; I _D =10mA
V _{GS(on)}	Recommended Turn-on Voltage	-	12/15/18	-	V	Static
V _{GS(off)}	Recommended Turn-off Voltage	-	0	-		
R _{DS(on)}	Static Drain-Source on Resistance	-	300	375	mΩ	V _{GS} =12V; I _D =7A; T _J =25°C
		-	255	-		V _{GS} =12V; I _D =7A; T _J =175°C
		-	180	215		V _{GS} =15V; I _D =7A; T _J =25°C
		-	165	-		V _{GS} =15V; I _D =7A; T _J =175°C
		-	130	-		V _{GS} =18V; I _D =7A; T _J =25°C
		-	143	-		V _{GS} =18V; I _D =7A; T _J =175°C
Dynamic characteristics (at T _J =25°C unless otherwise specified)						
C _{iss}	Input Capacitance	-	431	-	pF	V _{GS} =0V; V _{DS} =650V; f=1MHz
C _{oss}	Output Capacitance	-	32	-		
C _{rss}	Reverse Transfer Capacitance	-	4.2	-		
g _{fs}	Transconductance	-	5	-	S	V _{DS} =20V; I _D =7A
Q _G	Total Gate Charge	-	15.2	-	nC	V _{DS} =400V; V _{GS} =0/+15V; I _D =7A
Q _{GS}	Gate-Source Charge	-	5.5	-		
Q _{GD}	Gate-Drain Charge	-	2.6	-		
R _{G(int)}	Internal Gate Resistance	-	22	-	Ω	f=1MHz; V _{AC} =25mV
E _{on}	Turn-on Energy (Body Diode)	-	69	-	μJ	V _{DS} =400V; V _{GS} =0/+15V; I _D =7A; L=600μH; R _{G(ext)} =5.0Ω; T _J =175°C
E _{off}	Turn-off Energy (Body Diode)	-	12	-		
t _{d(on)}	Turn-on Delay Time	-	29	-	ns	V _{DS} =400V; V _{GS} =0/+15V; I _D =7A; L=600μH; R _{G(ext)} =5.0Ω
t _r	Rise Time	-	14	-		
t _{d(off)}	Turn-off Delay Time	-	43	-		
t _f	Fall Time	-	11	-		

Body Diode Characteristics (at $T_J=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
V_{SD}	Diode Forward Voltage	-	3.6	6	V	$V_{GS}=0\text{V}; I_F=3.5\text{A}; T_J=25^{\circ}\text{C}$
		-	3.3	6		$V_{GS}=0\text{V}; I_F=3.5\text{A}; T_J=175^{\circ}\text{C}$
I_S	Continuous Diode Forward Current	-	20	-	A	$V_{GS}=0\text{V}$
t_{rr}	Reverse Recovery Time	-	26	-	ns	$V_{GS}=0\text{V}; I_{SD}=7\text{A}; V_R=400\text{V};$ $di/dt=2000\text{A}/\mu\text{s}; T_J=175^{\circ}\text{C}$
Q_{rr}	Reverse Recovery Charge	-	68	-	nC	
I_{rm}	Peak Reverse Recovery Current	-	5.6	-	A	

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.98	$^{\circ}\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	40	$^{\circ}\text{C}/\text{W}$

The values are based on Junction-to-Case Thermal Impedance measured with the device mounted to a large heat sink, assuming a maximum junction temperature of $T_{J(max)}=175^{\circ}\text{C}$.

Typical Performance




Figure 1
Output Characteristics ($T_j = 25^\circ\text{C}$)




Figure 2
Output Characteristics ($T_j = 175^\circ\text{C}$)




Figure 3
Normalized On-Resistance vs. Temperature




Figure 4
On-Resistance vs. Temperature

Typical Performance




Figure 5
Transfer Characteristic




Figure 6
Body Diode Characteristic at 25°C




Figure 7
Threshold Voltage vs. Temperature




Figure 8
Gate Charge Characteristics

Typical Performance




Figure 9

Transfer Characteristic




Figure 10

Capacitances vs. Drain-Source




Figure 11

Max Power Dissipation Derating vs T_C




Figure 12

Safe Operating Area

Typical Performance




Figure 13
Switching Energy vs. Drain Current




Figure 14
Switching Energy vs. $R_{G(ext)}$




Figure 15
Switching Energy vs. Temperature




Figure 16
Switching Times vs. $R_{G(ext)}$

Typical Performance





Figure 17

Transient Thermal Impedance

Package Dimensions (mm)

Package Type: TO-252-3



Symbol	Millimeters			Symbol	Millimeters		
	Min.	Type.	Max.		Min.	Type.	Max.
A	2.25	2.30	2.35	F	0.76		
A1	0.96	1.01	1.06	F1	0.08		
A2	0.05	0.10	0.15	F2	1.20 REF		
A3	0.51			F3	0.30 REF		
B	6.45	6.50	6.55	L	9.84	10.04	10.24
C	2.25	2.30	2.35	L1	5.90	6.10	6.30
C1	0.51			L2	5.25 REF		
D	3.70	3.90	4.10	G	1.01	1.06	1.11
D1	5.20	5.40	5.60	N	0.70	0.80	0.90
D2	5.06 REF			S	0.07	0.27	0.47
E	2.29						

Pin	Symbol	Description
1	G	Gate
2	D	Drain
3	S	Source
mb	D	Mounting Base; Connected to Drain

Note:

1. All metal surfaces are Sn plated (matte), except area of cut.
2. Burr or mold flash size (0.5 mm) is not included in the dimensions.

Notes & Disclaimer

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by AST Technology. No communication from any employee or agent of AST Technology or any third party shall effect an amendment or modification of this document.

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, AST Technology hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of AST Technology in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Except as otherwise explicitly approved by AST Technology in a written document signed by authorized representatives, the products of AST Technology may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Contact Info

Tel: +86 755-89300160

Web: <http://www.astsic.com/>

Add: No.1 Rongtian Rd., Pingshan, Shenzhen, China

@2026 Shenzhen AST Technology Company. All Rights Reserved.