



GT10PI120T5H


IGBT Module

Preliminary Data

Features:

- Trench & Field Stop IGBT
- Short Circuit Rated $>10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested($2\times I_c$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Industrial Inverters
- Servo Applications

IGBT, Inverter

Maximum Rated Values ($T_c=25^\circ\text{C}$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage	$T_J=25^\circ\text{C}$	1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_c	Continuous Collector Current	$T_c=100^\circ\text{C}$	10	A
		$T_c=25^\circ\text{C}$	20	A
I_{CM}	Peak Collector Current Repetitive	$t_p=1\text{ms}$	20	A
P_D	Maximum Power Dissipation per IGBT	$T_c=25^\circ\text{C}, T_{Jmax}=175^\circ\text{C}$	137	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1\text{mA}$, $V_{CE}=V_{GE}$, $T_J=25^{\circ}\text{C}$	5.00	5.70	6.50	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=10\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.85	2.00	V
			$T_J=125^{\circ}\text{C}$	2.10		V
			$T_J=150^{\circ}\text{C}$	2.15		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			200	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$, $T_J=25^{\circ}\text{C}$		972		pF
C_{oes}	Output Capacitance			43		
C_{res}	Reverse Transfer Capacitance			12		

Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =10A, R _{Gon} =68Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		101		ns
			T _J =125℃		84		
			T _J =150℃		93		
t _r	Rise Time		T _J =25℃		62		ns
			T _J =125℃		61		
			T _J =150℃		55		
t _{d(off)}	Turn-off Delay Time	V _{CC} =600V, I _C =10A, R _{Goff} =68Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		166		ns
			T _J =125℃		172		
			T _J =150℃		172		
t _f	Fall Time		T _J =25℃		382		ns
			T _J =125℃		573		
			T _J =150℃		546		
E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =10A, R _{Gon} =68Ω, V _{GE} =±15V, di/dt=145A/μs (T _J =150℃), Inductive Load	T _J =25℃		2.25		mJ
			T _J =125℃		2.55		
			T _J =150℃		2.61		



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =10A, R _{Goff} =68Ω, V _{GE} =±15V, du/dt=1532V/μs (T _J =150°C), Inductive Load	T _J =25°C		0.31		mJ
			T _J =125°C		0.62		
			T _J =150°C		0.75		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		340		nC
RBSOA	I _C =20A, V _{CC} =1050V, V _p =1200V, R _G =1Ω, V _{GE} =+15V to 0V, T _J =150°C			Trapezoid			
I _{SC}	V _{CC} =600V, V _{GE} =±15V, R _G =1Ω, T _J =150°C			10			μs
R _{θJC}	Thermal Resistance: Junction-To-Case (per IGBT)					1.093	°C/W

Diode, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current		10	A
I _{FM}	Repetitive Peak Forward Current	tp=1ms	20	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =10A	T _J =25℃		1.70		V
			T _J =125℃		1.80		
			T _J =150℃		1.80		
t _{rr}	Reverse Recovery Time	I _F =10A, -diF/dt=208A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		279		ns
			T _J =125℃		305		
			T _J =150℃		392		
I _{rr}	Peak Reverse Recovery Current		T _J =25℃		6.6		A
			T _J =125℃		7.2		
			T _J =150℃		8.4		
Q _{rr}	Reverse Recovery Charge		T _J =25℃		1.05		μC
			T _J =125℃		1.46		
			T _J =150℃		1.91		



E _{rec}	Reverse Recovery Energy	I _F =10A, -diF/dt=208A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		0.18		mJ
			T _J =125℃		0.25		
			T _J =150℃		0.43		
R _{θJC}	Thermal Resistance: Junction-To-Case (per Diode)					1.451	℃/W

IGBT, Brake-Chopper

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{CES}	Collector-Emitter Blocking Voltage	T _J =25°C	1200	V
V _{GES}	Gate-Emitter Voltage		±20	V
I _C	Continuous Collector Current	T _C =100°C	10	A
		T _C =25°C	20	A
I _{CM}	Repetitive Peak Collector Current	tp=1ms	20	A
P _D	Maximum Power Dissipation per IGBT	T _C =25°C, T _{Jmax} =175°C	137	W

Electrical Characteristics of IGBT (T_C=25°C unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{GE(th)}	Gate-Emitter Threshold Voltage	I _C =1mA, V _{CE} =V _{GE} , T _J =25°C		5.00	5.70	6.50	V
V _{CEsat}	Collector-Emitter Saturation Voltage	I _C =10A, V _{GE} =15V	T _J =25°C		1.85	2.00	V
			T _J =125°C		2.10		V
			T _J =150°C		2.15		V
I _{CES}	Collector-Emitter Leakage Current	V _{GE} =0V, V _{CE} =V _{CES} , T _J =25°C				1	mA
I _{GES}	Gate-Emitter Leakage Current	V _{GE} = ±20V, V _{CE} = 0V, T _J =25°C				200	nA
C _{ies}	Input Capacitance	V _{CE} =25V, V _{GE} =0V, f=100kHz, T _J =25°C			972		pF
C _{oes}	Output Capacitance				43		
C _{res}	Reverse Transfer Capacitance				12		



Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =10A, R _{Gon} =68Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		101		ns	
			T _J =125℃		84			
			T _J =150℃		93			
t _r	Rise Time	V _{CC} =600V, I _C =10A, R _{Gon} =68Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		62		ns	
			T _J =125℃		61			
			T _J =150℃		55			
t _{d(off)}	Turn-off Delay Time	V _{CC} =600V, I _C =10A, R _{Goff} =68Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		166		ns	
			T _J =125℃		172			
			T _J =150℃		172			
t _f	Fall Time		T _J =25℃		382		ns	
			T _J =125℃		573			
			T _J =150℃		546			
E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =10A, R _{Gon} =68Ω, V _{GE} =±15V, di/dt=145A/μs (T _J =150℃) Inductive Load	T _J =25℃		2.25		mJ	
			T _J =125℃		2.55			
			T _J =150℃		2.61			
E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =10A, R _{Goff} =68Ω, V _{GE} =±15V, du/dt=1532V/μs (T _J =150℃) Inductive Load	T _J =25℃		0.31		mJ	
			T _J =125℃		0.62			
			T _J =150℃		0.75			
Q _g	Total Gate Charge	V _{GE} =+15V...-15V				340		nC
RBSOA	I _C =20A, V _{CC} =1050V, V _p =1200V, R _G =68Ω, V _{GE} =+15V to 0V, T _J =150℃				Trapezoid			
SCSOA	V _{CC} =600V, V _{GE} =±15V, R _G =68Ω, T _J =125℃				10			μs
R _{θJC}	IGBT Thermal Resistance: Junction-To-Case (per IGBT)						1.093	℃/W

Diode, Brake-Chopper

Maximum Rated Values ($T_C=25^\circ C$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	$T_J=25^\circ C$	1200	V
I_F	Diode Continuous Forward Current		10	A
I_{FM}	Diode Maximum Forward Current	$t_p=1ms$	20	A



Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =10A	T _J =25℃		1.70		V
			T _J =125℃		1.80		
			T _J =150℃		1.80		
t _{rr}	Reverse Recovery Time	I _F =10A, -diF/dt=208A/μs(T _J =150℃) V _R =600V, V _{GE} = -15V	T _J =25℃		279		ns
			T _J =125℃		305		
			T _J =150℃		392		
I _{rr}	Peak Reverse Recovery Current		T _J =25℃		6.6		A
			T _J =125℃		7.2		
			T _J =150℃		7.4		
Q _{rr}	Reverse Recovery Charge		T _J =25℃		1.05		μC
			T _J =125℃		1.46		
			T _J =150℃		1.91		
E _{rec}	Reverse Recovery Energy		T _J =25℃		0.18		mJ
			T _J =125℃		0.25		
			T _J =150℃		0.43		
R _{θJC}	Diode Thermal Resistance: Junction-To-Case (per Diode)					1.451	℃/W

Diode, Rectifier

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1600	V
I _F	Diode Continuous Forward Current	T _J =25°C	10	A
I _{FRMSM}	Maximum RMS Forward Current per Chip	T _J =80°C	20	A
I _{RMSM}	Maximum RMS Current at Rectifier Output	T _J =80°C	30	A
I _{FSM}	Surge Current @t _p =10ms	T _J =25°C	300	A
		T _J =125°C	250	
I ² t	I ² t - value	T _J =25°C	450	A ² s
		T _J =125°C	312	



Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _F	Forward Voltage	I _F =10A	T _J =25°C		1.05		V
			T _J =125°C		1.00		
I _R	Reverse Current	V _R =1200V	T _J =25°C			1	mA
R _{θJC}	Diode Thermal Resistance: Junction-To-Case (per Diode)					1.074	°C/W

Internal NTC-Thermistor Characteristics

R ₂₅	T _C =25°C	5		kΩ
ΔR/R	T _C =100°C, R ₁₀₀ =465Ω		±5	%
P ₂₅	T _C =25°C	10		mW
B _{25/50}	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15K))]$	3380		K
B _{25/80}	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15K))]$	3440		K
B _{25/100}	$R_2=R_{25} \exp[B_{25/100}(1/T_2-1/(298.15K))]$	3545		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V _{iso}	Isolation Voltage (All Terminals Shorted)	RMS, f=50Hz, 30s	4500			V
Internal Isolation			Al ₂ O ₃			
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+150	°C
CTI	Comparative Tracking Index		200			
R _{θCS}	Case-To-Sink Thermally (Conductive Grease Applied)				0.044	°C/W
M	Mounting Screw:M5		3.0		6.0	N·m
G	Weight			200		g







Ordering Information Table

Device code

G	T	10	PI	120	T5	H
①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Trench, Low Switching Losses IGBT
- ③ - Rated Current (10=10A)
- ④ - Circuit Configuration: (Power Integrated)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)






Fig.5 Typical Switching Loss vs. Collector Current (Inverter)




Fig.6 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.7 Typical Switching Loss vs. Forward Current (Inverter)




Fig.8 Typical Switching Loss vs. Gate Resistance (Inverter)







Fig.11 Typical Saturation Voltage Characteristics (Brake-Chopper) Fig.12 Forward Characteristics of Diode (Brake-Chopper)




Fig.13 Forward Characteristics of Diode (Rectifier)




Fig.14 NTC Temperature Characteristics



Date	Revision	Notes
01/02/2024	01	Initial Release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.