



GT15PI120B2H


IGBT Module

Preliminary Data

Features:

- Field Stop Trench Gate IGBT
- Short Circuit Rated $>10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested($2\times I_c$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Industrial Inverters

IGBT, Inverter

Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_c	Continuous Collector Current	$T_C=100^\circ\text{C}$	15	A
		$T_C=25^\circ\text{C}$	30	A
I_{CM}	Repetitive Peak Collector Current	$T_p=1\text{ms}$	30	A
P_D	Maximum Power Dissipation per IGBT	$T_C=25^\circ\text{C}$, $T_{Jmax}=175^\circ\text{C}$	199	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1\text{mA}$, $V_{CE}=V_{GE}$	5.0	5.9	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=15\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.85	2.00	V
			$T_J=125^{\circ}\text{C}$	2.05		V
			$T_J=150^{\circ}\text{C}$	2.10		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			100	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		1.45		nF
C_{oes}	Output Capacitance			0.10		nF
C_{res}	Reverse Transfer Capacitance			0.06		nF

Switching Characteristics

Switching Characteristics							
$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		85		ns
			$T_J=125^{\circ}C$		89		
			$T_J=150^{\circ}C$		92		
t_r	Rise Time	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		50		ns
			$T_J=125^{\circ}C$		52		
			$T_J=150^{\circ}C$		53		
$t_{d(off)}$	Turn-off Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Goff}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		137		ns
			$T_J=125^{\circ}C$		146		
			$T_J=150^{\circ}C$		151		
t_f	Fall Time	$V_{CC}=600V, I_C=15A,$ $R_{Goff}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		222		ns
			$T_J=125^{\circ}C$		290		
			$T_J=150^{\circ}C$		428		
E_{on}	Turn-on Switching Loss	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ $di/dt=232A/\mu s(T_J=150^{\circ}C),$ Inductive Load	$T_J=25^{\circ}C$		2.35		mJ
			$T_J=125^{\circ}C$		3.03		
			$T_J=150^{\circ}C$		3.29		



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =15A, R _{Goff} =36Ω, V _{GE} =±15V, du/dt=1984V/μs(T _J =150°C), Inductive Load	T _J =25°C		0.70		mJ
			T _J =125°C		1.23		
			T _J =150°C		1.28		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		354		nC
R _G	Internal Gate Resistance				0		Ω
RBSOA	I _C =30A, V _{CC} =1050V, V _p =1200V, R _G =36Ω, V _{GE} =+15V to 0V, T _J =150°C			Trapezoid			
SCSOA	V _{CC} =600V, V _{GE} =±15V, R _{Gon} =36Ω, R _{Goff} =36Ω, T _J =125°C			10			μs
R _{θJC}	Thermal Resistance: Junction-to-Case (per IGBT)					0.753	°C/W

Diode, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	1200	V
I _F	Diode Continuous Forward Current	15	A
I _{FM}	Diode Maximum Forward Current	30	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =15A	T _J =25°C		1.90		V
			T _J =125°C		2.05		
			T _J =150°C		2.00		
t _{rr}	Reverse Recovery Time	I _F =15A, -diF/dt=344A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		154		ns
			T _J =125°C		159		
			T _J =150°C		206		
I _{rr}	Peak Reverse Recovery Current		T _J =25°C		7.8		A
			T _J =125°C		12.2		
			T _J =150°C		12.8		
Q _{rr}	Reverse Recovery Charge		T _J =25°C		0.83		μC
			T _J =125°C		1.22		
			T _J =150°C		1.47		



E _{rec}	Reverse Recovery Energy	I _F =15A, -diF/dt=344A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		0.10		mJ
			T _J =125°C		0.15		
			T _J =150°C		0.17		
R _{θJC}	Thermal Resistance: Junction-To-Case (per Diode)					1.127	°C/W

IGBT, Brake-Chopper

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{CES}	Collector-Emitter Blocking Voltage		1200	V
V _{GES}	Gate-Emitter Voltage		±20	V
I _C	Continuous Collector Current	T _C =100°C	15	A
		T _C =25°C	30	A
I _{CM}	Repetitive Peak Collector Current	t _p =1ms	30	A
P _D	Maximum Power Dissipation per IGBT	T _C =25°C T _{Jmax} =175°C	199	W

Electrical Characteristics of IGBT (T_C=25°C unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{GE(th)}	Gate-Emitter Threshold Voltage	I _C =1mA, V _{CE} =V _{GE}		5.00	5.90	6.50	V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =15A, V _{GE} =15V	T _J =25°C		1.85	2.00	V
			T _J =125°C		2.05		V
			T _J =150°C		2.10		V
I _{CES}	Collector-Emitter Leakage Current	V _{GE} =0V, V _{CE} =V _{CES} , T _J =25°C				1	mA
I _{GES}	Gate-Emitter Leakage Current	V _{GE} =±20V, V _{CE} =0V, T _J =25°C				100	nA
C _{ies}	Input Capacitance	V _{CE} =25V, V _{GE} =0V, f=100kHz			1.45		nF
C _{oes}	Output Capacitance				0.10		nF
C _{res}	Reverse Transfer Capacitance				0.06		nF



Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		85		ns	
			$T_J=125^{\circ}C$		89			
			$T_J=150^{\circ}C$		92			
t_r	Rise Time		$T_J=25^{\circ}C$		50		ns	
			$T_J=125^{\circ}C$		52			
			$T_J=150^{\circ}C$		53			
$t_{d(off)}$	Turn-off Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Goff}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		137		ns	
			$T_J=125^{\circ}C$		146			
			$T_J=150^{\circ}C$		151			
t_f	Fall Time		$T_J=25^{\circ}C$		222		ns	
			$T_J=125^{\circ}C$		290			
			$T_J=150^{\circ}C$		428			
E_{on}	Turn-on Switching Loss	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ $di/dt=232A/\mu s$ ($T_J=150^{\circ}C$), Inductive Load	$T_J=25^{\circ}C$		2.35		mJ	
			$T_J=125^{\circ}C$		3.03			
			$T_J=150^{\circ}C$		3.29			
E_{off}	Turn-off Switching Loss		$V_{CC}=600V, I_C=15A,$ $R_{Goff}=36\Omega, V_{GE}=\pm 15V,$ $du/dt=1984V/\mu s$ ($T_J=150^{\circ}C$), Inductive Load	$T_J=25^{\circ}C$		0.70		mJ
				$T_J=125^{\circ}C$		1.23		
				$T_J=150^{\circ}C$		1.28		
Q_g	Total Gate Charge	$V_{GE}=+15V \dots -15V$		$T_J=25^{\circ}C$		354		nC
R_G	Internal Gate Resistance				0		Ω	
RBSOA	$I_C=30A, V_{CC}=1050V, V_p=1200V, R_G=36\Omega, V_{GE}=+15V$ to $0V, T_J=150^{\circ}C$			Trapezoid				
SCSOA	$V_{CC}=600V, V_{GE}=\pm 15V, R_{Gon}=36\Omega, R_{Goff}=36\Omega, T_J=125^{\circ}C$			10			μs	
$R_{\theta JC}$	Thermal Resistance: Junction-to-Case (per IGBT)					0.753	$^{\circ}C/W$	

Diode, Brake-Chopper

Maximum Rated Values ($T_C=25^\circ C$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	15	A
I_{FM}	Diode Maximum Forward Current	30	A



Electrical Characteristics of Diode ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =15A	T _J =25°C		1.90		V
			T _J =125°C		2.05		
			T _J =150°C		2.00		
t _{rr}	Reverse Recovery Time	I _F =15A, -diF/dt=344A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		154		ns
			T _J =125°C		159		
			T _J =150°C		206		
I _{rr}	Peak Reverse Recovery Current		T _J =25°C		7.8		A
			T _J =125°C		12.2		
			T _J =150°C		12.8		
Q _{rr}	Reverse Recovery Charge		T _J =25°C		0.83		μC
			T _J =125°C		1.22		
			T _J =150°C		1.47		
E _{rec}	Reverse Recovery Energy		T _J =25°C		0.10		mJ
			T _J =125°C		0.15		
			T _J =150°C		0.17		
R _{θJC}	Thermal Resistance: Junction-To-Case (per Diode)					1.127	°C/W

Diode, Rectifier

Maximum Rated Values ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	$T_J=25^{\circ}\text{C}$	1600	V
I_F	Diode Continuous Forward Current	$T_J=25^{\circ}\text{C}$	10	A
I_{FRMSM}	Maximum RMS Forward Current per Chip	$T_J=80^{\circ}\text{C}$	20	A
I_{RMSM}	Maximum RMS Current at Rectifier Output	$T_J=80^{\circ}\text{C}$	30	A
I_{FSM}	Surge Current @ $t_p=10\text{ms}$	$T_J=25^{\circ}\text{C}$	300	A
		$T_J=150^{\circ}\text{C}$	250	
I^2t	I^2t - value	$T_J=25^{\circ}\text{C}$	450	A^2s
		$T_J=150^{\circ}\text{C}$	312	



Electrical Characteristics of Diode ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

V_F	Forward Voltage	$I_F=10\text{ A}$	$T_J=25^{\circ}\text{C}$		1.05		V
			$T_J=150^{\circ}\text{C}$		1.00		
I_R	Reverse Current	$V_R=1600\text{V}$	$T_J=25^{\circ}\text{C}$			1	mA
$R_{\theta JC}$	Thermal Resistance: Junction-To-Case (per Diode)					0.944	$^{\circ}\text{C/W}$

Internal NTC-Thermistor Characteristics

R_{25}	$T_C=25^{\circ}\text{C}$	22.7		k Ω
$\Delta R/R$	$T_C=100^{\circ}\text{C}$, $R_{100}=1481\Omega$		± 3	%
P_{25}	$T_C=25^{\circ}\text{C}$	5		mW
$B_{25/50}$	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$	3950		K
$B_{25/80}$	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$	4000		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V_{iso}	Isolation Voltage (All Terminals Shorted)	RMS, f=50Hz, 30s	4500			V
T_J	Maximum Junction Temperature				175	$^{\circ}\text{C}$
T_{JOP}	Maximum Operating Junction Temperature Range		-40		+150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature		-40		+125	$^{\circ}\text{C}$
CTI	Comparative Tracking Index		200			
$R_{\theta CS}$	Case-To-Sink Thermally (Conductive Grease Applied)				0.09	$^{\circ}\text{C/W}$
T	Mounting Screw:M4		1.0		1.2	N·m
G	Weight			25		g







Ordering Information Table

Device code

G	T	15	PI	120	B2	H
①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Trench, Low Switching Losses IGBT
- ③ - Rated Current (15=15A)
- ④ - Circuit Configuration (Power Integrated)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)






Fig.5 Typical Switching Loss vs. Collector Current (Inverter)




Fig.6 Typical Switching Loss vs. Forward Current (Inverter)




Fig.7 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.8 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.9 Reverse Bias Safe Operation Area (RBSOA)




Fig.10 Capacitance Characteristics




Fig.11 Typical Saturation Voltage Characteristics (Brake-Chopper)




Fig.12 Forward Characteristics of Diode (Brake-Chopper)




Fig.13 Forward Characteristics of Diode (Rectifier Diode)




Fig.14 NTC Temperature Characteristics




Fig.15 Transient Thermal Impedance (IGBT)






Fig.16 Transient Thermal Impedance (Diode)



Internal Circuit



Package Outline (Unit: mm):





Date	Revision	Notes
11/08/2023	01	Initial Release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.