



GT15PI120C7H


IGBT Module

Preliminary Data

Features:

- Trench & Field Stop IGBT
- Short Circuit Rated $>10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested($2\times I_c$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Industrial Inverters
- Industrial Drivers

IGBT, Inverter

Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current	$T_C=100^\circ\text{C}$	15	A
		$T_C=25^\circ\text{C}$	30	A
I_{CM}	Repetitive Peak Collector Current	$t_p=1\text{ms}$	30	A
P_D	Maximum Power Dissipation per IGBT	$T_C=25^\circ\text{C}$, $T_{Jmax}=175^\circ\text{C}$	160	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=0.5\text{mA}$, $V_{CE}=V_{GE}$	5.0	5.8	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=15\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.80	2.20	V
			$T_J=125^{\circ}\text{C}$	2.15		V
			$T_J=150^{\circ}\text{C}$	2.25		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			200	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		1.02		nF
C_{oes}	Output Capacitance			0.11		nF
C_{res}	Reverse Transfer Capacitance			0.02		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		84		ns
			$T_J=125^{\circ}C$		92		
			$T_J=150^{\circ}C$		96		
t_r	Rise Time		$T_J=25^{\circ}C$		68		ns
			$T_J=125^{\circ}C$		78		
			$T_J=150^{\circ}C$		86		
$t_{d(off)}$	Turn-off Delay Time	$V_{CC}=600V, I_C=15A,$ $R_{Goff}=36\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		158		ns
			$T_J=125^{\circ}C$		168		
			$T_J=150^{\circ}C$		190		
t_f	Fall Time		$T_J=25^{\circ}C$		158		ns
			$T_J=125^{\circ}C$		214		
			$T_J=150^{\circ}C$		271		
E_{on}	Turn-on Switching Loss	$V_{CC}=600V, I_C=15A,$ $R_{Gon}=36\Omega, V_{GE}=\pm 15V,$ $di/dt=166A/\mu s(T_J=150^{\circ}C),$ Inductive Load	$T_J=25^{\circ}C$		2.13		mJ
			$T_J=125^{\circ}C$		2.49		
			$T_J=150^{\circ}C$		2.62		



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =15A, R _{Goff} =36Ω, V _{GE} =±15V, du/dt=4130V/μs(T _J =150°C), Inductive Load	T _J =25°C		1.28		mJ
			T _J =125°C		1.49		
			T _J =150°C		1.53		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		350		nC
R _{G(int)}	Internal Gate Resistance				0		Ω
I _{SC}	V _{CC} =600V, V _{GE} =±15V, t _p =10μs, T _J =25°C				55		A
R _{θJC}	Thermal Resistance: Junction-to-Case (per IGBT)					0.93	°C/W

FWD, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current		15	A
I _{FM}	Diode Maximum Forward Current	t _p =1ms	30	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =15A	T _J =25℃		1.70		V
			T _J =125℃		1.80		
			T _J =150℃		1.80		
t _{rr}	Reverse Recovery Time	I _F =15A, -diF/dt=130A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		306		ns
			T _J =125℃		538		
			T _J =150℃		602		
I _{rr}	Peak Reverse Recovery Current		T _J =25℃		10.9		A
			T _J =125℃		11.8		
			T _J =150℃		12.1		
Q _{rr}	Reverse Recovery Charge		T _J =25℃		2.1		μC
			T _J =125℃		3.3		
			T _J =150℃		3.6		



E _{rec}	Reverse Recovery Energy	I _F =15A, -diF/dt=130A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		0.54		mJ
			T _J =125℃		1.02		
			T _J =150℃		1.03		
R _{θJC}	Thermal Resistance: Junction-to-Case (per Diode)					1.62	℃/W

IGBT, Brake-Chopper

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{CES}	Collector-Emitter Blocking Voltage		1200	V
V _{GES}	Gate-Emitter Voltage		±20	V
I _C	Continuous Collector Current	T _C =100°C	15	A
		T _C =25°C	30	A
I _{CM}	Repetitive Peak Collector Current	t _p =1ms	30	A
P _D	Maximum Power Dissipation per IGBT	T _C =25°C, T _{Jmax} =175°C	160	W

Electrical Characteristics of IGBT (T_C=25°C unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{GE(th)}	Gate-Emitter Threshold Voltage	I _C =0.5mA, V _{CE} =V _{GE}		5.0	5.8	6.5	V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =15A, V _{GE} =15V	T _J =25°C		1.80	2.20	V
			T _J =125°C		2.15		V
			T _J =150°C		2.25		V
I _{CES}	Collector-Emitter Leakage Current	V _{GE} =0V, V _{CE} =V _{CES} , T _J =25°C				1	mA
I _{GES}	Gate-Emitter Leakage Current	V _{GE} =20V, V _{CE} =0V, T _J =25°C				200	nA
C _{ies}	Input Capacitance	V _{CE} =25V, V _{GE} =0V, f=100kHz			1.02		nF
C _{oes}	Output Capacitance				0.11		nF
C _{res}	Reverse Transfer Capacitance				0.02		nF



Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =15A, R _{Gon} =36Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		84		ns
			T _J =125℃		92		
			T _J =150℃		96		
t _r	Rise Time		T _J =25℃		68		ns
			T _J =125℃		78		
			T _J =150℃		86		
t _{d(off)}	Turn-off Delay Time	V _{CC} =600V, I _C =15A, R _{Goff} =36Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		158		ns
			T _J =125℃		168		
			T _J =150℃		190		
t _f	Fall Time		T _J =25℃		158		ns
			T _J =125℃		214		
			T _J =150℃		271		
E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =15A, R _{Gon} =36Ω, V _{GE} =±15V, di/dt=166A/μs(T _J =150℃), Inductive Load	T _J =25℃		2.13		mJ
			T _J =125℃		2.49		
			T _J =150℃		2.62		
E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =15A, R _{Goff} =36Ω, V _{GE} =±15V, du/dt=4130V/μs(T _J =150℃), Inductive Load	T _J =25℃		1.28		mJ
			T _J =125℃		1.49		
			T _J =150℃		1.53		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25℃		350		nC
R _{G(int)}	Internal Gate Resistance				0		Ω
I _{SC}	V _{CC} =600V, V _{GE} =±15V, tp=10μs, T _J =25℃				55		A
R _{θJC}	Thermal Resistance: Junction-to-Case (per IGBT)					0.93	℃/W

Diode, Brake-Chopper

Maximum Rated Values ($T_C=25^\circ C$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	$T_J=25^\circ C$	1200	V
I_F	Diode Continuous Forward Current		10	A
I_{FM}	Diode Maximum Forward Current	$t_p=1ms$	20	A



Electrical Characteristics of Diode ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =10A	T _J =25°C		1.70		V
			T _J =125°C		1.80		
			T _J =150°C		1.75		
t _{rr}	Reverse Recovery Time	I _F =10A, -diF/dt=176A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		217		ns
			T _J =125°C		241		
			T _J =150°C		256		
I _{rr}	Peak Reverse Recovery Current		T _J =25°C		7.4		A
			T _J =125°C		8.4		
			T _J =150°C		8.8		
Q _{rr}	Reverse Recovery Charge		T _J =25°C		0.7		μC
			T _J =125°C		0.8		
			T _J =150°C		0.9		
E _{rec}	Reverse Recovery Energy		T _J =25°C		0.17		mJ
			T _J =125°C		0.35		
			T _J =150°C		0.48		
R _{θJC}	Diode Thermal Resistance: Junction-to-Case(per Diode)					2.02	°C/W

Diode, Rectifier

Maximum Rated Values ($T_C=25^\circ\text{C}$ unless otherwise specified)

V_{RRM}	Repetitive Peak Reverse Voltage	$T_J=25^\circ\text{C}$	1800	V
I_{FRMSM}	Maximum RMS Forward Current per Chip	$T_C=80^\circ\text{C}$	20	A
I_{RMSM}	Maximum RMS Current at Rectifier Output	$T_C=80^\circ\text{C}$	30	A
I_{FSM}	Surge Current @ $t_p=10\text{ms}$	$T_J=25^\circ\text{C}$	300	A
		$T_J=150^\circ\text{C}$	245	
I^2t	I^2t - value	$T_J=25^\circ\text{C}$	450	A^2s
		$T_J=150^\circ\text{C}$	300	



Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _F	Forward Voltage	I _F =15A	T _J =25°C		1.15		V
			T _J =125°C		1.10		
I _R	Reverse Current	V _R =1600V	T _J =25°C			1	mA
R _{θJC}	Diode Thermal Resistance: Junction-to-Case (per Diode)					1.14	°C/W

Internal NTC-Thermistor Characteristics

Symbol	Conditions	Min.	Typ.	Max.	Units
R ₂₅	T _C =25°C		5		kΩ
ΔR/R	T _C =100°C, R ₁₀₀ =465Ω	-5		+5	%
P ₂₅	T _C =25°C			10	mW
B _{25/50}	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298.15K))]$		3380		K
B _{25/80}	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298.15K))]$		3440		K
B _{25/100}	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298.15K))]$		3545		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V _{iso}	Isolation Voltage (All Terminals Shorted)	f=50Hz, 60s	2500			V
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+125	°C
CTI	Comparative Tracking Index		225			
R _{θCS}	Case-To-Sink Thermally (Conductive Grease Applied)				0.05	°C/W
T	Mounting Screw:M4		1.5		2.0	N·m
G	Weight			31		g



Ordering Information Table

Device code	G	T	15	PI	120	C7	H
	①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Trench & Field Stop IGBT
- ③ - Rated Current (15=15A)
- ④ - Circuit Configuration (Power Integrated)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)




Fig.1 Typical Saturation Voltage Characteristics(Inverter)




Fig.2 Typical Output Characteristics (Inverter)




Fig.3 Transfer Characteristics(Inverter)




Fig.4 Forward Characteristics of Diode (Inverter)




Fig.5 Typical Switching Loss vs. Collector Current (Inverter)




Fig.6 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.7 Typical Switching Loss vs. Forward Current (Inverter)




Fig.8 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.9 Reverse Bias Safe Operation Area (RBSOA)




Fig.10 Capacitance Characteristics




Fig.11 Typical Saturation Voltage Characteristics (Brake-Chopper)




Fig.12 Forward Characteristics of Diode (Brake-Chopper)




Fig.13 Forward Characteristics of Diode (Rectifier)




Fig.14 Transient Thermal Impedance (Inverter-IGBT)




Fig.15 Transient Thermal Impedance (Inverter-Diode)






Fig.16 NTC Temperature Characteristics



Internal Circuit



Package Outline (Unit: mm):





Revision	Notes
01	Initial Release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.