


GT40FF120B3H

IGBT Module

Circuit Diagram


Features:

- $V_{CES}=1200V$ $I_C=40A$ Trench & Field Stop IGBT Module
- Short Circuit Capability
- Low Switching Loss
- 100% RBSOA Tested($2 \times I_C$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



Applications:

- Motor Drives
- Air Conditioning
- Servo Drives
- UPS



Type	Package	Marking
GT40FF120B3H	B3	GT40FF120B3H

IGBT, Inverter

Maximum Rated Values ($T_C=25^\circ C$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current Limited by T_{Jmax}	$T_C=100^\circ C$	40	A
		$T_C=25^\circ C$	80	A
I_{CM}	Peak Collector Current Repetitive	T_p limited by T_{Jmax}	80	A
P_D	Maximum Power Dissipation (IGBT)	$T_C=25^\circ C, T_{Jmax}=175^\circ C$	350	W

GT40FF120B3H

IGBT Module Datasheet



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.5\text{mA}$, $V_{CE}=V_{GE}$	5.0	5.8	6.6	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=40\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.85	2.25	V
			$T_J=125^{\circ}\text{C}$	2.26		V
			$T_J=175^{\circ}\text{C}$	2.45		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=1200\text{V}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			250	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		2.31		nF
C_{oes}	Output Capacitance			0.51		nF
C_{res}	Reverse Transfer Capacitance			0.04		nF

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC}=600V, I_C=40A,$ $R_{Gon}=20\Omega, V_{GE}=\pm 15V,$ Inductive Load	$T_J=25^{\circ}C$		48		ns
			$T_J=125^{\circ}C$		45		
			$T_J=175^{\circ}C$		45		
t_r	Rise Time		$T_J=25^{\circ}C$		35		ns
			$T_J=125^{\circ}C$		41		
			$T_J=175^{\circ}C$		45		
$t_{d(off)}$	Turn-off Delay Time		$T_J=25^{\circ}C$		175		ns
			$T_J=125^{\circ}C$		198		
			$T_J=175^{\circ}C$		211		
t_f	Fall Time	$T_J=25^{\circ}C$		156		ns	
		$T_J=125^{\circ}C$		202			
		$T_J=175^{\circ}C$		222			
E_{on}	Turn-on Switching Loss	$V_{CC}=600V, I_C=40A,$ $R_{Gon}=20\Omega, V_{GE}=\pm 15V,$ $di/dt=700A/\mu s(T_J=175^{\circ}C)$ Inductive Load	$T_J=25^{\circ}C$		4.8		mJ
		$T_J=125^{\circ}C$		5.9			
		$T_J=175^{\circ}C$		6.5			

GT40FF120B3H

IGBT Module Datasheet



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =40A, R _{Goff} =20Ω, V _{GE} =±15V, du/dt=6000V/μs(T _J =175°C) Inductive Load	T _J =25°C		2.5		mJ
			T _J =125°C		3.2		
			T _J =175°C		3.5		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		198		nC
T _{SC}	V _{CC} =600V, V _{GE} =±15V, T _J =175°C ^{note1}					10	us
R _{θJC}	IGBT Thermal Resistance: Junction-to-Case (per IGBT)					0.419	°C/W
R _{θCS}	IGBT Thermal Resistance: Case-to-Sink (per IGBT) (per IGBT, λ _{grease} = 1 W/(m • K))				0.715		°C/W

note1: Short circuit withstand time cannot exceed 10us under specified condition

Diode, Inverter

Maximum Rated Values of Diode (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current		40	A
I _{FM}	Diode Maximum Forward Current	t _p =1ms	80	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =40A	T _J =25°C		1.55	1.90	V
			T _J =125°C		1.60		
			T _J =175°C		1.57		
t _{rr}	Reverse Recovery Time	I _F =40A, -diF/dt=730A/μs(T _J =175°C), V _R =600V, V _{GE} =-15V	T _J =25°C		325		ns
			T _J =125°C		437		
			T _J =175°C		532		
I _{rr}	Peak Reverse Recovery Current		T _J =25°C		23		A
			T _J =125°C		25		
			T _J =175°C		26		
Q _{rr}	Reverse Recovery Charge		T _J =25°C		3.3		μC
			T _J =125°C		5.5		
			T _J =175°C		7.5		



GT40FF120B3H

IGBT Module Datasheet

E _{rec}	Reverse Recovery Energy	I _F =40A, -diF/dt=1100A/μs(T _J =175°C), V _R =600V, V _{GE} =-15V	T _J =25°C		0.96		mJ
			T _J =125°C		1.84		
			T _J =175°C		2.66		
R _{θJC}	Diode Thermal Resistance: Junction-to-Case (per Diode)					0.663	°C/W
R _{θCS}	Diode Thermal Resistance: Case-to-Sink (per Diode, λ _{grease} = 1 W/(m • K))				1.131		°C/W

Internal NTC-Thermistor Characteristics

Symbol	Conditions	Min.	Typ.	Max.	Units.
R ₂₅	T _C =25°C		5		kΩ
ΔR/R	T _C =100°C, R ₁₀₀ =465Ω	-5		+5	%
P ₂₅	T _C =25°C			10	mW
B _{25/50}	R ₂ =R ₂₅ exp[B _{25/50} (1/T ₂ -1/(298.15K))]		3380		K
B _{25/80}	R ₂ =R ₂₅ exp[B _{25/80} (1/T ₂ -1/(298.15K))]		3440		K
B _{25/100}	R ₂ =R ₂₅ exp[B _{25/100} (1/T ₂ -1/(298.15K))]		3545		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V _{iso}	Isolation Voltage (All Terminals Shorted)	RMS, f=50Hz, 60s	2500			V
T _J	Maximum Junction Temperature		-40		175	°C
T _{JOP}	Maximum Operating Junction Temperature Range ^{note2}		-40		150	°C
T _{stg}	Storage Temperature		-40		125	°C
CTI	Comparative Tracking Index		200			
T	Mounting Torque for solder pins	Screw M4--Mounting according to valid application note	1.5		1.8	N·m
G	Weight			23		g

note2: T_{JOP}> 150°C is only allowed for operation at overload conditions.

GT40FF120B3H

IGBT Module Datasheet



Ordering Information Table

Device code	G	T	40	FF	120	B3	H
	①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Field Stop Trench Gate IGBT
- ③ - Rated Current (40=40A)
- ④ - Circuit Configuration: FF(Full Bridge)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)



GT40FF120B3H

IGBT Module Datasheet

Characteristic diagram




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Transfer Characteristic




Fig.4 Forward Characteristics of Diode

GT40FF120B3H

IGBT Module Datasheet




Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Gate Resistance




Fig.7 Typical Switching Loss vs. Forward Current




Fig.8 Typical Switching Loss vs. Gate Resistance




Fig.9 Transient Thermal Impedance (IGBT)




Fig.10 Transient Thermal Impedance (Diode)




Fig.11 Capacitance Characteristics






Fig.12 Reverse Bias Safe Operation Area (RBSOA)



GT40FF120B3H


IGBT Module Datasheet




GT40FF120B3H

IGBT Module Datasheet

Internal Circuit:



Package Outline (Unit: mm):



GT40FF120B3H

IGBT Module Datasheet



Revision	Notes
A	Fina Datasheet Initial Release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.