



GT50FF120A1H-C


IGBT Module

Preliminary Data

Features:

- Field Stop Trench Gate IGBT
- Short Circuit Rated $>10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested($2\times I_c$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Motor Drives
- Air Conditioning
- Servo Drives
- UPS

IGBT, Inverter

Maximum Rated Values ($T_c=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Values	Units
V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_c	Continuous Collector Current	$T_c=100^\circ\text{C}$	50	A
		$T_c=25^\circ\text{C}$	100	A
I_{CM}	Repetitive Peak Collector Current	$t_p=1\text{ms}$	100	A
P_D	Maximum Power Dissipation per Leg	$T_c=25^\circ\text{C}$ $T_{Jmax}=175^\circ\text{C}$	470	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.7\text{mA}$, $V_{CE}=V_{GE}$	5.0	5.6	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=50\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.75	2.10	V
			$T_J=125^{\circ}\text{C}$	2.20		V
			$T_J=150^{\circ}\text{C}$	2.30		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			± 200	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		5.32		nF
C_{oes}	Output Capacitance			0.81		nF
C_{res}	Reveres Transfer Capacitance			0.34		nF

Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		58		ns	
			T _J =125℃		62			
			T _J =150℃		66			
t _r	Rise Time		T _J =25℃		36		ns	
			T _J =125℃		38			
			T _J =150℃		40			
t _{d(off)}	Turn-off Delay Time		V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		262		ns
				T _J =125℃		288		
				T _J =150℃		302		
t _f	Fall Time	T _J =25℃			170		ns	
		T _J =125℃			218			
		T _J =150℃			244			
E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, di/dt=1212A/μs(T _J =150℃), Inductive Load		T _J =25℃		2.7		mJ
		T _J =125℃			3.8			
		T _J =150℃			3.9			



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V, du/dt=5557V/μs(T _J =150°C), Inductive Load	T _J =25°C		3.7		mJ
			T _J =125°C		5.1		
			T _J =150°C		5.3		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		2850		nC
R _{g internal}	Internal Gate Resistor		T _J =25°C		3.0		Ω
I _{SC}	V _{CC} =600V, V _{GE} =+/-15V, t _p =10μs, T _J =150°C				209		A
R _{θJC}	Thermal Resistance: Junction-to-Case (per IGBT)					0.32	°C/W

Diode, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current	T _C =100°C	40	A
I _{FM}	Diode Maximum Forward Current	t _p =1ms	80	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =40A	T _J =25℃		1.70		V
			T _J =125℃		1.85		
			T _J =150℃		1.85		
I _{rr}	Peak Reverse Recovery Current	I _F =40A, di/dt=351A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		53.7		A
			T _J =125℃		62.5		
			T _J =150℃		63.8		
t _{rr}	Reverse Recovery Time		T _J =25℃		134		ns
			T _J =125℃		156		
			T _J =150℃		156		
Q _{rr}	Reverse Recovery Charge		T _J =25℃		4.13		μC
			T _J =125℃		6.00		
			T _J =150℃		6.12		




E _{rec}	Reverse Recovery Energy	I _F =40A, di/dt=351A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		1.04		mJ
			T _J =125°C		2.13		
			T _J =150°C		2.41		
R _{θJC}	Thermal Resistance: Junction-to-Case (per Diode)					0.66	°C/W

Module

Symbol	Description		Min.	Typ.	Max.	Units
V_{iso}	Isolation Voltage (All Terminals Shorted)	$f=50Hz$, 1minute	2500			V
T_J	Maximum Junction Temperature				175	$^\circ C$
T_{JOP}	Maximum Operating Junction Temperature Range		-40		+150	$^\circ C$
T_{stg}	Storage Temperature		-40		+125	$^\circ C$
CTI	Comparative Tracking Index		200			
$R_{\theta CS}$	Case-to-Sink Thermally (Conductive Grease Applied)				0.06	$^\circ C/W$
T	Mounting Screw:M3		0.75		1.20	N·m
G	Weight			30		g

Ordering Information Table



- ① - IGBT Module
- ② - Trench, Low Switching Losses IGBT
- ③ - Rated Current (50=50A)
- ④ - Circuit Configuration (Full Bridge)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)
- ⑧ - Internal Code




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Transfer Characteristic








Fig.4 Forward Characteristics of Diode






Fig.9 Capacitance Characteristics




Fig.10 Reverse Bias Safe Operation Area




Fig.11 Transient Thermal Impedance (IGBT)






Fig.12 Transient Thermal Impedance (Diode)



Internal Circuit



Package Outline (Unit: mm):





Revision	Notes
01	Initial Release

Announcements

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.