




GT50FF120T6H

IGBT Module

Features:

- Trench & Field Stop IGBT
- Short Circuit Rated > 10μs
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested (2×I_c)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Industrial Inverters
- Servo Applications

IGBT, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{CES}	Collector-Emitter Blocking Voltage	T _J =25°C	1200	V
V _{GES}	Gate-Emitter Voltage		±20	V
I _C	Continuous Collector Current	T _C =100°C	50	A
		T _C =25°C	100	A
I _{CM}	Peak Collector Current Repetitive	t _p =1ms	100	A
P _D	Maximum Power Dissipation per IGBT	T _C =25°C T _{Jmax} =175°C	391	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1\text{mA}$, $V_{CE}=V_{GE}$, $T_J=25^{\circ}\text{C}$	5.00	5.60	6.50	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=50\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.75	1.90	V
			$T_J=125^{\circ}\text{C}$	2.20		V
			$T_J=150^{\circ}\text{C}$	2.30		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=\pm 15\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			± 200	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		5.32		nF
C_{oes}	Output Capacitance			0.81		nF
C_{res}	Reveres Transfer Capacitance			0.34		nF

Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		92		ns
			T _J =125℃		92		
			T _J =150℃		96		
t _r	Rise Time		T _J =25℃		54		ns
			T _J =125℃		56		
			T _J =150℃		56		
t _{d(off)}	Turn-off Delay Time	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		222		ns
			T _J =125℃		272		
			T _J =150℃		256		
t _f	Fall Time		T _J =25℃		222		ns
			T _J =125℃		192		
			T _J =150℃		210		
E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, di/dt=767A/μs (T _J =150℃), Inductive Load	T _J =25℃		4.81		mJ
			T _J =125℃		6.16		
			T _J =150℃		7.48		



E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V, du/dt=4951V/μs (T _J =150°C), Inductive Load	T _J =25°C		3.76		mJ
			T _J =125°C		4.21		
			T _J =150°C		5.30		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		2850		nC
R _{g internal}	Internal Gate Resistance		T _J =25°C		3.4		Ω
SCSOA	V _{CC} =600V, V _{GE} =±15V, R _G =15Ω, T _J =150°C			10			μs
R _{θJC}	Thermal Resistance: Junction-To-Case (per IGBT)					0.384	°C/W

Diode, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current		50	A
I _{FM}	Repetitive Peak Forward Current	tp=1ms	100	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =50A	T _J =25℃		1.75		V
			T _J =125℃		1.85		
			T _J =150℃		1.85		
t _{rr}	Reverse Recovery Time	I _F =50A, -diF/dt=904A/μs(T _J =150℃), V _{rr} =600V, V _{GE} =-15V	T _J =25℃		290		ns
			T _J =125℃		524		
			T _J =150℃		542		
I _{rr}	Peak Reverse Recovery Current		T _J =25℃		38.6		A
			T _J =125℃		45.2		
			T _J =150℃		43.8		
Q _{rr}	Reverse Recovery Charge		T _J =25℃		5.7		μC
			T _J =125℃		10.3		
			T _J =150℃		11.1		



E _{rec}	Reverse Recovery Energy	I _F =50A, -diF/dt=904A/μs(T _J =150°C), V _{rr} =600V, V _{GE} =-15V	T _J =25°C		1.86		mJ
			T _J =125°C		3.83		
			T _J =150°C		4.09		
R _{θJC}	Thermal Resistance: Junction-To-Case (per Diode)					0.501	°C/W

Internal NTC-Thermistor Characteristics

R ₂₅	T _C =25°C	5		kΩ
ΔR/R	T _C =100°C, R ₁₀₀ =465Ω		±5	%
P ₂₅	T _C =25°C	10		mW
B _{25/50}	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15K))]$	3380		K
B _{25/80}	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15K))]$	3440		K
B _{25/100}	$R_2=R_{25} \exp[B_{25/100}(1/T_2-1/(298.15K))]$	3545		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V _{iso}	Isolation Voltage (All Terminals Shorted)	RMS, f=50Hz, t=30s	4500			V
M	Baseplate		Copper			
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+150	°C
CTI	Comparative Tracking Index		200			
R _{θCS}	Case-To-Sink Thermally (Conductive Grease Applied)				0.03	°C/W
T	Mounting Screw:M5		3.0		6.0	N·m
G	Weight			300		g



Ordering Information Table

Device code

G	T	50	FF	120	T6	H
①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Trench, Low Switching Losses IGBT
- ③ - Rated Current (50=50A)
- ④ - Circuit Configuration: FF (Full Bridge)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Transfer Characteristics (Inverter)




Fig.4 Forward Characteristics of Diode




Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Gate Resistance




Fig.7 Typical Switching Loss vs. Forward Current








Fig.8 Typical Switching Loss vs. Gate Resistance








Fig.13 NTC Temperature Characteristics




Internal Circuit:




Package Outline (Unit: mm)



View B
scale 3:1



View A
scale 3:1





Date	Revision	Notes
04/10/2024	A	Final Version

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.