



GT50RFF120T5H


IGBT Module

Preliminary Data

Features:

- Field Stop Trench Gate IGBT
- Short Circuit Rated $>10\mu\text{s}$
- Low Saturation Voltage
- Low Switching Loss
- 100% RBSOA Tested($2\times I_c$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement

Circuit Diagram



Applications:

- Industrial Inverters
- Servo Applications

IGBT, Inverter

Maximum Rated Values ($T_c=25^\circ\text{C}$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_c	Continuous Collector Current	$T_c=100^\circ\text{C}$	50	A
		$T_c=25^\circ\text{C}$	100	A
I_{CM}	Peak Collector Current Repetitive	$t_p=1\text{ms}$	100	A
P_D	Maximum Power Dissipation (IGBT)	$T_c=25^\circ\text{C}$ $T_{Jmax}=175^\circ\text{C}$	391	W



Electrical Characteristics of IGBT ($T_C=25^{\circ}\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Description	Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.7\text{mA}$, $V_{CE}=V_{GE}$	5.0	5.6	6.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=50\text{A}$, $V_{GE}=15\text{V}$	$T_J=25^{\circ}\text{C}$	1.75	2.10	V
			$T_J=125^{\circ}\text{C}$	2.20		
			$T_J=150^{\circ}\text{C}$	2.30		
I_{CES}	Collector-Emitter Leakage Current	$V_{GE}=0\text{V}$, $V_{CE}=V_{CES}$, $T_J=25^{\circ}\text{C}$			1	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$, $T_J=25^{\circ}\text{C}$			± 200	nA
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$		5.32		
C_{oes}	Output Capacitance			0.81		
C_{res}	Reveres Transfer Capacitance			0.34		

Switching Characteristics

t _{d(on)}	Turn-on Delay Time	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, Inductive Load	T _J =25℃		92		ns
			T _J =125℃		92		
			T _J =150℃		96		
t _r	Rise Time		T _J =25℃		54		ns
			T _J =125℃		56		
			T _J =150℃		56		
t _{d(off)}	Turn-off Delay Time		T _J =25℃		222		ns
			T _J =125℃		256		
			T _J =150℃		272		
t _f	Fall Time	T _J =25℃		192		ns	
		T _J =125℃		210			
		T _J =150℃		222			



E _{on}	Turn-on Switching Loss	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V, di/dt=767A/μs(T _J =150°C), Inductive Load	T _J =25°C		4.81		mJ
			T _J =125°C		6.16		
			T _J =150°C		7.48		
E _{off}	Turn-off Switching Loss	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V, du/dt=4951V/μs(T _J =150°C), Inductive Load	T _J =25°C		3.76		mJ
			T _J =125°C		4.21		
			T _J =150°C		5.30		
Q _g	Total Gate Charge	V _{GE} =+15V...-15V	T _J =25°C		2850		nC
R _{g internal}	Internal Gate Resistor		T _J =25°C		3.4		Ω
SCSOA	V _{CC} =600V, V _{GE} =±15V, t _p =10μs, R _{Gon} =47Ω, R _{Goff} =47Ω, T _J =150°C				209		A
R _{θJC}	Thermal Resistance: Junction-to-Case (per IGBT)					0.384	°C/W

Diode, Inverter

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1200	V
I _F	Diode Continuous Forward Current	T _C =100°C	50	A
I _{FM}	Diode Maximum Forward Current	t _p =1ms	100	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _{FM}	Forward Voltage	I _F =50A	T _J =25°C		1.75		V
			T _J =125°C		1.85		
			T _J =150°C		1.85		
t _{rr}	Reverse Recovery Time	I _F =50A, -diF/dt=904A/μs(T _J =150°C), V _R =600V, V _{GE} =-15V	T _J =25°C		290		ns
			T _J =125°C		524		
			T _J =150°C		542		
I _{rr}	Peak Reverse Recovery Current		T _J =25°C		38.6		A
			T _J =125°C		43.8		
			T _J =150°C		45.5		



Q _{rr}	Reverse Recovery Charge	I _F =50A, -diF/dt=904A/μs(T _J =150℃), V _R =600V, V _{GE} =-15V	T _J =25℃		5.7		μC
			T _J =125℃		10.3		
			T _J =150℃		11.1		
E _{rec}	Reverse Recovery Energy		T _J =25℃		1.86		mJ
			T _J =125℃		3.83		
			T _J =150℃		4.09		
R _{θJC}	Thermal Resistance: Junction-to-Case (per Diode)					0.501	℃/W

Diode, Rectifier

Maximum Rated Values (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	T _J =25°C	1800	V
I _{FRMSM}	Maximum RMS Forward Current per Chip	T _J =80°C	55	A
I _{RMSM}	Maximum RMS Current at Rectifier Output	T _J =80°C	65	A
I _{FSM}	Surge Current @t _p =10ms	T _J =25°C	630	A
		T _J =150°C	550	
I ² t	I ² t - value	T _J =25°C	1960	A ² s
		T _J =150°C	1500	

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions		Min.	Typ.	Max.	Units
V _F	Forward Voltage	I _F =35A	T _J =25°C		1.10		V
			T _J =125°C		1.05		
I _R	Reverse Current	V _R =1600V	T _J =25°C			1	mA
R _{θJC}	Diode Thermal Resistance: Junction-to-Case (per Diode)					0.56	°C/W



Internal NTC-Thermistor Characteristics

Symbol	Conditions	Min.	Typ.	Max.	Units
R ₂₅	T _C =25°C		5		kΩ
△R/R	T _C =100°C, R ₁₀₀ =465Ω	-5		5	%
P ₂₅	T _C =25°C			10	mW
B _{25/50}	$R_2=R_{25} \exp[B_{25/50}(1/T_2-1/(298.15K))]$		3380		K
B _{25/80}	$R_2=R_{25} \exp[B_{25/80}(1/T_2-1/(298.15K))]$		3440		K
B _{25/100}	$R_2=R_{25} \exp[B_{25/100}(1/T_2-1/(298.15K))]$		3545		K

Module

Symbol	Description		Min.	Typ.	Max.	Units
V _{iso}	Isolation Voltage (All Terminals Shorted)	RMS, f=50Hz, 30s	4500			V
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+150	°C
CTI	Comparative Tracking Index		200			
R _{θCS}	Case-to-Sink Thermally (Conductive Grease Applied)				0.04	°C/W
M	Mounting Screw:M5		3.0		6.0	N·m
G	Weight			190		g



Ordering Information Table

Device code

G	T	50	RFF	120	T5	H
①	②	③	④	⑤	⑥	⑦

- ① - IGBT Module
- ② - Trench, Low Switching Losses IGBT
- ③ - Rated Current (50=50A)
- ④ - Circuit Configuration: RFF (Rectifier +Full Bridge)
- ⑤ - Rated Voltage (120=1200V)
- ⑥ - Package Type
- ⑦ - Test Level (Pass the Important Reliability Test-Industrial Grade)




Fig.1 Typical Saturation Voltage Characteristics(Inverter)




Fig.2 Typical Output Characteristics(Inverter)




Fig.3 Transfer Characteristics(Inverter)




Fig.4 Forward Characteristics of Diode(Inverter)




Fig.5 Typical Switching Loss vs. Collector Current (Inverter)




Fig.6 Typical Switching Loss vs. Gate Resistance (Inverter)




Fig.7 Typical Switching Loss vs. Forward Current (Inverter)








Fig.8 Typical Switching Loss vs. Gate Resistance (Inverter)






Fig.13 Forward Characteristics of Diode (Rectifier)






Fig.14 NTC Temperature Characteristics



Internal Circuit



Package Outlines (Unit: mm):





Revision	Notes
01	Initial Release

Announcement

Information in this document is believed to be accurate and reliable. However, NJSME does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to Make Changes

NJSME reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

The datasheet with “REV.” + “Arabic numerals” is based on engineering data for initial reference purpose only.

The released datasheet would be issued with “REV.” + “alphabet characters”.