

Features:


- 1200V Trench & field stop technology
- Low switching losses
- High short circuit capability
- Positive Temperature coefficient
- Easy paralleling

Recommended for:

Low / medium power modules

Applications:

Low / medium power drives



Mechanical parameters

Die size	$L \times W$	3.8×3.42	mm ²
Emitter pad size	$L \times W$	See chip drawing	mm ²
Gate pad size	$L \times W$	1.092×0.608	mm ²
Silicon thickness		115	μm
Wafer size		200	mm
Maximum possible chips per wafer		2066	
Passivation frontside		Polyimide	
Pad Metallization	AlCu	4	μm
Backside Metallization	Al / Ti / Ni / Ag	1.7	μm

Maximum Ratings

Parameters	Symbol	Value	Unit
Collector-emitter voltage	V_{CE}	1200	V
DC collector current, limited by $T_{vj\ max}$	I_C	10 ¹	A
Pulsed collector current, t_p limited by $T_{vj\ max}$ ²	$I_{C\ puls}$	30	A
Gate-emitter voltage	V_{GE}	±20	V
Operating junction temperature	$T_{vj\ op}$	-40~175	°C
Storage temperature	T_{stg}	-40~150	°C
Short circuit data ³ ($V_{GE}=15V$, $V_{CC}=600V$, $T_{vj}=150^{\circ}C$)	t_{sc}	10	μs

Static Characteristic ($T_{vj}=25^{\circ}C$, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Collector-emitter breakdown voltage	$V_{(BR)CES}$	$V_{GE}=0V$, $I_C=1mA$	1200	-	-	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	$V_{GE}=15V$, $I_C=10A$	1.58	1.85	2.07	V
Gate-emitter threshold voltage	$V_{GE(th)}$	$I_C=0.35mA$, $V_{CE}=V_{GE}$	5.3	5.8	6.3	V
Collector-emitter leakage	I_{CES}	$V_{CE}=1200V$, $V_{GE}=0V$	-	-	2	μA
Gate-emitter leakage	I_{GES}	$V_{CE}=0V$, $V_{GE}=20V$	-	-	120	nA
Integrated gate resistor	R_{Gint}		none			Ω


¹ Depending on thermal properties of assembly.

² Not subject to production test - verified by design/characterization.

³ Allowed number of short circuit: <1000; time between short circuit: >1s.

Electrical Characteristic ¹

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Collector-emitter saturation voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=10A,$ $T_{vj}=150^{\circ}C$	-	2.25	-	V
Input capacitance	C_{ies}	$V_{CE}=25V$ $V_{GE}=0V, f=1MHz$	-	655	-	pF
Reverse transfer capacitance	C_{res}	$T_{vj}=25^{\circ}C$	-	13	-	pF

Chip Drawing (unit: μm)


¹ Not subject to production test - verified by design/characterization.

Disclaimer:

NJSM does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

NJSM reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

NJSM makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, NJSM disclaims (1) any and all liability arising out of the application or use of any product, (2) any and all liability, including without limitation special, consequential or incidental damages, and (3) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

NJSM products, except as expressly indicated in writing, are not designed for use in medical, life-saving, or life-sustaining applications, or for any other application in which the failure of the NJSM product could result in personal injury or death. Customers using or selling NJSM products not expressly indicated for use in such applications do so at their own risks.

Resale of NJSM products with statements different from or beyond the parameters stated by NJSM for that product or service voids all express or implied warranties for the associated NJSM product or service and is unfair and deceptive business practice. NJSM is not responsible or liable for any such statements.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of NJSM. Product names and markings noted herein may be trademarks of their respective owners.