NCE P-Channel Enhancement Mode Power MOSFET

Description

The NCE01P62D uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge. It can be used in a wide variety of applications.


General Features

- V_{DS} = -100 V,I_D = -62 A
  $R_{DS(on)}$ < 24 mΩ @ V_{GS}=-10V
  $R_{DS(on)}$ < 30 mΩ @ V_{GS}=-4.5V
- High density cell design for ultra low $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

Application

- Portable equipment and battery powered systems
- Power Switch
- DC/DC Converters

100% UIS TESTED!
100% ΔVds TESTED!



Schematic diagram



G D S

Marking and pin assignment



TO-263-2L Top View

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
NCE01P62D	NCE01P62D	TO-263-2L	Ø330mm	24mm	800units

Absolute Maximum Ratings (T_C=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-100	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	-62	A
Drain Current-Continuous(100℃)	I_D (100℃)	-45.7	A
Pulsed Drain Current (T_C=25℃)	I_{DM}	-250	A
Maximum Power Dissipation	P_D	220	W
Derating factor		1.47	W/℃
Single pulse avalanche energy(Note 1)	E_{AS}	615	mJ
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 175	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Case	$R_{\theta JC}$	0.68	℃/W
Thermal Resistance,Junction-to-Ambient (Note 2)	$R_{\theta JA}$	40	℃/W

Electrical Characteristics (T_C=25℃unless otherwise noted)


Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=-250μA	-100	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-100V,V_{GS}=0V	-	-	-1	uA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250μA	-1.3	-1.9	-2.5	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-20A	-	20	24	mΩ
		V_{GS}=-4.5V, I_D=-20A	-	21	30	
Forward Transconductance	g_{FS}	V_{DS}=-10V,I_D=-30A	-	77	-	S
Dynamic Characteristics						
Input Capacitance	C_{iss}	V_{DS}=-50V,V_{GS}=0V, F=1.0MHz	-	11313.5	-	pF
Output Capacitance	C_{oss}		-	294.1	-	pF
Reverse Transfer Capacitance	C_{rss}		-	238.3	-	pF
Switching Characteristics (Note 3)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=-50V,I_D=-20A, V_{GS}=-10V,R_{GEN}=3Ω	-	8	-	nS
Turn-on Rise Time	t_r		-	17	-	nS
Turn-off Delay Time	$t_{d(off)}$		-	153	-	nS
Turn-off Fall Time	t_f		-	55	-	nS
Total Gate Charge	Q_g	V_{DS}=-50V,I_D=-20A, V_{GS}=-10V	-	189	-	nC
Gate-Source Charge	Q_{gs}		-	27	-	nC
Gate-Drain Charge	Q_{gd}		-	26	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage	V_{SD}	V_{GS}=0V,I_S=-20A	-	-	-1.2	V
Diode Forward Current	I_S		-	-	-62	A
Reverse Recovery Time	t_{rr}	T_J = 25°C, I_F =-20A di/dt =-100A/μs	-	44	-	nS
Reverse Recovery Charge	Qrr		-	110	-	nC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

Notes:


1. EAS condition : Tj=25℃,V_{DD}=-30V,V_G=-10V,L=0.5mH,Rg=25Ω.
2. The value of $R_{\theta JA}$ is measured in a still air environment with T_A =25°C.The maximum allowed junction temperature of 175°C. The value in any given application depends on the user's specific board design.
3. Guaranteed by design, not subject to production.
4. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=175°C. The SOA curve provides a single pulse rating.

Test Circuit


1) E_{AS} Test Circuit



2) Gate Charge Test Circuit



3) Switch Time Test Circuit



Typical Electrical and Thermal Characteristics (Curves)




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Rdson vs Drain Current




Figure 4 Rdson vs Junction Temperature




Figure 5 Gate Charge




Figure 6 Source-Drain Diode Forward




Figure 7 Capacitance vs Vds




Figure 9 Power De-rating




Figure 8 Safe Operation Area(Note 4)




Figure10 Drain Current De-rating





Figure 11 Normalized Maximum Transient Thermal Impedance

TO-263-2L(P) Package Information



COMMON DIMENSIONS
(UNITS OF MEASURE =MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	4.40	4.50	4.60
A1	0	0.10	0.25
A2	2.20	2.40	2.60
b	0.76	---	0.89
b1	0.75	0.80	0.85
b2	1.23	---	1.37
b3	1.22	1.27	1.32
c	0.47	---	0.60
c1	0.46	0.51	0.56
c2	1.25	1.30	1.35
D	9.10	9.20	9.30
D1	8.00	---	---
E	9.80	9.90	10.00
E1	7.80	---	---
e	2.54 BSC		
H	14.90	15.30	15.70
L	2.00	2.30	2.60
L1	1.17	1.27	1.40
L2	---	---	1.75
L3	0.25BSC		
L4	4.60 REF		
θ	0°	---	8°
θ1	1°	3°	5°

Revision History

Revision	Date	Subjects
V1.0	2025.12	Initial test completed

Attention

- Any and all NCE power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your NCE power representative nearest you before using any NCE power products described or contained herein in such applications.
- NCE power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all NCE power products described or contained herein.
- Specifications of any and all NCE power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- NCE power CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all NCE power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of NCE power CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. NCE power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the NCE power product that you intend to use.
- This catalog provides information as of Dec.2025. Specifications and information herein are subject to change without notice.