SKM1200MLI12BE4



SEMITRANS® 10

IGBT4 Modules

SKM1200MLI12BE4

Features*

- High efficient MLI topology
- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- 1500V Solar inverters

Remarks*

- BOT-Switch
- Recommended T_{jop} = -40 … 150°C
- IGBT1 : outer IGBTs T1 & T4
- IGBT2 : inner IGBTs T2 & T3
- Diode1 : outer diodes D1 & D4
- Diode2 : inner diodes D2 & D3
- Diode5 : clamping diodes D5 & D6

Footnotes

[1)]Please find further technical information on the SEMIKRON website.

Absolute Maximum Ratings

Symbol	Conditions		Values	Unit
IGBT1				
V_{CES}	T_j = 25 °C		1200	V
I_C	T_j = 175 °C	T_c = 25 °C	2078	A
		T_c = 100 °C	1383	A
I_{Cnom}			1200	A
I_{CRM}			2400	A
V_{GES}			-20 ... 20	V
t_{psc}	V_{CC} = 800 V, V_{GE} ≤ 15 V, T_j = 150 °C, V_{CES} ≤1200 V		10	µs
T_j			-40 ... 175	°C
IGBT2				
V_{CES}	T_j = 25 °C		1200	V
I_C	T_j = 175 °C	T_c = 25 °C	2078	A
		T_c = 100 °C	1383	A
I_{Cnom}			1200	A
I_{CRM}			2400	A
V_{GES}			-20 ... 20	V
t_{psc}	V_{CC} = 800 V, V_{GE} ≤ 15 V, T_j = 150 °C, V_{CES} ≤ 1200 V		10	µs
T_j			-40 ... 175	°C
Diode1				
V_{RRM}	T_j = 25 °C		1200	V
I_F	T_j = 175 °C	T_c = 25 °C	1057	A
		T_c = 100 °C	676	A
I_{FRM}			1800	A
I_{FSM}	t_p = 10 ms, sin 180°, T_j = 25 °C		4128	A
T_j			-40 ... 175	°C
Diode2				
V_{RRM}	T_j = 25 °C		1200	V
I_F	T_j = 175 °C	T_c = 25 °C	1057	A
		T_c = 100 °C	676	A
I_{FRM}			1800	A
I_{FSM}	t_p = 10 ms, sin 180°, T_j = 25 °C		4128	A
T_j			-40 ... 175	°C
Diode5				
V_{RRM}	T_j = 25 °C		1200	V
I_F	T_j = 175 °C	T_c = 25 °C	1328	A
		T_c = 100 °C	848	A
I_{FRM}			2400	A
I_{FSM}	t_p = 10 ms, sin 180°, T_j = 25 °C		5280	A
T_j			-40 ... 175	°C
Module				
T_{stg}	module without TIM		-40 ... 150	°C
V_{isol}	AC sinus 50 Hz, t = 1 min		4000	V



MLI BOT-Switch



SEMITRANS® 10

IGBT4 Modules

SKM1200MLI12BE4

Features*

- High efficient MLI topology
- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- 1500V Solar inverters

Remarks*

- BOT-Switch
- Recommended T_{jop} = -40 … 150°C
- IGBT1 : outer IGBTs T1 & T4
- IGBT2 : inner IGBTs T2 & T3
- Diode1 : outer diodes D1 & D4
- Diode2 : inner diodes D2 & D3
- Diode5 : clamping diodes D5 & D6

Footnotes

[1)] Please find further technical information on the SEMIKRON website.



MLI BOT-Switch

Characteristics

Symbol	Conditions		min.	typ.	max.	Unit
IGBT1						
$V_{CE(sat)}$	I_C = 1200 A V_{GE} = 15 V chiplevel	T_j = 25 °C		1.80	2.05	V
		T_j = 150 °C		2.05	2.30	V
V_{CE0}	chiplevel	T_j = 25 °C		0.87	1.01	V
		T_j = 150 °C		0.77	0.90	V
r_{CE}	V_{GE} = 15 V chiplevel	T_j = 25 °C		0.78	0.87	mΩ
		T_j = 150 °C		1.07	1.17	mΩ
$V_{GE(th)}$	V_{GE} = V_{CE}, I_C = 44.4 mA		5.1	5.8	6.3	V
I_{CES}	V_{GE} = 0 V, V_{CE} = 1200 V, T_j = 25 °C				5	mA
C_{ies}	V_{CE} = 25 V V_{GE} = 0 V	f = 1 MHz		75.0		nF
C_{oes}		f = 1 MHz		7		nF
C_{res}		f = 1 MHz		4.08		nF
Q_G	V_{GE} = - 8 V...+ 15 V			6900		nC
R_{Gint}	T_j = 25 °C			0.9		Ω
$t_{d(on)}$	V_{CC} = 600 V I_C = 1200 A V_{GE} = +15/-15 V $R_{G\ on}$ = 1 Ω $R_{G\ off}$ = 2 Ω di/dt_{on} = 15500 A/µs di/dt_{off} = 7500 A/µs dv/dt = 3300 V/µs	T_j = 150 °C		249		ns
t_r		T_j = 150 °C		83		ns
E_{on}		T_j = 150 °C		108		mJ
$t_{d(off)}$		T_j = 150 °C		887		ns
t_f		T_j = 150 °C		130		ns
E_{off}		T_j = 150 °C		189		mJ
$R_{th(j-c)}$	per IGBT				0.021	K/W
$R_{th(c-s)}$	per IGBT (λgrease= 0.81 W/(m*K))			0.0137		K/W
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			-		K/W
IGBT2						
$V_{CE(sat)}$	I_C = 1200 A V_{GE} = 15 V chiplevel	T_j = 25 °C		1.80	2.05	V
		T_j = 150 °C		2.05	2.30	V
V_{CE0}	chiplevel	T_j = 25 °C		0.87	1.01	V
		T_j = 150 °C		0.77	0.90	V
r_{CE}	V_{GE} = 15 V chiplevel	T_j = 25 °C		0.78	0.87	mΩ
		T_j = 150 °C		1.07	1.17	mΩ
$V_{GE(th)}$	V_{GE} = V_{CE}, I_C = 44.4 mA		5.1	5.8	6.3	V
I_{CES}	V_{GE} = 0 V, V_{CE} = 1200 V, T_j = 25 °C				5	mA
C_{ies}	V_{CE} = 25 V V_{GE} = 0 V	f = 1 MHz		75.0		nF
C_{oes}		f = 1 MHz		7		nF
C_{res}		f = 1 MHz		4.08		nF
Q_G	V_{GE} = - 8 V...+ 15 V			6900		nC
R_{Gint}	T_j = 25 °C			0.9		Ω
$t_{d(on)}$	V_{CC} = 600 V I_C = 1200 A V_{GE} = +15/-15 V $R_{G\ on}$ = 1 Ω $R_{G\ off}$ = 5.1 Ω di/dt_{on} = 6400 A/µs di/dt_{off} = 7600 A/µs dv/dt = 2000 V/µs	T_j = 150 °C		422		ns
t_r		T_j = 150 °C		162		ns
E_{on}		T_j = 150 °C		101		mJ
$t_{d(off)}$		T_j = 150 °C		1544		ns
t_f		T_j = 150 °C		155		ns
E_{off}		T_j = 150 °C		238		mJ
$R_{th(j-c)}$	per IGBT				0.021	K/W
$R_{th(c-s)}$	per IGBT (λgrease= 0.81 W/(m*K))			0.0137		K/W
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			-		K/W

 © by SEMIKRON

SKM1200MLI12BE4



SEMITRANS® 10

IGBT4 Modules

SKM1200MLI12BE4

Features*

- High efficient MLI topology
- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- 1500V Solar inverters

Remarks*

- BOT-Switch
- Recommended T_{jop} = -40 … 150°C
- IGBT1 : outer IGBTs T1 & T4
- IGBT2 : inner IGBTs T2 & T3
- Diode1 : outer diodes D1 & D4
- Diode2 : inner diodes D2 & D3
- Diode5 : clamping diodes D5 & D6

Footnotes

[1)]Please find further technical information on the SEMIKRON website.



MLI BOT-Switch

Characteristics

Symbol	Conditions		min.	typ.	max.	Unit
Diode1						
$V_F = V_{EC}$	I_F = 1200 A V_{GE} = 0 V chiplevel	T_j = 25 °C		2.46	2.82	V
		T_j = 150 °C		2.51	2.86	V
V_{F0}	chiplevel	T_j = 25 °C		1.30	1.50	V
		T_j = 150 °C		0.90	1.10	V
r_F	chiplevel	T_j = 25 °C		0.97	1.10	mΩ
		T_j = 150 °C		1.34	1.47	mΩ
I_{RRM}	I_F = 1200 A di/dt_{off} = 6400 A/µs V_{CC} = 600 V V_{GE} = +15/-15 V	T_j = 150 °C		595		A
Q_{rr}		T_j = 150 °C		127		µC
E_{rr}		T_j = 150 °C		76		mJ
$R_{th(j-c)}$	per diode				0.057	K/W
$R_{th(c-s)}$	per Diode (λgrease= 0.81 W/(m*K))			0.0178		K/W
$R_{th(c-s)}$	per Diode, pre-applied phase change material			-		K/W
Diode2						
$V_F = V_{EC}$	I_F = 1200 A V_{GE} = 0 V chiplevel	T_j = 25 °C		2.46	2.82	V
		T_j = 150 °C		2.51	2.86	V
V_{F0}	chiplevel	T_j = 25 °C		1.30	1.50	V
		T_j = 150 °C		0.90	1.10	V
r_F	chiplevel	T_j = 25 °C		0.97	1.10	mΩ
		T_j = 150 °C		1.34	1.47	mΩ
I_{RRM}	I_F = 1200 A di/dt_{off} = 6400 A/µs V_R = 600 V V_{GE} = +15/-15 V	T_j = 150 °C		595		A
Q_{rr}		T_j = 150 °C		127		µC
E_{rr} [1)]		T_j = 150 °C		-		mJ
$R_{th(j-c)}$	per diode				0.057	K/W
$R_{th(c-s)}$	per Diode (λgrease= 0.81 W/(m*K))			0.0178		K/W
$R_{th(c-s)}$	per Diode, pre-applied phase change material			-		K/W
Diode5						
$V_F = V_{EC}$	I_F = 1200 A	T_j = 25 °C		2.20	2.52	V
	chiplevel	T_j = 150 °C		2.15	2.47	V
V_{F0}	chiplevel	T_j = 25 °C		1.30	1.50	V
		T_j = 150 °C		0.90	1.10	V
r_F	chiplevel	T_j = 25 °C		0.75	0.85	mΩ
		T_j = 150 °C		1.04	1.14	mΩ
I_{RRM}	I_F = 1200 A di/dt_{off} = 15500 A/µs V_R = 600 V V_{GE} = +15/-15 V	T_j = 150 °C		1022		A
Q_{rr}		T_j = 150 °C		194		µC
E_{rr}		T_j = 150 °C		96		mJ
$R_{th(j-c)}$	per diode				0.046	K/W
$R_{th(c-s)}$	per Diode (λgrease= 0.81 W/(m*K))			0.0164		K/W
$R_{th(c-s)}$	per Diode, pre-applied phase change material			-		K/W



SEMITRANS® 10

IGBT4 Modules

SKM1200MLI12BE4

Features*

- High efficient MLI topology
- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- 1500V Solar inverters

Remarks*

- BOT-Switch
- Recommended T_{jop} = -40 … 150°C
- IGBT1 : outer IGBTs T1 & T4
- IGBT2 : inner IGBTs T2 & T3
- Diode1 : outer diodes D1 & D4
- Diode2 : inner diodes D2 & D3
- Diode5 : clamping diodes D5 & D6

Footnotes

[1)]Please find further technical information on the SEMIKRON website.

Characteristics

Symbol	Conditions		min.	typ.	max.	Unit
Module						
L_{sCE1}				10		nH
L_{sCE2}				50		nH
$R_{CC'+EE'}$	measured per switch	T_C = 25 °C		0.1		mΩ
		T_C = 125 °C		0.15		mΩ
$R_{th(c-s)1}$	calculated without thermal coupling (λ_{grease}=0.81 W/(m*K))			0.0031		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module (λ_{grease}=0.81 W/(m*K))			0.005		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, pre-applied phase change material			-		K/W
M_s	to heat sink M5		4		6	Nm
M_t		to terminals M8	8		10	Nm
		to terminals M4	1.8		2.1	Nm
w					1250	g
Temperature Sensor						
R_{100}	T_c=100°C (R_{25}=5 kΩ)			493 ± 5%		Ω
$B_{100/125}$	$R_{(T)}=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; T[K];			3550 ±2%		K



MLI BOT-Switch

 © by SEMIKRON



Fig. 1: Typ. IGBT1 output characteristics $I_C=f(V_{CE})$, V_{GE}=15V (chiplevel)



Fig. 2: Typ. IGBT1 output characteristics $I_C=f(V_{CE})$, T_j=150°C (chiplevel)



Fig. 3: Typ. IGBT1 switching losses $E=f(I_C)$



Fig. 4: Typ. IGBT1 switching losses $E=f(R_G)$



Fig. 5: Typ. Diode5 forward characteristics $I_F=f(V_F)$ (chiplevel)



Fig. 6: Typ. Diode5 switching losses $E=f(I_F)$



Fig. 7: Typ. Diode5 switching losses E=f(R_G)



Fig. 8: IGBT1 transient thermal impedance



Fig. 9: Diode5 transient thermal impedance



Fig. 10: RBSOA IGBT1



Fig. 11: RBSOA Diode5



Fig. 12: Typ. IGBT2 output characteristics I_C=f(V_{CE}), V_{GE}=15V (chiplevel)

 © by SEMIKRON



Fig. 13: Typ. IGBT2 output characteristics $I_C=f(V_{CE})$, T_j=150°C (chiplevel)



Fig. 14: Typ. IGBT2 switching losses $E=f(I_C)$



Fig. 15: Typ. IGBT2 switching losses $E=f(R_G)$



Fig. 16: Typ. Diode1 forward characteristics $I_F=f(V_F)$ (chiplevel)



Fig. 17: Typ. Diode1 switching losses $E=f(I_F)$



Fig. 18: Typ. Diode1 switching losses $E=f(R_G)$



Fig. 19: IGBT2 transient thermal impedance



Fig. 20: Diode1 transient thermal impedance



Fig. 21: RBSOA IGBT2



Fig. 22: RBSOA Diode1



Fig. 23: Typ. Diode2 forward characteristics $I_F=f(V_F)$ (chiplevel)



Fig. 24: Diode2 transient thermal impedance

 © by SEMIKRON



Fig. 25: RBSOA Diode2



Fig. 26: Typ. NTC characteristics



- Dimensions in mm
- General tolerances ±0,5mm

SEMITRANS 10



BOT MLI

 © by SEMIKRON

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.